


Lichttechnischer Prüfbefund

Familie Floodlight FL11	Bestell-Nr.: 5XA779524Q01AA EAN: 4058352847695	LP-Nummer 59465_36
-----------------------------------	---	------------------------------

Kegelmantelkurven in cd/klm KMK 0° siteco



Lichttechnischer Prüfbefund

Familie Floodlight FL11	Bestell-Nr.: 5XA779524Q01AA EAN: 4058352847695	LP-Nummer 59465_36
-----------------------------------	---	------------------------------

Wertetabelle Lichtstärkemessung	Maximale Lichtstärke	siteco
--	-----------------------------	---------------

C- Ebenen	0° 180°	5°	10°	15°	20°	25°	30°	35°	40°	45°	
		175° 185° 355°	170° 190° 350°	165° 195° 345°	160° 200° 340°	155° 205° 335°	150° 210° 330°	145° 215° 325°	140° 220° 320°	135° 225° 315°	
γ		Lichtstärke in cd/klm									
0,0°	28210.3	28210.3	28210.3	28210.3	28210.3	28210.3	28210.3	28210.3	28210.3	28210.3	
0,5°	27726.4	27992.9	27732.1	27998.7	27737.9	27998.7	27806.6	28024.5	27769.4	28041.7	
1,0°	27422.6	27414.0	27448.4	27422.6	27457.0	27425.5	27474.2	27448.4	27497.1	27459.9	
1,5°	26299.1	26233.2	26310.6	26230.3	26293.4	26233.2	26307.7	26247.5	26304.8	26241.8	
2,0°	24825.9	24522.1	24828.8	24519.3	24814.5	24522.1	24817.3	24530.7	24820.2	24507.8	
3,0°	20807.7	20566.9	20773.3	20544.0	20764.7	20532.6	20779.0	20509.6	20704.5	20446.6	
4,0°	16330.9	15663.1	16276.4	15645.9	16276.4	15654.5	16279.3	15640.2	16219.1	15562.8	
5,0°	11768.1	11581.8	11791.0	11587.5	11822.6	11636.3	11854.1	11639.1	11831.2	11587.5	
6,0°	8292.1	8219.9	8314.2	8256.9	8373.5	8328.5	8438.6	8383.8	8459.2	8324.2	
7,0°	5582.5	5471.9	5600.0	5524.1	5688.9	5639.0	5786.3	5693.7	5780.9	5655.3	
8,0°	3591.2	3538.2	3625.9	3604.7	3746.5	3755.1	3895.3	3890.4	3964.4	3889.8	
9,0°	2245.3	2224.9	2278.2	2284.3	2371.7	2403.5	2516.7	2564.6	2651.1	2631.9	
10,0°	1313.2	1276.5	1338.2	1349.3	1427.9	1501.0	1557.7	1589.8	1666.3	1658.6	
15,0°	153.9	151.5	153.7	151.9	156.5	156.8	163.2	163.9	170.4	168.4	
20,0°	72.2	70.0	71.4	68.3	69.2	66.5	67.8	65.4	67.4	65.1	
30,0°	34.1	34.1	34.1	33.8	33.0	33.3	33.6	33.3	33.1	33.0	
45,0°	34.6	33.0	33.8	34.0	33.6	32.5	32.0	31.3	31.1	31.4	
60,0°	22.8	23.3	24.9	26.3	21.8	19.9	18.9	18.6	19.2	19.1	
75,0°	10.0	9.2	8.5	8.2	8.6	8.9	8.8	8.1	8.3	8.2	
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Lichttechnischer Prüfbefund

Familie Floodlight FL11	Bestell-Nr.: 5XA779524Q01AA EAN: 4058352847695	LP-Nummer 59465_36
-----------------------------------	---	------------------------------



Wertetabelle Lichtstärkemessung	Maximale Lichtstärke
--	-----------------------------

C- Ebenen	50°	55°	60°	65°	70°	75°	80°	85°	90°	Phi-Zone	Summe Phi-Zone
	130°	125°	120°	115°	110°	105°	100°	95°			
	230°	235°	240°	245°	250°	255°	260°	265°			
	310°	305°	300°	295°	290°	285°	280°	275°			
γ	Lichtstärke in cd/klm									Lichtstrom in lm/klm	
0,0°	28210.3	28210.3	28210.3	28210.3	28210.3	28210.3	28210.3	28210.3	28210.3	1.7	1.7
0,5°	27786.6	28067.5	27806.6	28093.3	27849.6	28119.0	27869.7	28127.6	27881.2	13.4	15.0
1,0°	27508.6	27479.9	27534.4	27500.0	27563.0	27520.0	27586.0	27525.8	27606.0	26.3	41.4
1,5°	26276.2	26244.6	26313.4	26250.4	26299.1	26253.2	26310.6	26244.6	26310.6	37.7	79.1
2,0°	24780.1	24487.7	24794.4	24464.8	24774.3	24447.6	24765.7	24433.3	24757.1	75.2	154.2
3,0°	20650.1	20377.8	20578.4	20309.0	20532.6	20248.8	20483.8	20223.0	20498.2	117.9	272.1
4,0°	16150.3	15462.5	16024.2	15319.2	15909.6	15175.9	15815.0	15135.7	15809.3	120.8	392.9
5,0°	11742.3	11438.5	11553.1	11243.6	11372.6	11108.9	11240.7	11011.5	11229.3	110.2	503.1
6,0°	8299.9	8174.0	8239.1	7966.3	8043.3	7775.1	7897.2	7682.8	7869.1	93.8	596.9
7,0°	5698.3	5534.7	5550.7	5338.6	5313.1	5085.6	5105.3	4937.1	5017.9	73.3	670.2
8,0°	3904.7	3783.2	3740.8	3552.5	3466.2	3283.9	3249.3	3152.1	3198.0	55.5	725.6
9,0°	2617.3	2503.8	2416.7	2267.6	2190.8	2085.1	2056.4	2005.7	2022.3	40.2	765.9
10,0°	1658.6	1560.9	1502.1	1391.0	1340.3	1263.2	1226.7	1184.2	1181.6	89.8	855.6
15,0°	168.9	158.6	154.8	146.8	144.7	139.0	139.0	135.4	137.1	21.8	877.4
20,0°	66.6	64.0	65.5	63.5	65.0	63.1	65.0	63.3	65.2	19.8	897.2
30,0°	33.1	33.2	33.5	33.1	32.6	32.6	32.6	32.7	32.7	23.6	920.8
45,0°	31.1	30.9	31.1	31.2	31.6	31.8	31.5	30.8	31.6	37.1	957.9
60,0°	19.1	18.6	18.5	18.2	18.0	21.1	20.5	19.4	19.2	28.9	986.8
75,0°	8.0	7.6	8.3	8.3	8.0	7.6	7.7	8.2	8.7	13.2	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Lichttechnischer Prüfbefund

Familie
Floodlight FL11

Bestell-Nr.: 5XA779524Q01AA
EAN: 4058352847695

LP-Nummer
59465_36

Dimmstufen-Tabelle

Umgebungstemperatur: 10°C

siteco

Lichtstrom [%]	Dimmstufe linear	Lichtstrom [lm]	Systemleistung [W]
100	255	139160	1334.7
95	235	132387	1226.5
90	217	125348	1129.2
85	201	118317	1043.2
80	185	111497	956.9
75	170	104475	876.6
70	157	97562	807.7
65	143	90515	734.2
60	130	83589	666.3
55	118	76257	604.3
50	104	69492	531.4
45	93	62510	475.0
40	82	55881	419.1
35	71	49021	362.6
30	60	41817	307.0
25	49	35182	251.7
20	39	27998	202.4
15	28	20563	148.6
10	19	13982	104.3
5	9	6982	56.1
1	2	1885	20.5

Dimmstufen-Tabelle

Umgebungstemperatur: 25°C

Lichtstrom [%]	Dimmstufe linear	Lichtstrom [lm]	Systemleistung [W]
100	----	----	----
95	----	----	----
90	213	119643	1099.8
85	197	113056	1014.0
80	181	106278	928.2
75	166	99727	848.6
70	152	93063	775.0
65	139	86402	707.2
60	126	79505	640.3
55	115	73177	582.0
50	101	66434	510.9
45	90	59622	455.3
40	79	53076	399.7
35	68	46417	343.7
30	58	39806	293.8
25	47	33023	239.3
20	37	26380	190.5
15	27	19664	141.9
10	18	13412	98.2
5	9	6919	55.5
1	2	1870	20.2

Lichttechnischer Prüfbefund

Familie Floodlight FL11	Bestell-Nr.: 5XA779524Q01AA EAN: 4058352847695	LP-Nummer 59465_36
-----------------------------------	---	-------------------------------------

Lichtstrom-Tabelle	siteco
---------------------------	---------------

Temperatur °C	Lichtstrom lm	Systemleistung W
10.0	139160.0	1334.7
25.0	120230.0	1109.4