




Photometric test report

Family Rondel 31	Order number: 51WC10MB34A EAN: 4058352616970	LP number 59345_28
	Version enclosure, PC, transparent, opal, diffuse beam	serial documentation 18.11.2022
	Lamps LED 3000 K CRI ≥ 80	
	Controlgear ECG Multilumen	
	Rated values <ul style="list-style-type: none"> Net luminous flux = 4250 lm Power consumption = 34.0 W Luminous efficacy = 125 lm/W 	
		

Luminous intensity in cd/klm C180-0 **Imax: 297 cd/klm**



Classifications	
DIN 5040	A 4 1
CIE	N1=44 N2=75 N3=94 N4=94 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	94.2%
ϕ_o	5.8%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Rondel 31	Order number: 51WC10MB34A EAN: 4058352616970	LP number 59345_28
----------------------------	---	------------------------------

Table of values for luminous intensities	Maximum luminous intensity	siteco
---	-----------------------------------	---------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	296.8	1.8	1.8
5°	296.7	14.2	15.9
10°	293.8	28.0	43.9
15°	288.9	41.0	84.9
20°	281.8	52.8	137.7
25°	272.6	63.1	200.9
30°	261.1	71.6	272.4
35°	247.5	77.8	350.2
40°	231.8	81.7	431.9
45°	214.2	83.0	514.9
50°	194.6	81.7	596.6
55°	173.0	77.7	674.3
60°	149.9	71.1	745.5
65°	125.1	62.1	807.6
70°	99.2	51.1	858.7
75°	72.7	38.5	897.2
80°	47.5	25.7	922.8
85°	26.9	14.7	937.5
90°	16.1	8.8	946.3
95°	14.2	7.7	954.1
100°	13.7	7.4	961.5
105°	13.1	7.0	968.4
110°	12.4	6.4	974.8
115°	11.6	5.8	980.6
120°	10.4	4.9	985.5
125°	9.0	4.0	989.6
130°	7.6	3.2	992.7
135°	6.1	2.4	995.1
140°	4.9	1.7	996.8
145°	3.8	1.2	998.0
150°	2.9	0.8	998.8
155°	2.2	0.5	999.3
160°	1.6	0.3	999.6
165°	1.3	0.2	999.8
170°	1.2	0.1	999.9
175°	1.2	0.1	1000.0
180°	1.2	0.0	1000.0

Photometric test report

Family Rondel 31	Order number: 51WC10MB34A EAN: 4058352616970	LP number 59345_28
----------------------------	---	------------------------------

UGR-Table		Standard room									
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	18.8	20.5	19.1	20.8	21.2	18.8	20.5	19.1	20.8	21.2
	3H	20.5	22.1	20.9	22.4	22.8	20.5	22.1	20.9	22.4	22.8
	4H	21.2	22.7	21.6	23.0	23.4	21.2	22.7	21.6	23.0	23.4
	6H	21.7	23.1	22.2	23.5	23.9	21.7	23.1	22.2	23.5	23.9
	8H	22.0	23.3	22.4	23.6	24.0	22.0	23.3	22.4	23.6	24.0
	12H	22.1	23.3	22.6	23.7	24.2	22.1	23.3	22.6	23.7	24.2
4H	2H	19.6	21.1	20.0	21.4	21.8	19.6	21.1	20.0	21.4	21.8
	3H	21.5	22.8	21.9	23.1	23.5	21.5	22.8	21.9	23.1	23.5
	4H	22.3	23.5	22.7	23.9	24.3	22.3	23.5	22.7	23.9	24.3
	6H	23.0	24.0	23.4	24.4	24.9	23.0	24.0	23.4	24.4	24.9
	8H	23.2	24.1	23.7	24.6	25.1	23.2	24.1	23.7	24.6	25.1
	12H	23.4	24.3	23.9	24.7	25.2	23.4	24.3	23.9	24.7	25.2
8H	4H	22.7	23.6	23.1	24.0	24.5	22.7	23.6	23.1	24.0	24.5
	6H	23.5	24.2	24.0	24.7	25.2	23.5	24.2	24.0	24.7	25.2
	8H	23.8	24.5	24.3	25.0	25.5	23.8	24.5	24.3	25.0	25.5
	12H	24.1	24.7	24.6	25.2	25.7	24.1	24.7	24.6	25.2	25.7
12H	4H	22.7	23.6	23.2	24.0	24.5	22.7	23.6	23.2	24.0	24.5
	6H	23.6	24.3	24.1	24.7	25.2	23.6	24.3	24.1	24.7	25.2
	8H	23.9	24.5	24.5	25.0	25.6	23.9	24.5	24.5	25.0	25.6

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 480	H(C0) = 30 H(C90) = 30	H(C180) = 30 H(C270) = 30
------------------------	---------------------------------	---------------------------------------	---------------------------	------------------------------


C-planes	0°
γ	Luminance in cd/m ²
45°	6588.9
50°	6492.8
55°	6361.8
60°	6186.4
65°	5937.0
70°	5588.9
75°	5085.1
80°	4430.3
85°	3789.3

Photometric test report

Family Rondel 31	Order number: 51WC10MB34A EAN: 4058352616970	LP number 59345_28
-----------------------------------	---	-------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°



Photometric test report

Family Rondel 31	Order number: 51WC10MB34A EAN: 4058352616970	LP number 59345_28
----------------------------	---	------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting		Luminous flux [lm]	Power consumption [W]
	1	2		
3	ON	ON	4250	34.0
2	ON	OFF	4070	32.5
1	OFF	ON	3850	30.5
0	OFF	OFF	3600	28.5