




Photometric test report

Family DUS® 31	Order number: 53BD812M1V4085 EAN: 4058352421741	LP number 59062_9
	Version diffuser optic, frosted, wide distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG Multilumen Rated values Net luminous flux = 8950 lm Power consumption = 59.6 W Luminous efficacy = 150.2 lm/W	serial documentation 01.09.2020
		

Luminous intensity in cd/klm **C180-0** **C270-90** **Imax: 303 cd/klm**



Classifications	
DIN 5040	A 4 1
CIE	N1=47 N2=80 N3=95 N4=92 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	92.2%
ϕ_o	7.8%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family DUS® 31	Order number: 53BD812M1V4085 EAN: 4058352421741	LP number 59062_9
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	301.3	301.3	301.3	301.3	301.3	301.3	301.3	1.8	1.8
5°	303.4	302.1	299.8	300.7	301.4	300.9	301.0	14.4	16.2
10°	301.2	300.2	298.0	298.8	298.8	297.4	296.9	28.4	44.6
15°	294.6	294.0	291.7	292.8	293.3	291.0	289.8	41.5	86.1
20°	290.9	289.9	285.2	284.3	284.4	281.8	279.7	53.5	139.6
25°	292.2	290.5	282.4	276.3	273.3	269.6	266.6	64.5	204.1
30°	297.0	294.4	282.2	270.2	261.0	254.7	250.5	74.7	278.9
35°	298.1	296.1	282.7	264.8	248.2	237.3	231.4	83.5	362.4
40°	283.7	283.9	275.8	257.5	234.7	217.8	209.8	89.0	451.4
45°	251.1	253.7	254.1	243.4	219.0	195.8	185.6	89.4	540.8
50°	211.2	214.3	220.3	219.1	199.3	172.1	159.4	84.7	625.6
55°	171.8	174.4	181.0	185.6	174.0	146.8	132.6	75.9	701.4
60°	135.8	137.5	141.9	147.8	143.1	120.2	106.0	64.2	765.6
65°	104.0	105.0	107.3	111.5	110.8	93.7	80.9	51.4	817.0
70°	75.7	76.6	78.0	80.9	80.7	68.8	58.4	38.8	855.8
75°	54.8	55.1	55.5	57.1	55.6	46.5	38.4	27.9	883.8
80°	42.1	41.7	40.7	39.3	35.7	27.8	21.5	19.5	903.3
85°	34.4	33.7	31.6	27.6	21.5	14.0	8.7	13.6	916.9
90°	28.4	27.8	25.3	20.0	13.0	5.8	0.9	9.7	926.7
95°	25.4	25.0	23.0	18.3	11.9	5.4	1.0	8.8	935.5
100°	23.4	22.9	21.1	17.1	11.7	5.5	1.6	8.2	943.6
105°	21.5	21.0	19.3	16.3	11.6	5.9	2.4	7.6	951.2
110°	19.9	19.3	18.1	15.8	11.8	6.2	2.9	7.1	958.3
115°	18.9	18.3	17.5	15.6	12.1	6.6	3.0	6.7	965.0
120°	18.4	17.9	17.3	15.6	12.2	6.6	2.9	6.4	971.4
125°	18.2	17.7	17.1	15.5	11.8	6.5	2.7	5.9	977.3
130°	18.1	17.6	16.9	14.9	10.9	6.2	2.5	5.4	982.7
135°	17.9	17.2	16.1	13.6	9.8	5.6	2.4	4.7	987.4
140°	16.8	15.9	14.5	11.9	8.4	5.0	2.1	3.8	991.2
145°	14.9	14.0	12.6	10.1	6.8	4.5	2.0	3.0	994.1
150°	12.5	11.8	10.5	7.9	5.6	4.1	1.8	2.2	996.3
155°	10.2	9.6	8.3	6.3	5.0	3.7	1.7	1.5	997.8
160°	8.1	7.6	6.2	5.1	4.6	3.6	1.5	1.0	998.8
165°	6.4	6.1	4.7	4.5	4.0	4.8	1.5	0.7	999.5
170°	5.3	4.3	3.8	4.0	3.9	3.9	1.5	0.4	999.8
175°	3.8	3.2	4.6	4.9	4.0	2.2	1.5	0.2	1000.0
180°	1.5	1.5	1.5	1.5	1.5	1.5	1.5	0.0	1000.0

Photometric test report

Family DUS® 31	Order number: 53BD812M1V4085 EAN: 4058352421741	LP number 59062_9
--------------------------	--	-----------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	22.3	24.0	22.7	24.3	24.6	22.1	23.8	22.5	24.1	24.5
	3H	23.3	24.8	23.7	25.2	25.5	23.3	24.8	23.7	25.2	25.5
	4H	23.7	25.1	24.1	25.4	25.8	23.7	25.1	24.1	25.5	25.9
	6H	24.0	25.3	24.4	25.7	26.1	24.0	25.3	24.4	25.7	26.1
	8H	24.2	25.4	24.6	25.8	26.2	24.1	25.3	24.5	25.7	26.1
	12H	24.4	25.5	24.8	25.9	26.3	24.1	25.3	24.5	25.7	26.1
4H	2H	23.0	24.4	23.4	24.8	25.1	22.9	24.3	23.3	24.6	25.0
	3H	24.1	25.3	24.5	25.7	26.1	24.2	25.4	24.6	25.8	26.2
	4H	24.6	25.7	25.0	26.1	26.5	24.7	25.9	25.2	26.3	26.7
	6H	25.0	26.0	25.5	26.4	26.9	25.1	26.1	25.6	26.5	27.0
	8H	25.2	26.1	25.7	26.6	27.0	25.2	26.1	25.7	26.6	27.0
	12H	25.5	26.3	26.0	26.7	27.2	25.3	26.1	25.8	26.6	27.1
8H	4H	24.8	25.7	25.3	26.2	26.6	25.0	25.9	25.5	26.3	26.8
	6H	25.4	26.1	25.9	26.6	27.1	25.5	26.2	26.0	26.7	27.2
	8H	25.7	26.4	26.2	26.8	27.4	25.7	26.4	26.2	26.8	27.3
	12H	26.1	26.6	26.6	27.1	27.6	25.8	26.4	26.3	26.9	27.4
12H	4H	24.9	25.7	25.3	26.1	26.6	25.1	25.8	25.5	26.3	26.8
	6H	25.5	26.1	26.0	26.6	27.1	25.6	26.2	26.1	26.7	27.2
	8H	25.8	26.4	26.3	26.9	27.4	25.8	26.4	26.3	26.9	27.4


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1514	H(C0) = 25	H(C180) = 25
			B = 75	H(C90) = 0	H(C270) = 0

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
	45°	20993.0	21389.7	21980.6	21952.3	20923.0	20090.5	20685.1	
	50°	18538.0	18995.0	20097.5	20973.8	20387.3	19131.8	19544.2	
	55°	15997.2	16416.5	17610.1	19086.6	19308.8	17958.5	18226.1	
	60°	13571.3	13910.6	14916.8	16547.5	17505.6	16483.3	16706.8	
	65°	11312.1	11589.5	12357.5	13813.5	15223.9	14745.9	15095.2	
	70°	9100.4	9366.8	10025.0	11316.6	12763.9	12816.0	13468.9	
	75°	7434.8	7620.0	8142.4	9243.1	10446.0	10705.7	11708.5	
	80°	6606.7	6695.3	7013.7	7624.8	8340.4	8474.2	9778.9	
	85°	6458.3	6511.9	6643.3	6744.6	6690.7	6385.3	7882.4	

Photometric test report


Family DUS® 31	Order number: 53BD812M1V4085 EAN: 4058352421741	LP number 59062_9
---------------------------------	--	------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family DUS® 31	Order number: 53BD812M1V4085 EAN: 4058352421741	LP number 59062_9
---------------------------------	--	------------------------------------

Multilumen Table	environmental temperature: 25°C	
-------------------------	---------------------------------	---

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
1	A	C	E	8950	59.6
2	A	C	F	8050	52.3
3	A	D	E	7560	48.7
4	A	D	F	7050	44.6
5	B	C	E	6530	40.9
6	B	C	F	6060	37.6
7	B	D	E	5520	33.9
8	B	D	F	5040	29.6