


Photometric test report

Family Licross® 11 Recessed	Order number: 51TL12DN455MD EAN: 4058352929643	LP number 58689_114
	Version cover frosted, wide distribution, high visual comfort Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Setting DC mode (central or group accumulator) initial emergency light level Rated values Net luminous flux = 900 lm Power consumption = 5.5 W Luminous efficacy = 163.6 lm/W	serial documentation 04.10.2023



Luminous intensity in cd/klm C180-0 C270-90 **Imax: 575 cd/klm**



Classifications	
DIN 5040	A 5 0
CIE	N1=66 N2=91 N3=98 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL12DN455MD EAN: 4058352929643	LP number 58689_114
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	555.4	555.4	555.4	555.4	555.4	555.4	555.4	3.3	3.3
5°	551.9	549.3	545.0	546.0	548.1	548.0	548.5	26.2	29.5
10°	538.7	535.0	528.7	529.1	532.7	535.9	538.2	50.8	80.3
15°	515.9	510.9	504.6	513.1	530.5	544.7	552.3	74.2	154.5
20°	477.2	471.4	470.1	497.6	537.0	563.7	575.1	95.8	250.2
25°	425.5	419.5	426.9	469.4	521.2	548.6	558.0	111.1	361.3
30°	371.2	364.3	378.4	421.3	459.9	477.2	482.9	115.5	476.8
35°	317.2	309.8	328.6	357.7	367.8	374.7	379.7	109.4	586.2
40°	263.2	255.5	280.4	291.4	277.2	277.7	283.1	97.2	683.4
45°	213.7	204.0	230.1	230.5	202.8	200.2	207.0	82.5	765.9
50°	172.3	160.2	177.2	176.6	149.6	143.3	148.0	67.7	833.6
55°	133.3	121.6	126.4	129.1	111.8	101.0	103.0	53.0	886.6
60°	96.7	87.9	85.2	90.2	83.1	71.0	72.1	39.7	926.3
65°	67.7	61.0	56.3	61.1	60.5	50.8	52.1	29.0	955.3
70°	46.9	41.7	36.5	40.2	42.1	36.4	38.1	20.6	975.8
75°	30.9	26.7	22.6	25.0	27.1	24.7	26.6	13.7	989.5
80°	17.8	14.8	12.0	13.1	14.7	14.1	15.6	7.7	997.1
85°	6.6	5.4	4.4	4.8	5.3	5.4	5.9	2.9	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL12DN455MD EAN: 4058352929643	LP number 58689_114
---------------------------------------	---	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	14.5	16.0	14.9	16.3	16.6	14.0	15.5	14.3	15.8	16.1
	3H	15.2	16.6	15.6	16.9	17.3	14.6	15.9	14.9	16.2	16.6
	4H	15.5	16.8	15.9	17.1	17.5	14.8	16.1	15.2	16.4	16.8
	6H	15.8	16.9	16.2	17.3	17.6	15.0	16.2	15.5	16.5	16.9
	8H	15.9	16.9	16.3	17.3	17.7	15.2	16.2	15.6	16.6	17.0
	12H	15.9	16.9	16.3	17.3	17.7	15.2	16.2	15.6	16.5	17.0
4H	2H	14.8	16.1	15.2	16.4	16.8	14.4	15.6	14.8	16.0	16.4
	3H	15.7	16.7	16.1	17.1	17.5	15.2	16.2	15.6	16.6	17.0
	4H	16.0	16.9	16.5	17.3	17.8	15.5	16.5	16.0	16.9	17.3
	6H	16.3	17.1	16.8	17.5	18.0	15.8	16.6	16.3	17.0	17.5
	8H	16.4	17.1	16.9	17.6	18.0	15.9	16.6	16.4	17.1	17.6
	12H	16.5	17.1	17.0	17.6	18.1	16.0	16.6	16.5	17.1	17.6
8H	4H	16.1	16.8	16.6	17.3	17.7	15.7	16.4	16.1	16.8	17.3
	6H	16.4	17.0	16.9	17.5	18.0	16.0	16.6	16.5	17.1	17.6
	8H	16.6	17.1	17.1	17.6	18.1	16.1	16.7	16.6	17.1	17.7
	12H	16.7	17.1	17.2	17.6	18.1	16.2	16.7	16.8	17.2	17.7
12H	4H	16.1	16.7	16.6	17.2	17.7	15.7	16.3	16.2	16.8	17.2
	6H	16.5	17.0	17.0	17.4	18.0	16.0	16.5	16.5	17.0	17.5
	8H	16.6	17.0	17.1	17.5	18.1	16.2	16.6	16.7	17.1	17.7

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1500 B = 58
------------------------	---	--------------------------------------	----------------------------------

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		3126.5	2984.3	3365.7	3371.6	2967.1	2928.5	3028.8	
50°		2772.5	2578.9	2852.1	2842.7	2407.7	2306.2	2381.8	
55°		2404.6	2192.4	2279.0	2327.9	2015.9	1822.1	1857.7	
60°		2000.1	1818.1	1763.4	1865.8	1720.0	1469.2	1490.9	
65°		1656.7	1493.8	1378.8	1494.7	1481.5	1244.5	1274.4	
70°		1418.1	1262.6	1104.3	1216.6	1273.7	1101.7	1152.6	
75°		1236.4	1065.9	902.1	997.4	1082.2	985.9	1062.3	
80°		1058.6	879.5	713.5	783.3	873.1	842.3	929.7	
85°		782.5	641.1	521.4	566.3	626.3	637.1	697.2	

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL12DN455MD EAN: 4058352929643	LP number 58689_114
---------------------------------------	---	--------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**

