



Photometric test report

Family Licross® 21 Performance	Order number: 52TM16CN445G EAN: 4058352903421	LP number 58520_390
	Version cover frosted, direct-/ indirect distribution, UGR≤19 (L65≤3000cd/m²) Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-Multilumen CLOi Rated values Net luminous flux = 4500 lm Power consumption = 24.1 W Luminous efficacy = 186.7 lm/W	serial documentation 20.02.2024
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 452 cd/klm**



Classifications	
DIN 5040	B 5 1
CIE	N1=65 N2=88 N3=96 N4=79 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	79.3%
ϕ_o	20.7%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 21 Performance	Order number: 52TM16CN445G EAN: 4058352903421	LP number 58520_390
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	427.7	427.7	427.7	427.7	427.7	427.7	427.7	2.6	2.6
5°	424.4	422.4	420.2	422.1	424.3	424.4	424.8	20.2	22.8
10°	414.9	412.5	408.9	409.5	411.2	411.6	412.2	39.1	61.9
15°	410.8	406.7	398.1	393.2	390.9	389.7	390.1	56.3	118.2
20°	424.3	415.5	394.5	375.8	364.0	357.7	356.8	71.8	190.0
25°	451.7	439.9	403.9	360.3	329.2	311.6	307.2	85.9	275.8
30°	429.5	430.9	412.5	347.4	284.5	251.0	241.5	94.2	370.0
35°	325.6	344.5	379.3	329.0	231.5	183.8	171.0	89.9	460.0
40°	224.9	238.5	293.1	289.7	177.2	125.7	113.8	76.0	535.9
45°	176.4	174.8	199.5	224.7	128.0	84.3	75.7	60.6	596.5
50°	156.0	144.3	136.6	154.2	90.2	58.9	53.2	48.2	644.7
55°	139.0	122.9	98.4	99.7	63.9	43.4	39.8	38.7	683.4
60°	113.7	99.1	72.2	64.7	46.3	33.0	30.8	30.7	714.1
65°	79.7	70.2	51.6	43.8	34.5	25.6	24.0	23.0	737.1
70°	47.7	43.4	35.6	31.1	26.2	19.7	18.2	16.2	753.3
75°	33.9	31.2	26.1	23.2	19.9	14.4	12.7	12.2	765.5
80°	33.7	30.7	23.7	18.2	15.1	9.9	7.5	10.6	776.1
85°	39.3	35.6	26.3	17.2	11.4	6.2	3.2	10.7	786.9
90°	50.4	45.6	32.3	18.9	10.0	3.9	0.6	12.4	799.3
95°	71.3	63.5	42.3	22.5	11.4	4.6	1.0	16.4	815.7
100°	97.9	84.6	52.5	26.5	12.9	5.3	1.6	20.8	836.6
105°	120.7	101.7	62.6	30.2	14.2	6.1	2.4	24.4	860.9
110°	134.6	112.6	69.4	33.2	15.3	6.7	2.9	26.3	887.2
115°	137.8	115.5	72.0	34.6	16.0	7.2	3.2	26.1	913.3
120°	129.6	108.9	68.7	33.6	15.7	7.4	3.5	23.8	937.1
125°	109.1	92.2	59.5	30.3	14.7	7.4	3.7	19.5	956.6
130°	83.4	71.0	47.4	25.5	13.2	7.2	3.7	14.5	971.2
135°	58.6	50.3	35.1	20.5	11.4	6.8	3.7	10.0	981.2
140°	39.2	34.3	25.3	16.3	9.8	6.3	3.7	6.7	987.9
145°	26.6	23.8	18.6	13.0	8.2	5.4	3.7	4.4	992.3
150°	18.7	17.2	14.2	10.0	6.9	5.0	3.7	2.9	995.2
155°	13.8	12.8	10.8	7.8	6.8	4.4	3.6	2.0	997.2
160°	10.2	9.8	7.9	6.8	5.6	4.6	3.5	1.3	998.5
165°	8.2	7.8	6.5	5.6	5.0	4.1	3.7	0.8	999.3
170°	6.4	5.6	4.7	4.7	5.0	4.1	3.9	0.5	999.8
175°	4.2	3.7	4.1	4.1	4.1	4.2	4.2	0.2	1000.0
180°	3.7	3.7	3.7	3.7	3.7	3.7	3.7	0.0	1000.0

Photometric test report

Family Licross® 21 Performance	Order number: 52TM16CN445G EAN: 4058352903421	LP number 58520_390
--	--	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	16.3	17.6	16.9	18.1	18.8	12.5	13.8	13.1	14.3	15.0
	3H	16.9	18.0	17.5	18.6	19.3	12.9	14.0	13.5	14.6	15.3
	4H	17.1	18.1	17.7	18.7	19.4	13.1	14.2	13.7	14.8	15.5
	6H	17.3	18.2	18.0	18.9	19.6	13.3	14.2	13.9	14.8	15.6
	8H	17.6	18.4	18.3	19.0	19.8	13.2	14.1	13.9	14.8	15.5
	12H	17.9	18.6	18.6	19.3	20.1	13.3	14.1	13.9	14.8	15.5
4H	2H	16.3	17.4	16.9	18.0	18.7	13.0	14.0	13.6	14.6	15.3
	3H	17.0	17.8	17.6	18.5	19.3	13.5	14.4	14.2	15.0	15.8
	4H	17.2	18.0	17.9	18.7	19.5	13.8	14.6	14.5	15.3	16.1
	6H	17.7	18.3	18.4	19.0	19.9	14.0	14.7	14.7	15.4	16.2
	8H	18.0	18.6	18.7	19.3	20.2	14.1	14.7	14.8	15.4	16.3
	12H	18.5	19.0	19.3	19.8	20.7	14.1	14.7	14.9	15.4	16.3
8H	4H	17.2	17.8	17.9	18.5	19.4	14.0	14.6	14.7	15.3	16.1
	6H	17.8	18.3	18.5	19.0	19.9	14.4	14.8	15.1	15.6	16.5
	8H	18.3	18.7	19.0	19.5	20.3	14.5	15.0	15.3	15.7	16.6
	12H	19.0	19.4	19.8	20.2	21.1	14.6	15.0	15.4	15.8	16.7
12H	4H	17.1	17.7	17.9	18.4	19.3	14.0	14.5	14.8	15.2	16.1
	6H	17.7	18.2	18.5	18.9	19.8	14.5	14.9	15.2	15.6	16.6
	8H	18.3	18.7	19.1	19.4	20.4	14.7	15.1	15.5	15.8	16.8

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1480	H(C0) = 36	H(C180) = 36
			B = 115	H(C90) = 0	H(C270) = 0

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°	45°	5023.8	5018.4	5868.8	6879.2	4139.9	2916.3	2828.9	
50°	50°	4673.3	4361.9	4245.2	5019.1	3127.8	2210.6	2187.0	
55°	55°	4427.7	3957.5	3270.4	3492.8	2407.2	1793.0	1833.6	
60°	60°	3898.2	3440.1	2596.9	2473.4	1928.0	1532.5	1628.5	
65°	65°	2985.1	2662.3	2040.1	1858.2	1618.1	1365.9	1503.6	
70°	70°	1981.6	1832.2	1577.3	1497.1	1413.8	1244.8	1409.5	
75°	75°	1599.3	1496.2	1325.8	1297.9	1285.1	1132.2	1298.5	
80°	80°	1850.5	1723.3	1422.0	1227.1	1220.0	1034.8	1143.0	
85°	85°	2602.2	2426.8	1945.7	1478.4	1236.9	978.2	973.2	


Photometric test report

Family Licross® 21 Performance	Order number: 52TM16CN445G EAN: 4058352903421	LP number 58520_390
---	--	--------------------------------------

Luminance values in cd/m²

γ 65°	γ 70°	γ 75°	γ 80°	γ 85°
--------------	--------------	--------------	--------------	--------------

siteco



Photometric test report

Family Licross® 21 Performance	Order number: 52TM16CN445G EAN: 4058352903421	LP number 58520_390
--	--	--------------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
	1	2	3			end of lifetime	average
1	A	C	E	4500	24.1	28.2	26.2
2	A	C	F	4416	23.7	27.9	25.8
3	A	D	E	4343	23.2	27.4	25.3
4	A	D	F	4259	22.8	27.0	24.9
5	B	C	E	4185	22.3	26.2	24.2
6	B	C	F	4101	22.0	25.7	23.8