



Photometric test report

Family Licross® 11 Recessed	Order number: 51TE10CN49XG EAN: 4058352929025	LP number 58684_160
	Version cover frosted Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-Multilumen CLOi Rated values Net luminous flux = 9050 lm Power consumption = 49.3 W Luminous efficacy = 183.6 lm/W	serial documentation 14.11.2025





Luminous intensity in cd/klm C180-0 C270-90 **Imax: 385 cd/klm**



Classifications	
DIN 5040	A 4 0
CIE	N1=50 N2=81 N3=96 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE10CN49XG EAN: 4058352929025	LP number 58684_160
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	384.9	384.9	384.9	384.9	384.9	384.9	384.9	2.3	2.3
5°	384.9	383.5	380.9	382.4	383.7	383.9	383.8	18.3	20.6
10°	379.5	378.4	375.4	376.4	377.1	376.9	376.6	35.9	56.5
15°	370.8	369.9	366.1	365.8	365.5	363.9	363.9	52.0	108.5
20°	358.8	358.1	353.2	350.6	348.2	345.1	343.9	65.8	174.3
25°	343.3	342.7	336.1	331.0	326.3	322.1	320.9	76.8	251.1
30°	324.2	323.3	314.8	307.4	302.4	299.4	299.2	84.9	336.1
35°	301.1	299.6	289.7	281.8	279.3	280.0	281.8	90.2	426.3
40°	274.8	272.4	262.0	255.7	258.0	262.5	265.4	92.8	519.1
45°	245.2	241.9	231.9	229.2	235.1	240.6	244.6	92.0	611.1
50°	213.6	209.5	202.3	202.7	208.5	212.2	215.6	87.5	698.5
55°	180.7	176.6	172.5	174.4	178.1	179.3	181.7	79.5	778.0
60°	146.9	143.9	142.8	145.1	146.4	145.5	146.6	68.9	846.9
65°	113.3	112.0	113.5	115.8	115.6	113.0	112.9	56.5	903.4
70°	80.7	81.0	84.0	87.4	86.4	83.3	82.2	43.2	946.6
75°	51.4	52.0	55.5	60.1	59.2	56.0	54.4	29.6	976.3
80°	28.6	28.8	31.3	34.2	34.2	31.5	29.9	17.0	993.3
85°	11.6	11.6	12.6	13.6	13.2	11.7	10.4	6.7	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE10CN49XG EAN: 4058352929025	LP number 58684_160
---------------------------------------	--	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	24.3	26.0	24.7	26.3	26.6	24.4	26.0	24.7	26.3	26.7
	3H	25.7	27.2	26.0	27.5	27.8	25.7	27.2	26.1	27.6	27.9
	4H	26.1	27.5	26.5	27.9	28.3	26.2	27.7	26.6	28.0	28.4
	6H	26.4	27.7	26.8	28.1	28.5	26.6	27.9	27.0	28.3	28.6
	8H	26.6	27.8	27.0	28.2	28.6	26.7	27.9	27.1	28.3	28.7
	12H	26.6	27.8	27.1	28.2	28.6	26.8	27.9	27.2	28.3	28.7
4H	2H	25.0	26.4	25.4	26.8	27.2	25.1	26.5	25.5	26.8	27.2
	3H	26.6	27.7	27.0	28.1	28.5	26.6	27.8	27.1	28.2	28.6
	4H	27.1	28.2	27.6	28.6	29.0	27.3	28.3	27.7	28.7	29.2
	6H	27.5	28.5	28.0	28.9	29.3	27.7	28.6	28.2	29.1	29.5
	8H	27.7	28.5	28.1	28.9	29.4	27.9	28.7	28.3	29.1	29.6
	12H	27.8	28.5	28.2	29.0	29.5	27.9	28.7	28.4	29.2	29.6
8H	4H	27.4	28.3	27.9	28.7	29.2	27.6	28.4	28.0	28.9	29.3
	6H	28.0	28.7	28.4	29.1	29.6	28.2	28.9	28.6	29.3	29.8
	8H	28.1	28.8	28.6	29.2	29.8	28.3	29.0	28.8	29.4	30.0
	12H	28.3	28.8	28.8	29.3	29.8	28.5	29.0	29.0	29.5	30.0
12H	4H	27.5	28.2	28.0	28.7	29.2	27.6	28.4	28.1	28.8	29.3
	6H	28.0	28.6	28.5	29.1	29.6	28.2	28.8	28.7	29.3	29.8
	8H	28.2	28.8	28.8	29.3	29.8	28.4	29.0	29.0	29.5	30.0


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1500
			B = 58

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
	45°	36068.3	35580.8	34113.2	33711.6	34584.6	35398.8	35982.5	
	50°	34574.7	33908.9	32736.5	32795.4	33738.1	34339.1	34892.9	
	55°	32764.4	32024.8	31292.0	31622.0	32295.6	32513.4	32949.4	
	60°	30556.5	29942.8	29715.6	30192.9	30450.4	30260.9	30495.8	
	65°	27888.6	27575.0	27924.5	28498.0	28444.4	27816.9	27799.0	
	70°	24558.6	24636.2	25543.1	26573.0	26270.9	25320.8	25010.6	
	75°	20659.2	20887.5	22311.4	24172.7	23790.9	22510.4	21873.8	
	80°	17108.1	17271.7	18761.5	20504.1	20493.3	18874.7	17910.8	
	85°	13861.7	13831.8	14978.8	16269.0	15718.8	14022.8	12436.6	

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE10CN49XG EAN: 4058352929025	LP number 58684_160
---------------------------------------	--	-------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family Licross® 11 Recessed	Order number: 51TE10CN49XG EAN: 4058352929025	LP number 58684_160
---------------------------------------	--	--------------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
	1	2	3			end of lifetime	average
1	A	C	E	9050	49.3	52.0	50.6
2	A	C	F	8530	46.2	48.4	47.3
3	A	D	E	8010	43.1	45.3	44.2
4	A	D	F	7480	40.0	42.2	41.1
5	B	C	E	7020	37.4	39.6	38.5
6	B	C	F	6480	34.3	36.5	35.4
7	B	D	E	6020	31.8	33.5	32.6
8	B	D	F	5540	29.2	30.9	30.0