

Photometric test report

Family
Taris®

Order number: 51MT1LV0JHGEDB02
EAN: 4058352218792

LP number
58112_33



Version recessed luminaire for lay-in mounting,
Combined lens and reflector optics, UGR≤19
(L65≤3000cd/m²)

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG

Rated values Net luminous flux = 4620 lm
Power consumption = 31.1 W
Luminous efficacy = 148.6 lm/W

serial
documentation
16.11.2020


sitEco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 681 cd/klm



Classifications

DIN 5040 A 6 0
CIE N1=79 N2=97 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Taris®	Order number: 51MT1LV0JHGEDB02 EAN: 4058352218792	LP number 58112_33
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	589.9	589.9	589.9	589.9	589.9	589.9	589.9	3.5	3.5
5°	588.7	589.0	592.1	596.9	601.1	606.4	606.3	28.5	32.1
10°	580.8	584.8	599.2	616.6	632.8	645.8	648.3	58.6	90.7
15°	567.0	574.3	602.6	635.5	662.1	678.0	680.7	89.3	179.9
20°	551.0	554.8	587.3	624.4	654.1	665.4	665.6	115.4	295.4
25°	514.2	525.6	561.3	575.5	595.4	611.3	613.5	132.5	427.9
30°	441.6	477.7	526.4	513.0	520.7	546.4	552.1	140.7	568.6
35°	356.1	390.2	427.9	438.7	434.5	464.3	474.5	134.7	703.4
40°	254.0	278.7	312.5	330.4	326.6	358.4	375.6	112.8	816.2
45°	125.3	144.2	184.1	221.0	208.9	235.0	260.2	76.6	892.8
50°	68.1	75.9	88.8	113.1	112.9	130.9	156.0	44.3	937.2
55°	40.1	49.3	51.7	56.7	60.1	72.8	89.4	26.6	963.8
60°	15.6	16.8	22.5	34.4	35.9	44.2	53.6	14.9	978.7
65°	9.0	9.2	10.4	17.0	24.2	28.8	33.5	9.2	987.8
70°	6.7	6.6	6.6	7.5	14.8	18.9	20.8	5.9	993.7
75°	4.7	4.7	4.6	4.7	6.2	12.0	12.2	3.6	997.3
80°	3.0	3.0	2.9	2.9	3.1	5.5	5.7	1.9	999.2
85°	1.5	1.4	1.4	1.4	1.4	1.5	1.4	0.8	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Taris®	Order number: 51MT1LV0JHGEDB02 EAN: 4058352218792	LP number 58112_33
-------------------------	--	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	16.2	17.6	16.6	17.9	18.2	18.1	19.5	18.5	19.8	20.1
	3H	16.1	17.3	16.5	17.7	18.0	18.3	19.5	18.7	19.8	20.1
	4H	16.1	17.2	16.5	17.6	17.9	18.3	19.4	18.7	19.8	20.1
	6H	16.0	17.1	16.5	17.4	17.8	18.3	19.3	18.7	19.7	20.1
	8H	16.1	17.0	16.5	17.4	17.8	18.4	19.2	18.8	19.6	20.0
	12H	16.1	16.9	16.5	17.3	17.7	18.4	19.2	18.8	19.5	20.0
4H	2H	16.2	17.3	16.6	17.6	18.0	18.0	19.1	18.4	19.5	19.8
	3H	16.1	17.0	16.5	17.4	17.8	18.2	19.1	18.6	19.5	19.9
	4H	16.1	16.9	16.5	17.3	17.7	18.2	19.0	18.7	19.5	19.9
	6H	16.0	16.7	16.5	17.2	17.6	18.3	19.0	18.7	19.4	19.9
	8H	16.0	16.6	16.5	17.1	17.6	18.3	18.9	18.7	19.3	19.8
	12H	16.0	16.5	16.5	17.0	17.5	18.3	18.8	18.8	19.2	19.7
8H	4H	16.0	16.6	16.5	17.1	17.5	18.1	18.8	18.6	19.2	19.7
	6H	16.0	16.5	16.5	16.9	17.5	18.2	18.7	18.7	19.1	19.7
	8H	15.9	16.4	16.4	16.9	17.4	18.1	18.6	18.7	19.1	19.6
	12H	15.9	16.3	16.5	16.8	17.3	18.1	18.5	18.7	19.0	19.5
12H	4H	16.0	16.5	16.5	17.0	17.5	18.1	18.7	18.6	19.1	19.6
	6H	16.0	16.4	16.5	16.9	17.4	18.1	18.6	18.6	19.0	19.6
	8H	15.9	16.3	16.4	16.8	17.3	18.1	18.5	18.6	19.0	19.5

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 368 B = 333
------------------------	---	--------------------------------------	----------------------------------

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		6679.6	7687.1	9816.7	11783.5	11140.5	12530.9	13874.9	
50°		3993.3	4452.2	5208.3	6633.3	6622.8	7675.0	9149.1	
55°		2634.7	3242.1	3398.9	3727.4	3951.3	4783.3	5874.3	
60°		1173.2	1269.9	1698.0	2593.1	2708.2	3331.7	4043.2	
65°		804.6	818.6	929.1	1514.0	2159.6	2565.8	2990.3	
70°		741.4	727.6	730.1	821.7	1634.3	2085.9	2293.7	
75°		691.6	683.0	665.5	679.8	903.0	1752.1	1774.2	
80°		658.3	640.5	621.6	619.2	670.0	1188.9	1229.1	
85°		634.6	622.9	603.9	599.1	620.3	634.6	592.2	

Photometric test report

Family Taris®	Order number: 51MT1LV0JHGEDB02 EAN: 4058352218792	LP number 58112_33
-------------------------	--	------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**

