

Photometric test report

Family
Licross® 21 Recessed

Order number: 52TE11CN4C5S
EAN: 4058352889343

LP number
58784_264



Version cover frosted, narrow distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-Multilumen CLOi
Rated values Net luminous flux = 12640 lm
 Power consumption = 68.4 W
 Luminous efficacy = 184.8 lm/W

serial
documentation
17.08.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 3431 cd/klm



Classifications

DIN 5040 A 7 0
 CIE N1=87 N2=95 N3=99
 N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 21 Recessed	Order number: 52TE11CN4C5S EAN: 4058352889343	LP number 58784_264
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	3431.3	3431.3	3431.3	3431.3	3431.3	3431.3	3431.3	20.5	20.5
5°	3030.0	3009.9	2995.2	3008.4	3015.8	3015.7	3017.5	143.9	164.4
10°	2113.5	2098.5	2092.1	2104.8	2111.9	2109.7	2109.2	200.3	364.7
15°	1287.2	1281.7	1283.9	1294.7	1294.7	1286.2	1283.2	182.7	547.4
20°	703.4	705.4	717.6	726.5	719.3	702.5	697.3	133.5	680.9
25°	354.0	358.8	370.9	376.0	367.5	355.6	354.0	84.3	765.2
30°	176.2	179.2	185.6	185.7	179.6	178.8	183.6	49.7	814.9
35°	102.4	102.6	103.9	102.5	99.6	107.7	116.7	32.8	847.7
40°	73.1	72.4	71.7	70.6	70.7	80.9	90.2	26.3	874.0
45°	60.7	58.7	57.0	56.9	57.9	66.7	75.5	23.6	897.6
50°	52.7	51.5	51.2	50.6	50.0	56.0	63.2	22.2	919.8
55°	44.8	43.4	45.4	45.0	43.0	46.3	51.7	20.3	940.1
60°	37.3	36.1	38.2	39.8	37.2	38.0	41.8	18.1	958.2
65°	29.8	28.9	31.0	34.0	31.7	30.7	33.0	15.5	973.8
70°	21.9	21.7	22.9	26.9	25.3	23.3	24.3	12.3	986.1
75°	12.2	12.7	14.5	18.5	17.7	15.7	16.0	8.2	994.3
80°	5.5	5.6	6.4	9.0	10.0	8.8	8.6	4.2	998.5
85°	2.2	2.1	2.4	3.2	3.5	3.4	3.0	1.6	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 21 Recessed	Order number: 52TE11CN4C5S EAN: 4058352889343	LP number 58784_264
--------------------------------	--	------------------------

UGR-Table		Standard room							siTeco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	16.8	18.0	17.2	18.3	18.6	17.2	18.3	17.6	18.6	19.0
	3H	18.2	19.1	18.6	19.5	19.8	18.6	19.6	19.0	19.9	20.3
	4H	18.5	19.5	18.9	19.8	20.2	19.1	20.0	19.5	20.4	20.8
	6H	18.7	19.5	19.1	19.9	20.3	19.5	20.3	19.9	20.6	21.0
	8H	18.8	19.5	19.2	19.9	20.3	19.6	20.3	20.1	20.7	21.1
	12H	18.8	19.4	19.2	19.8	20.3	19.6	20.3	20.1	20.7	21.1
4H	2H	17.6	18.5	18.0	18.8	19.2	17.9	18.8	18.3	19.1	19.5
	3H	19.0	19.8	19.5	20.2	20.6	19.5	20.2	19.9	20.6	21.0
	4H	19.5	20.2	19.9	20.6	21.0	20.1	20.7	20.5	21.2	21.6
	6H	19.7	20.3	20.1	20.7	21.2	20.5	21.1	20.9	21.5	22.0
	8H	19.7	20.2	20.2	20.7	21.2	20.6	21.1	21.1	21.6	22.0
	12H	19.7	20.2	20.2	20.6	21.1	20.7	21.1	21.1	21.6	22.1
8H	4H	19.8	20.3	20.3	20.8	21.3	20.3	20.9	20.8	21.3	21.8
	6H	20.1	20.5	20.6	21.0	21.5	20.9	21.3	21.4	21.8	22.3
	8H	20.1	20.5	20.6	21.0	21.5	21.0	21.4	21.5	21.9	22.4
	12H	20.1	20.4	20.6	20.9	21.5	21.1	21.4	21.6	21.9	22.5
12H	4H	19.8	20.3	20.3	20.7	21.2	20.3	20.8	20.8	21.2	21.7
	6H	20.1	20.4	20.6	20.9	21.5	20.9	21.2	21.4	21.7	22.2
	8H	20.1	20.5	20.7	21.0	21.5	21.0	21.4	21.6	21.9	22.4

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1500 B = 58	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	12475.0	12065.7	11718.6	11687.4	11895.5	13699.5	15520.8
50°	11922.0	11646.5	11583.0	11443.1	11294.1	12660.5	14288.1
55°	11359.0	11003.6	11506.9	11403.6	10897.5	11738.0	13090.3
60°	10837.6	10483.6	11090.1	11559.6	10819.3	11042.1	12157.4
65°	10238.8	9946.9	10654.4	11673.0	10912.9	10565.0	11341.6
70°	9289.3	9209.9	9722.6	11408.2	10748.1	9896.8	10338.2
75°	6869.8	7117.9	8118.8	10364.7	9921.3	8787.9	8962.5
80°	4636.0	4678.7	5380.7	7551.8	8331.6	7331.8	7196.3
85°	3647.4	3577.4	3949.1	5286.0	5792.8	5622.7	4959.3

Photometric test report

Family Licross® 21 Recessed	Order number: 52TE11CN4C5S EAN: 4058352889343	LP number 58784_264
--	--	--------------------------------------

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Licross® 21 Recessed	Order number: 52TE11CN4C5S EAN: 4058352889343	LP number 58784_264
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
	1	2	3			end of lifetime	average
1	A	C	E	12640	68.4	83.1	75.8
2	A	C	F	12130	65.4	79.7	72.6
3	A	D	E	11100	59.4	71.9	65.6
4	A	D	F	10120	53.9	64.9	59.4
5	B	C	E	9060	47.9	57.7	52.8
6	B	C	F	8060	42.4	50.9	46.6
7	B	D	E	7050	37.1	44.2	40.7
8	B	D	F	6020	31.6	37.5	34.6