

Photometric test report

Family
Licross® 11 Protected

Order number: 51TD11CN4EXS
EAN: 4058352928523

LP number
58525_202



Version prismatic cover, frosted, narrow distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-Multilumen CLOi
Rated values Net luminous flux = 14460 lm
 Power consumption = 77.6 W
 Luminous efficacy = 186.3 lm/W

serial
documentation
12.10.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 2130 cd/klm



Classifications

DIN 5040 A 7 1
 CIE N1=84 N2=94 N3=98
 N4=99 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 99.1%
 ϕ_o 0.9%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Protected	Order number: 51TD11CN4EXS EAN: 4058352928523	LP number 58525_202
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	2130.5	2130.5	2130.5	2130.5	2130.5	2130.5	2130.5	12.7	12.7
5°	1990.0	1982.4	1972.8	1980.9	1991.5	1994.0	1997.3	94.9	107.6
10°	1609.4	1602.7	1594.9	1604.0	1616.7	1623.6	1628.9	153.3	260.9
15°	1156.5	1152.7	1146.1	1151.7	1161.7	1170.4	1176.7	164.3	425.2
20°	757.1	754.5	751.0	754.8	760.5	766.7	772.3	142.2	567.4
25°	464.1	463.3	461.4	464.7	468.5	471.4	475.4	108.1	675.5
30°	281.8	280.0	276.3	277.8	280.6	282.2	284.6	76.7	752.2
35°	178.8	175.8	169.5	168.1	169.9	172.0	174.0	54.1	806.3
40°	123.8	119.7	111.6	107.8	108.9	112.2	115.0	39.9	846.2
45°	92.5	87.9	79.0	74.1	74.5	78.8	82.8	31.1	877.3
50°	72.9	68.3	60.1	54.9	54.7	59.1	63.7	25.6	902.9
55°	58.5	54.5	47.8	42.9	42.0	45.8	50.2	21.5	924.4
60°	46.6	43.5	38.6	34.6	32.9	35.6	39.1	18.0	942.5
65°	36.7	34.5	31.1	28.0	26.1	27.3	29.5	14.9	957.4
70°	28.5	27.0	24.6	22.5	20.4	20.1	21.2	12.0	969.4
75°	21.8	20.7	19.0	17.5	15.4	14.0	14.0	9.2	978.6
80°	16.2	15.4	14.3	12.9	10.9	8.9	8.1	6.7	985.3
85°	11.7	11.2	10.3	9.1	7.1	4.7	3.5	4.6	989.8
90°	8.1	7.7	6.9	5.8	3.9	1.7	0.3	2.8	992.6
95°	6.9	6.6	5.8	4.7	3.0	1.1	0.2	2.3	994.8
100°	6.0	5.6	4.9	3.8	2.2	0.6	0.2	1.8	996.7
105°	5.1	4.8	4.0	2.9	1.5	0.3	0.2	1.4	998.1
110°	4.3	4.0	3.2	2.2	0.9	0.2	0.2	1.1	999.2
115°	3.6	3.2	2.5	1.6	0.5	0.3	0.3	0.8	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Protected	Order number: 51TD11CN4EXS EAN: 4058352928523	LP number 58525_202
---------------------------------	--	------------------------

UGR-Table		Standard room							siTeco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	17.3	18.6	17.7	18.9	19.2	17.0	18.2	17.3	18.5	18.8
	3H	18.4	19.5	18.8	19.8	20.2	17.9	19.0	18.3	19.3	19.7
	4H	18.9	19.9	19.3	20.3	20.6	18.3	19.3	18.7	19.6	20.0
	6H	19.4	20.3	19.8	20.7	21.0	18.6	19.4	19.0	19.8	20.2
	8H	19.7	20.4	20.1	20.8	21.2	18.7	19.5	19.2	19.9	20.3
	12H	19.9	20.6	20.3	21.0	21.4	18.8	19.5	19.2	19.9	20.3
4H	2H	17.6	18.6	18.0	18.9	19.3	17.3	18.3	17.7	18.6	19.0
	3H	18.9	19.7	19.3	20.1	20.5	18.4	19.2	18.8	19.6	20.0
	4H	19.5	20.2	20.0	20.7	21.1	18.8	19.6	19.3	20.0	20.4
	6H	20.1	20.8	20.6	21.2	21.7	19.2	19.9	19.7	20.3	20.8
	8H	20.4	21.0	20.9	21.4	21.9	19.4	19.9	19.9	20.4	20.9
	12H	20.7	21.2	21.2	21.7	22.2	19.5	20.0	20.0	20.4	20.9
8H	4H	19.7	20.2	20.2	20.7	21.2	19.1	19.6	19.6	20.1	20.6
	6H	20.5	20.9	21.0	21.4	21.9	19.6	20.1	20.1	20.5	21.1
	8H	20.8	21.2	21.3	21.7	22.3	19.8	20.2	20.3	20.7	21.2
	12H	21.2	21.6	21.8	22.1	22.6	20.0	20.3	20.5	20.8	21.4
12H	4H	19.7	20.2	20.2	20.6	21.1	19.2	19.6	19.6	20.1	20.6
	6H	20.5	20.9	21.0	21.4	21.9	19.7	20.1	20.2	20.6	21.1
	8H	20.9	21.3	21.5	21.8	22.3	20.0	20.3	20.5	20.8	21.3

Luminance table		Max. for $\gamma \geq 65^\circ$			Photometric dimensions in mm:	L = 1480 B = 78	H(C0) = 13 H(C90) = 0	H(C180) = 13 H(C270) = 0
C- planes	γ	0°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
		Luminance in cd/m²						
	45°	14049.4	13405.0	12232.0	11744.6	12186.3	13385.1	14658.9
	50°	11853.1	11169.6	9999.3	9387.0	9688.4	10959.6	12404.8
	55°	10325.8	9683.3	8653.4	8022.2	8191.2	9428.6	10964.8
	60°	9068.4	8529.5	7735.8	7189.0	7212.1	8304.1	9795.3
	65°	8015.1	7602.1	7047.5	6634.1	6568.5	7394.9	8733.7
	70°	7154.1	6848.6	6452.9	6215.6	6093.3	6594.8	7755.0
	75°	6490.6	6250.0	5972.1	5870.2	5687.6	5821.4	6781.8
	80°	6017.1	5822.0	5667.0	5582.3	5323.1	5132.0	5809.7
	85°	5803.7	5650.4	5583.8	5591.9	5199.7	4566.5	5018.7

Photometric test report

Family
Licross® 11 Protected

Order number: 51TD11CN4EXS
EAN: 4058352928523

LP number
58525_202

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Licross® 11 Protected	Order number: 51TD11CN4EXS EAN: 4058352928523	LP number 58525_202
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
	1	2	3			end of lifetime	average
1	A	C	E	14460	77.6	87.4	82.5
2	A	C	F	13200	70.1	79.0	74.6
3	A	D	E	12220	64.3	74.9	69.6
4	A	D	F	11150	58.3	65.2	61.8
5	B	C	E	10150	52.6	58.7	55.6
6	B	C	F	9130	47.0	52.2	49.6
7	B	D	E	8110	41.5	46.2	43.8
8	B	D	F	7070	36.0	39.9	38.0