


Photometric test report

Family Licross® 11 Protected	Order number: 51TD11MN495G EAN: 4058352928585	LP number 58526_230
	Version prismatic cover, frosted, narrow distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG Multilumen Rated values Net luminous flux = 9980 lm Power consumption = 55.3 W Luminous efficacy = 180.5 lm/W	serial documentation 11.10.2023
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 1742 cd/klm**




Classifications	
DIN 5040	A 7 0
CIE	N1=83 N2=94 N3=98 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Protected	Order number: 51TD11MN495G EAN: 4058352928585	LP number 58526_230
Table of values for luminous intensities		
Maximum luminous intensity		

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	1742.2	1742.2	1742.2	1742.2	1742.2	1742.2	1742.2	10.4	10.4
5°	1666.1	1675.3	1660.6	1665.8	1671.6	1669.6	1670.7	79.7	90.1
10°	1438.7	1454.0	1443.6	1449.9	1452.8	1449.1	1448.5	137.9	228.0
15°	1099.0	1113.1	1114.3	1128.7	1137.3	1134.2	1132.4	159.4	387.5
20°	752.6	761.9	768.4	788.3	803.8	805.8	803.7	147.1	534.5
25°	477.8	482.8	489.1	506.4	523.2	529.8	529.1	117.2	651.7
30°	296.4	297.2	300.0	310.9	324.6	332.2	333.5	85.9	737.6
35°	189.3	187.5	185.3	189.4	198.7	205.9	208.7	61.1	798.7
40°	131.6	127.9	121.5	120.2	125.3	132.4	136.6	44.7	843.4
45°	99.4	94.4	85.5	81.0	83.2	90.3	95.8	34.4	877.7
50°	79.8	74.4	64.7	58.7	59.3	65.8	72.1	27.9	905.7
55°	65.2	60.1	51.3	45.2	44.8	50.3	56.0	23.4	929.0
60°	52.4	48.1	41.3	36.1	35.0	38.9	43.4	19.6	948.6
65°	41.2	37.9	33.1	29.2	27.7	29.8	32.8	16.1	964.7
70°	31.9	29.5	26.2	23.4	21.7	22.1	23.6	12.9	977.6
75°	24.4	22.6	20.2	18.2	16.5	15.4	15.7	10.0	987.6
80°	18.3	17.0	15.2	13.6	11.8	9.9	9.2	7.3	994.9
85°	13.3	12.5	11.1	9.7	7.7	5.4	4.2	5.0	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Protected	Order number: 51TD11MN495G EAN: 4058352928585	LP number 58526_230
--	--	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	16.6	17.8	16.9	18.1	18.4	16.4	17.7	16.8	18.0	18.3
	3H	17.7	18.8	18.1	19.1	19.5	17.3	18.4	17.7	18.7	19.1
	4H	18.2	19.2	18.6	19.6	19.9	17.7	18.7	18.1	19.1	19.4
	6H	18.7	19.6	19.1	20.0	20.4	18.0	18.9	18.4	19.3	19.7
	8H	19.0	19.8	19.5	20.2	20.6	18.2	19.0	18.6	19.3	19.7
	12H	19.3	20.0	19.7	20.4	20.8	18.3	19.0	18.7	19.4	19.8
4H	2H	16.8	17.8	17.2	18.2	18.5	16.7	17.7	17.1	18.0	18.4
	3H	18.1	19.0	18.5	19.3	19.8	17.7	18.6	18.2	19.0	19.4
	4H	18.8	19.5	19.2	19.9	20.4	18.2	19.0	18.7	19.4	19.8
	6H	19.4	20.0	19.9	20.5	21.0	18.6	19.3	19.1	19.7	20.2
	8H	19.7	20.3	20.2	20.8	21.2	18.8	19.3	19.3	19.8	20.3
	12H	20.1	20.6	20.6	21.0	21.5	18.9	19.4	19.4	19.8	20.3
8H	4H	18.9	19.5	19.4	19.9	20.4	18.4	19.0	18.9	19.4	19.9
	6H	19.7	20.2	20.2	20.6	21.2	19.0	19.4	19.5	19.9	20.4
	8H	20.1	20.5	20.6	21.0	21.6	19.2	19.6	19.7	20.1	20.6
	12H	20.6	20.9	21.1	21.4	22.0	19.4	19.7	19.9	20.2	20.8
12H	4H	19.0	19.4	19.5	19.9	20.4	18.5	19.0	19.0	19.4	19.9
	6H	19.8	20.2	20.3	20.6	21.2	19.1	19.4	19.6	19.9	20.5
	8H	20.2	20.6	20.8	21.1	21.6	19.3	19.7	19.9	20.2	20.7

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1480	H(C0) = 13	H(C180) = 13
			B = 78	H(C90) = 0	H(C270) = 0


C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		10419.4	9941.9	9132.0	8862.0	9394.4	10582.4	11708.2	
50°		8954.2	8391.7	7426.5	6924.6	7253.5	8422.4	9695.1	
55°		7934.3	7361.1	6414.2	5830.8	6037.7	7139.9	8446.6	
60°		7028.4	6509.7	5715.0	5178.0	5282.3	6260.0	7501.6	
65°		6212.9	5769.3	5176.0	4765.9	4803.3	5587.7	6715.2	
70°		5535.7	5163.3	4741.7	4463.1	4472.4	4985.0	5957.7	
75°		5025.8	4715.7	4395.5	4221.7	4207.5	4438.2	5259.5	
80°		4674.0	4422.1	4156.8	4062.2	3980.2	3956.4	4574.3	
85°		4531.1	4370.3	4158.2	4099.9	3935.2	3608.8	4128.4	

Photometric test report

Family Licross® 11 Protected	Order number: 51TD11MN495G EAN: 4058352928585	LP number 58526_230
---	--	--------------------------------------

Luminance values in cd/m²

γ 65°
γ 70°
γ 75°
γ 80°
γ 85°



Photometric test report

Family
Licross® 11 Protected

Order number: 51TD11MN495G
EAN: 4058352928585

LP number
58526_230

Multilumen Table

environmental temperature: 25°C

siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
1	A	C	E	9980	55.3
2	A	C	F	9469	52.1
3	A	D	E	9032	49.4
4	A	D	F	8510	46.3
5	B	C	E	7978	43.1
6	B	C	F	7530	40.5
7	B	D	E	6998	37.4
8	B	D	F	6529	34.7