




Photometric test report

Family Monsun® 12	Order number: 51FP208P460H EAN: 4058352389799	LP number 59060_109
	Version prismatic diffuser, opal, polycarbonate, wide distribution	serial documentation 12.12.2023
	Lamps LED 4000 K CRI ≥ 80 Controlgear ECG Rated values Net luminous flux = 5490 lm Power consumption = 33.9 W Luminous efficacy = 161.9 lm/W	
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 319 cd/klm**



Classifications	
DIN 5040	A 4 1
CIE	N1=45 N2=75 N3=93 N4=94 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	93.7%
ϕ_o	6.3%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 12	Order number: 51FP208P460H EAN: 4058352389799	LP number 59060_109
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	319.4	319.4	319.4	319.4	319.4	319.4	319.4	1.9	1.9
5°	319.1	317.8	316.0	317.2	318.6	318.6	318.8	15.2	17.1
10°	313.9	312.8	311.0	312.1	313.5	313.5	313.7	29.8	46.9
15°	305.6	304.7	302.7	303.7	305.0	304.9	305.2	43.2	90.1
20°	294.3	293.5	291.4	292.2	293.3	293.1	293.5	54.9	145.0
25°	280.9	280.2	277.7	277.9	278.8	278.5	278.8	64.6	209.6
30°	265.9	265.3	262.4	261.6	261.9	261.4	261.7	72.0	281.6
35°	249.2	248.5	245.6	243.7	242.9	242.2	242.4	77.0	358.5
40°	231.6	230.8	227.5	224.6	222.7	221.4	221.6	79.5	438.0
45°	212.9	211.8	208.5	204.2	201.3	199.0	199.4	79.5	517.5
50°	193.7	192.3	188.8	183.7	179.4	175.9	176.0	77.3	594.9
55°	174.1	172.4	168.8	162.7	157.2	152.3	152.1	73.1	667.9
60°	153.8	152.1	148.1	141.4	134.9	128.8	127.5	66.9	734.9
65°	133.1	131.4	127.0	119.9	112.8	105.5	102.8	59.2	794.0
70°	112.0	110.4	105.0	98.0	90.2	82.2	78.2	49.9	843.9
75°	90.5	88.8	83.0	75.7	67.3	58.8	53.6	39.3	883.2
80°	69.4	67.4	62.0	54.0	45.3	36.4	30.4	28.3	911.6
85°	51.2	49.1	43.8	35.9	26.7	17.7	11.3	18.6	930.2
90°	40.3	38.3	33.0	25.3	16.4	7.5	1.9	12.9	943.1
95°	36.9	35.1	30.2	22.8	14.1	5.6	1.6	11.6	954.7
100°	33.7	31.9	27.1	20.1	11.9	4.0	1.5	10.1	964.8
105°	30.1	28.5	23.8	17.3	9.5	2.6	1.3	8.6	973.4
110°	26.5	24.6	20.5	14.4	7.3	1.5	1.2	7.1	980.4
115°	22.8	21.1	17.3	11.6	5.2	1.3	1.2	5.7	986.1
120°	19.1	17.5	14.1	8.9	3.4	1.3	1.1	4.4	990.5
125°	15.4	13.9	10.8	6.2	1.7	1.2	1.0	3.2	993.6
130°	11.8	10.5	7.7	3.9	1.4	1.2	1.0	2.2	995.8
135°	8.3	7.2	5.0	2.0	1.4	1.2	1.1	1.4	997.2
140°	5.1	4.3	2.5	1.6	1.3	1.1	1.0	0.8	998.0
145°	2.4	2.0	1.8	1.6	1.4	1.2	1.2	0.5	998.5
150°	1.9	1.9	1.8	1.5	1.4	1.3	1.2	0.4	999.0
155°	1.8	1.8	1.6	1.5	1.4	1.3	1.3	0.4	999.3
160°	1.6	1.6	1.5	1.5	1.4	1.4	1.3	0.3	999.6
165°	1.5	1.5	1.4	1.4	1.4	1.4	1.3	0.2	999.8
170°	1.4	1.4	1.4	1.4	1.4	1.4	1.3	0.1	999.9
175°	1.3	1.3	1.3	1.4	1.4	1.4	1.3	0.1	1000.0
180°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.0	1000.0

Photometric test report

Family Monsun® 12	Order number: 51FP208P460H EAN: 4058352389799	LP number 59060_109
-----------------------------	--	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	20.0	21.7	20.4	22.1	22.4	19.8	21.6	20.2	21.9	22.2
	3H	21.8	23.4	22.2	23.7	24.1	21.4	23.0	21.8	23.3	23.6
	4H	22.7	24.1	23.1	24.5	24.9	22.0	23.5	22.4	23.8	24.2
	6H	23.4	24.7	23.8	25.1	25.5	22.4	23.8	22.8	24.2	24.6
	8H	23.7	25.0	24.1	25.4	25.8	22.6	23.9	23.0	24.2	24.6
	12H	24.0	25.2	24.4	25.6	26.0	22.6	23.9	23.1	24.3	24.7
4H	2H	20.8	22.2	21.1	22.6	23.0	20.6	22.1	21.0	22.4	22.8
	3H	22.8	24.0	23.2	24.4	24.8	22.4	23.6	22.8	24.0	24.4
	4H	23.7	24.9	24.2	25.3	25.7	23.1	24.3	23.5	24.7	25.1
	6H	24.6	25.6	25.0	26.0	26.5	23.6	24.6	24.1	25.1	25.5
	8H	25.0	25.9	25.4	26.4	26.8	23.8	24.7	24.3	25.2	25.6
	12H	25.4	26.2	25.8	26.6	27.1	23.9	24.8	24.4	25.2	25.7
8H	4H	24.1	25.0	24.5	25.4	25.9	23.5	24.5	24.0	24.9	25.4
	6H	25.1	25.9	25.6	26.3	26.8	24.2	25.0	24.7	25.5	26.0
	8H	25.6	26.3	26.1	26.8	27.3	24.4	25.2	24.9	25.6	26.1
	12H	26.1	26.7	26.6	27.2	27.7	24.6	25.2	25.1	25.7	26.2
12H	4H	24.1	25.0	24.6	25.4	25.9	23.6	24.4	24.1	24.9	25.4
	6H	25.2	25.9	25.7	26.4	26.9	24.4	25.0	24.9	25.5	26.0
	8H	25.7	26.3	26.2	26.8	27.4	24.6	25.2	25.2	25.7	26.3

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1590	H(C0) = 21	H(C180) = 21
			B = 87	H(C90) = 21	H(C270) = 21

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		9628.1	9614.9	9625.7	9714.1	9977.4	10387.1	11043.6	
50°		9288.5	9261.3	9275.9	9339.9	9570.5	9965.6	10696.4	
55°		8958.7	8914.8	8928.1	8954.8	9150.4	9515.6	10328.1	
60°		8606.3	8562.8	8559.2	8558.2	8715.1	9043.6	9894.7	
65°		8235.6	8189.5	8151.9	8126.2	8252.1	8527.0	9383.5	
70°		7813.9	7763.0	7654.5	7607.5	7677.7	7900.2	8753.6	
75°		7298.9	7233.8	7053.9	6944.5	6912.0	7041.3	7838.9	
80°		6698.1	6579.9	6377.1	6102.1	5914.6	5832.5	6473.8	
85°		6207.9	6041.8	5757.2	5341.6	4836.1	4322.1	4477.8	

Photometric test report

Family Monsun® 12	Order number: 51FP208P460H EAN: 4058352389799	LP number 59060_109
------------------------------------	--	--------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

siteco

