

Photometric test report

Family
Highbay 21

Order number: 52HN11DA4LLA02
EAN: 4069025421319

LP number
59724_171

serial
documentation
20.03.2025



Version primary light control with lens, PMMA, housing, white, for Licross® rail, narrow distribution, with Node BT

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 26500 lm
Power consumption = 143.1 W
Luminous efficacy = 185.2 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 2719 cd/klm



Classifications

DIN 5040 A 7 0
CIE N1=89 N2=97 N3=99
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 21	Order number: 52HN11DA4LLA02 EAN: 4069025421319	LP number 59724_171
Table of values for luminous intensities		Maximum luminous intensity

sitEco

C- planes	0,0° 180,0°	7,5° 172,5° 187,5° 352,5°	15,0° 165,0° 195,0° 345,0°	22,5° 157,5° 202,5° 337,5°	30,0° 150,0° 210,0° 330,0°	37,5° 142,5° 217,5° 322,5°	45,0° 135,0° 225,0° 315,0°
		Luminous intensity in cd/klm					
γ							
0,0°	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5
2,5°	2662.8	2671.1	2671.1	2670.6	2667.6	2663.3	2662.4
5,0°	2502.8	2490.9	2498.0	2494.5	2487.6	2479.1	2473.3
7,5°	2228.4	2233.8	2227.9	2223.2	2214.7	2203.4	2194.2
10,0°	1915.8	1894.8	1902.8	1897.9	1890.8	1880.8	1870.9
12,5°	1554.6	1560.7	1554.3	1552.6	1548.0	1540.2	1531.7
15,0°	1246.2	1237.0	1237.4	1238.4	1237.7	1233.9	1229.0
17,5°	947.1	964.7	959.6	960.0	960.5	959.5	958.4
20,0°	765.0	752.2	754.6	751.6	749.0	747.8	747.5
22,5°	591.2	598.6	590.3	583.2	577.5	573.8	572.1
25,0°	481.4	472.8	470.4	460.9	451.8	445.8	443.1
27,5°	370.5	376.3	371.1	363.9	355.1	347.9	344.8
30,0°	301.2	297.9	295.0	290.6	284.7	279.0	275.2
32,5°	234.8	237.8	234.9	232.8	229.2	225.3	220.4
35,0°	189.2	188.5	187.7	186.9	184.4	180.6	175.3
37,5°	154.0	153.7	151.7	151.0	148.4	144.9	141.0
40,0°	125.7	123.3	123.0	121.9	119.1	115.8	113.2
42,5°	99.2	100.3	99.3	98.6	95.9	92.9	90.7
45,0°	81.4	79.6	79.7	79.0	77.2	74.6	72.7
47,5°	64.2	64.9	64.5	64.0	62.8	60.9	59.5
50,0°	52.5	51.6	51.8	51.7	51.0	49.9	49.1
52,5°	41.7	41.9	41.8	42.1	41.9	41.4	40.9
55,0°	33.9	33.5	34.1	34.8	35.0	35.0	34.7
57,5°	27.1	27.4	28.1	29.2	29.7	29.7	29.6
60,0°	22.3	22.3	23.0	24.6	25.8	25.8	25.5
62,5°	19.0	19.2	19.6	20.7	22.4	22.3	22.0
65,0°	17.0	16.8	17.2	18.3	19.8	19.1	19.1
67,5°	14.7	14.8	14.9	16.1	17.2	16.3	16.1
70,0°	12.8	12.5	12.6	13.8	14.3	13.8	13.9
72,5°	11.3	11.1	10.9	11.6	11.4	11.2	11.7
75,0°	9.7	9.3	8.9	9.6	9.3	9.1	9.3
77,5°	7.4	7.4	7.1	7.5	7.1	6.8	7.1
80,0°	4.9	4.7	4.8	4.8	4.5	4.5	4.8
82,5°	2.2	2.3	2.3	2.4	2.4	2.5	2.7
85,0°	0.8	0.8	0.8	0.8	0.8	0.9	1.0
87,5°	0.4	0.4	0.4	0.4	0.4	0.4	0.4

Photometric test report

Family Highbay 21	Order number: 52HN11DA4LLA02 EAN: 4069025421319	LP number 59724_171
Table of values for luminous intensities		Maximum luminous intensity

sitEco

C- planes	52,5° 127,5° 232,5° 307,5°	60,0° 120,0° 240,0° 300,0°	67,5° 112,5° 247,5° 292,5°	75,0° 105,0° 255,0° 285,0°	82,5° 97,5° 262,5° 277,5°	90,0° 270,0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0,0°	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5	4.1	4.1
2,5°	2661.4	2660.0	2657.7	2657.0	2651.0	2647.2	31.8	35.9
5,0°	2468.0	2461.9	2456.3	2452.9	2444.7	2440.4	59.1	95.0
7,5°	2185.5	2176.0	2168.0	2162.0	2152.6	2148.3	78.5	173.5
10,0°	1860.3	1847.8	1837.7	1831.0	1822.1	1817.6	88.9	262.4
12,5°	1522.0	1510.4	1500.7	1495.5	1488.9	1485.2	90.6	353.0
15,0°	1223.0	1215.3	1207.9	1204.2	1200.8	1197.6	86.8	439.8
17,5°	955.3	949.4	945.6	944.9	945.8	944.0	78.6	518.5
20,0°	745.4	741.8	741.4	743.7	748.0	747.7	70.2	588.6
22,5°	571.4	571.2	573.5	575.9	579.7	580.1	60.8	649.4
25,0°	443.2	444.5	446.3	448.3	449.2	448.8	52.5	701.9
27,5°	344.0	344.5	345.1	346.1	344.9	343.6	44.7	746.7
30,0°	273.7	273.8	273.9	272.4	270.2	268.2	38.5	785.2
32,5°	217.7	217.2	215.9	213.7	211.0	209.4	32.9	818.1
35,0°	172.5	170.5	168.2	166.4	165.0	164.5	27.8	845.9
37,5°	138.1	135.6	133.3	132.0	130.7	130.3	23.7	869.5
40,0°	110.2	108.1	106.1	104.8	103.7	103.1	20.0	889.6
42,5°	88.5	86.8	85.0	83.9	83.2	82.7	16.9	906.5
45,0°	71.2	69.8	68.4	67.3	66.9	66.6	14.2	920.7
47,5°	58.5	57.3	56.0	55.1	54.8	54.6	12.1	932.8
50,0°	48.3	47.1	46.0	45.5	45.1	44.8	10.3	943.0
52,5°	40.2	39.3	38.3	37.7	37.1	36.8	8.7	951.8
55,0°	34.1	33.4	32.5	31.7	31.0	30.7	7.5	959.3
57,5°	29.3	29.0	28.2	27.0	26.3	26.1	6.6	965.9
60,0°	25.7	25.8	24.8	23.5	22.8	22.6	5.8	971.6
62,5°	22.4	22.9	21.8	20.7	20.1	19.9	5.1	976.8
65,0°	19.6	20.2	19.7	18.4	17.9	17.8	4.6	981.4
67,5°	16.7	17.6	17.8	16.4	16.0	16.0	4.1	985.5
70,0°	14.1	15.0	15.6	14.4	14.4	14.6	3.6	989.1
72,5°	11.7	12.4	13.4	12.9	13.2	13.4	3.1	992.3
75,0°	9.5	10.4	12.0	11.4	11.8	11.9	2.7	995.0
77,5°	7.2	8.1	9.6	9.6	10.0	10.2	2.1	997.1
80,0°	5.1	5.7	7.0	7.5	7.6	8.0	1.5	998.6
82,5°	3.0	3.6	4.5	5.0	5.3	5.6	0.9	999.5
85,0°	1.2	1.7	2.3	2.7	3.1	3.3	0.4	999.9
87,5°	0.4	0.4	0.5	0.6	0.8	0.9	0.1	1000.1

Photometric test report

Family Highbay 21			Order number: 52HN11DA4LLA02 EAN: 4069025421319							LP number 59724_171		
UGR-Table			Standard room							siteco		
Reflection factor of ceiling			0.7	0.7	0.5	0.5	0.3	0.7	0.7			0.5
Reflection factor of walls			0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor			0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions			View crosswise (C0)					View endwise (C90)				
x		y										
2H	2H	18.6	19.7	19.0	20.0	20.4	18.0	19.2	18.4	19.5	19.8	
	3H	19.0	20.0	19.4	20.3	20.7	18.7	19.7	19.1	20.0	20.4	
	4H	19.2	20.1	19.6	20.5	20.9	19.1	20.0	19.5	20.4	20.7	
	6H	19.4	20.2	19.8	20.6	21.0	19.5	20.3	19.9	20.7	21.1	
	8H	19.5	20.2	19.9	20.6	21.0	19.8	20.4	20.2	20.8	21.2	
	12H	19.5	20.1	19.9	20.5	20.9	19.8	20.4	20.3	20.8	21.3	
4H	2H	18.8	19.7	19.2	20.0	20.4	18.3	19.2	18.7	19.5	19.9	
	3H	19.3	20.1	19.8	20.5	20.9	19.1	19.9	19.6	20.3	20.7	
	4H	19.7	20.3	20.1	20.7	21.2	19.7	20.3	20.1	20.8	21.2	
	6H	19.9	20.4	20.4	20.9	21.4	20.2	20.8	20.7	21.2	21.7	
	8H	19.9	20.4	20.4	20.9	21.3	20.4	20.9	20.9	21.3	21.8	
	12H	19.9	20.3	20.4	20.8	21.3	20.5	20.9	21.0	21.4	21.9	
8H	4H	19.8	20.2	20.2	20.7	21.2	19.8	20.3	20.3	20.7	21.2	
	6H	20.0	20.4	20.5	20.9	21.4	20.4	20.8	20.9	21.2	21.8	
	8H	20.0	20.4	20.6	20.9	21.4	20.6	21.0	21.1	21.4	22.0	
	12H	20.0	20.3	20.6	20.8	21.4	20.8	21.1	21.3	21.6	22.1	
12H	4H	19.8	20.2	20.3	20.6	21.1	19.8	20.2	20.3	20.6	21.1	
	6H	20.0	20.4	20.6	20.9	21.4	20.4	20.7	20.9	21.2	21.7	
	8H	20.1	20.3	20.6	20.8	21.4	20.6	20.9	21.1	21.4	21.9	

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:			L = 426 B = 264			
C-planes	0,0° 180,0°	10,0° 170,0° 190,0° 350,0°	20,0° 160,0° 200,0° 340,0°	30,0° 150,0° 210,0° 330,0°	40,0° 140,0° 220,0° 320,0°	50,0° 130,0° 230,0° 310,0°	60,0° 120,0° 240,0° 300,0°	70,0° 110,0° 250,0° 290,0°	80,0° 100,0° 260,0° 280,0°	90,0° 270,0°
γ	Luminance in cd/m²									
45,0°	27122.5	26477.6	26442.3	25729.2	24622.1	23887.9	23272.6	22654.8	22333.6	22186.0
50,0°	19226.9	18905.7	18989.0	18691.7	18188.6	17834.3	17268.0	16774.8	16569.6	16411.3
55,0°	13927.7	13795.0	14214.5	14398.1	14334.0	14082.2	13732.6	13244.1	12797.0	12629.1
60,0°	10522.8	10589.6	11350.0	12180.7	12104.6	12081.6	12165.2	11517.0	10836.2	10661.8
65,0°	9499.5	9420.5	9954.9	11014.4	10619.9	10807.6	11270.3	10792.7	10067.8	9948.4
70,0°	8810.1	8618.6	9307.4	9831.2	9481.3	9605.4	10340.3	10600.2	9903.5	10041.3
75,0°	8806.4	8334.0	8633.7	8475.9	8273.0	8556.7	9432.7	11002.3	10675.6	10843.0
80,0°	6647.7	6395.6	6575.9	6164.6	6220.4	6682.3	7782.1	9870.0	10200.0	10804.0
85,0°	2184.5	2128.6	2176.4	2208.8	2442.5	2963.1	4531.2	6532.4	8048.5	8967.7

Photometric test report

Family Highbay 21	Order number: 52HN11DA4LLA02 EAN: 4069025421319	LP number 59724_171
------------------------------------	--	--------------------------------------

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 21	Order number: 52HN11DA4LLA02 EAN: 4069025421319	LP number 59724_171
Dimming levels table environmental temperature: 25°C		

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	26500	143.1
95	240	252	25141	135.1
90	227	250	23858	127.6
85	214	248	22571	120.2
80	200	245	21174	112.2
75	187	243	19866	104.9
70	174	240	18545	97.5
65	161	237	17219	90.2
60	148	234	15875	83.0
55	135	231	14529	75.7
50	123	227	13272	69.2
45	110	223	11900	62.0
40	98	219	10632	55.2
35	85	214	9243	48.1
30	73	208	7956	41.6
25	61	202	6658	35.1
20	48	193	5246	28.1
15	36	182	3931	21.7
10	24	168	2613	15.2
5	12	142	1286	8.4
2	5	110	507	4.6