



# Photometric test report

<b>Family</b> <b>Trunking Flex 31</b>	<b>Order number: 51RF12MB49XG5</b> <b>EAN: 4069025494467</b>	<b>LP number</b> <b>59302_244</b>
	<b>Version</b> primary light control with lens, transparent, PMMA, wide distribution <b>Lamps</b> LED 4000 K   CRI ≥ 80 <b>Controlgear</b> ECG Multilumen <b>Rated values</b> Net luminous flux = 9100 lm Power consumption = 50.7 W Luminous efficacy = 179.5 lm/W	<b>serial documentation</b> <b>01.08.2025</b>
		

**Luminous intensity in cd/klm** C180-0 C270-90 **Imax: 482 cd/klm**



Classifications	
DIN 5040	A 5 2
CIE	N1=64 N2=91 N3=98 N4=99 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	99.1%
$\phi_o$	0.9%

Measurement conditions
DIN EN 13032 and DIN 5032

## Photometric test report

Family Trunking Flex 31	Order number: 51RF12MB49XG5 EAN: 4069025494467	LP number 59302_244
Table of values for luminous intensities		Maximum luminous intensity
		<b>siteco</b>

C-planes $\gamma$	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	477.4	477.4	477.4	477.4	477.4	477.4	477.4	2.9	2.9
5°	479.2	479.4	476.1	476.9	477.7	479.1	480.6	22.8	25.7
10°	478.5	478.8	475.9	476.7	478.1	479.7	481.9	45.5	71.2
15°	473.7	474.6	472.3	472.8	474.3	476.3	478.1	67.3	138.5
20°	463.3	464.4	462.2	462.5	463.5	465.9	467.9	87.0	225.5
25°	446.5	446.1	441.7	442.3	444.6	445.0	446.7	102.9	328.5
30°	417.9	412.9	407.0	410.2	413.2	410.4	409.4	112.7	441.2
35°	373.8	365.6	358.8	365.1	368.4	362.5	359.0	114.6	555.7
40°	307.6	307.1	302.9	303.0	299.1	300.3	301.2	106.7	662.4
45°	238.0	232.2	241.2	229.3	232.4	226.8	239.9	90.5	752.9
50°	179.0	175.4	175.4	172.2	173.6	171.0	175.3	73.1	826.0
55°	127.6	127.0	119.9	124.4	123.4	123.3	117.8	55.4	881.5
60°	86.5	87.3	81.4	85.4	84.1	84.7	79.6	40.0	921.5
65°	57.4	58.2	54.6	57.2	56.0	56.8	53.2	28.0	949.5
70°	37.6	37.8	35.9	37.4	36.6	36.7	34.5	18.9	968.4
75°	23.7	23.8	22.9	23.5	22.9	22.8	21.3	12.2	980.6
80°	13.7	13.5	13.1	13.2	12.8	12.3	11.3	7.0	987.6
85°	6.4	6.2	5.9	5.7	5.2	4.6	4.0	3.0	990.6
90°	2.2	2.1	2.0	1.7	1.4	1.0	0.6	0.9	991.5
95°	1.8	1.7	1.7	1.5	1.2	0.8	0.5	0.7	992.2
100°	2.3	2.3	2.1	1.7	1.3	0.8	0.5	0.9	993.0
105°	2.1	2.1	2.0	1.7	1.3	0.7	0.5	0.8	993.9
110°	2.3	2.3	2.0	1.7	1.2	0.6	0.4	0.8	994.6
115°	2.2	2.1	1.9	1.7	1.1	0.7	0.5	0.7	995.4
120°	2.3	2.0	1.7	1.5	1.1	0.7	0.7	0.7	996.0
125°	2.7	2.1	1.8	1.4	1.0	0.7	0.7	0.7	996.7
130°	2.0	1.9	2.0	1.4	1.1	0.9	0.9	0.6	997.3
135°	2.0	1.9	1.8	1.5	1.2	1.2	1.2	0.6	997.9
140°	2.0	2.0	1.8	1.6	1.4	1.4	1.4	0.6	998.5
145°	2.1	2.0	1.9	1.7	1.6	1.6	1.6	0.6	999.1
150°	2.1	2.1	1.9	1.8	1.8	1.8	1.8	0.5	999.6
155°	1.9	1.9	1.8	1.8	1.8	1.8	1.8	0.4	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

Family Trunking Flex 31	Order number: 51RF12MB49XG5 EAN: 4069025494467	LP number 59302_244
----------------------------	---	------------------------

UGR-Table	Standard room	siteco	
-----------	---------------	--------	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	22.4	23.9	22.8	24.3	24.6	22.5	24.0	22.9	24.3	24.6
	3H	22.9	24.3	23.3	24.6	24.9	23.0	24.3	23.4	24.7	25.0
	4H	23.1	24.3	23.5	24.7	25.0	23.2	24.4	23.6	24.8	25.1
	6H	23.2	24.3	23.6	24.7	25.1	23.3	24.4	23.7	24.8	25.2
	8H	23.2	24.3	23.7	24.7	25.1	23.3	24.4	23.7	24.7	25.1
	12H	23.2	24.2	23.7	24.6	25.0	23.3	24.3	23.8	24.7	25.1
4H	2H	22.7	24.0	23.1	24.3	24.7	22.8	24.0	23.2	24.4	24.7
	3H	23.3	24.3	23.7	24.7	25.1	23.4	24.4	23.8	24.8	25.2
	4H	23.5	24.4	23.9	24.8	25.3	23.6	24.5	24.1	24.9	25.4
	6H	23.7	24.5	24.1	24.9	25.4	23.8	24.6	24.2	25.0	25.5
	8H	23.7	24.4	24.2	24.9	25.4	23.8	24.5	24.3	25.0	25.5
	12H	23.8	24.4	24.2	24.8	25.3	23.8	24.5	24.3	24.9	25.4
8H	4H	23.6	24.3	24.0	24.7	25.2	23.7	24.4	24.1	24.8	25.3
	6H	23.8	24.4	24.3	24.8	25.3	23.9	24.5	24.4	24.9	25.4
	8H	23.8	24.4	24.3	24.8	25.4	23.9	24.5	24.4	24.9	25.5
	12H	23.9	24.3	24.4	24.8	25.4	24.0	24.4	24.5	24.9	25.5
12H	4H	23.6	24.2	24.1	24.7	25.2	23.7	24.3	24.2	24.8	25.3
	6H	23.8	24.3	24.3	24.8	25.3	23.9	24.4	24.4	24.9	25.4
	8H	23.9	24.3	24.4	24.8	25.3	24.0	24.4	24.5	24.9	25.4

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1433 B = 61	H(C0) = 5 H(C90) = 5	H(C180) = 5 H(C270) = 5
-----------------	---------------------------------	-------------------------------	--------------------	-------------------------	----------------------------

C-planes	$\gamma$	Luminance in cd/m <sup>2</sup>							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
	45°	32380.7	31656.9	33100.6	31837.3	32772.4	32587.3	35198.3	
	50°	26415.5	25933.4	26145.2	26018.6	26714.1	26913.6	28267.2	
	55°	20736.5	20686.4	19712.2	20783.6	21074.5	21619.0	21272.9	
	60°	15777.1	15968.5	15058.2	16097.7	16271.9	16916.1	16478.7	
	65°	12028.4	12227.7	11641.7	12480.4	12600.4	13281.2	13011.8	
	70°	9338.3	9440.4	9113.4	9774.6	9943.2	10475.9	10404.4	
	75°	7309.3	7355.1	7230.6	7716.2	7913.0	8381.6	8467.6	
	80°	5592.5	5566.6	5555.1	5882.6	6126.7	6455.8	6630.6	
	85°	3976.4	3877.2	3873.0	4004.4	4145.3	4298.5	4554.4	

**Photometric test report**


**Family**  
Trunking Flex 31

**Order number: 51RF12MB49XG5**  
**EAN: 4069025494467**

**LP number**  
**59302\_244**

**Luminance values in cd/m<sup>2</sup>**

γ 65°    γ 70°    γ 75°    γ 80°    γ 85°



## Photometric test report

Family <b>Trunking Flex 31</b>	Order number: <b>51RF12MB49XG5</b> EAN: <b>4069025494467</b>	LP number <b>59302_244</b>
-----------------------------------	---	-------------------------------

<b>Multilumen Table</b>	environmental temperature: 25°C	<b>sITeco</b>
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
13	ON	ON	OFF	ON	9100	50.7
10	ON	OFF	ON	OFF	7580	42.7
8	ON	OFF	OFF	OFF	6680	37.5
6	OFF	ON	ON	OFF	5740	32.2
4	OFF	ON	OFF	OFF	4820	27.0
2	OFF	OFF	ON	OFF	3880	22.0