Photometric test report

Family
Apollon® 21

Order number: 51MQ12HC2L55
EAN: 4069025336347

LP number
59880_3

serial documentation
30.10.2025

Version	recessed luminaire for lay-in mounting, square M600, wide distribution, UGR≤19 (L65≤3000cd/m²), adjustable color temperature: 3000 K | 4000 K
Lamps	LED 4000 K | CRI ≥ 90
Controlgear	ECG-DALI
Setting	factory setting: DIP-Step=7, colour temperature 4000K
Rated values	Net luminous flux = 4660 lm Power consumption = 31.8 W Luminous efficacy = 146.5 lm/W

siteco

Luminous intensity in cd/klm

C180-0 C270-90

Imax: 468 cd/klm



Classifications

DIN 5040	A 5 0
CIE	N1=62 N2=87 N3=97 N4=100 N5=100

Luminaire light output ratios

ηLB	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family	Order number: 51MQ12HC2L55	LP number
Apollon® 21	EAN: 4069025336347	59880_3

siteco

Table of values for luminous intensities

Maximum luminous intensity

C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	468.4	468.4	468.4	468.4	468.4	468.4	468.4	2.8	2.8
5°	466.5	466.3	466.1	466.0	466.0	466.0	466.1	22.3	25.1
10°	460.2	460.0	459.9	459.8	459.7	459.7	459.7	43.8	68.8
15°	449.8	449.8	449.7	449.6	449.6	449.6	449.6	63.8	132.6
20°	435.7	435.8	435.9	435.9	435.7	435.5	435.3	81.7	214.3
25°	417.4	417.4	417.4	417.4	417.3	417.2	417.1	96.7	311.0
30°	393.4	393.3	393.2	393.1	393.3	393.5	393.6	107.8	418.8
35°	358.8	359.3	359.8	360.4	360.9	361.5	362.1	113.3	532.1
40°	299.7	301.2	302.3	304.1	306.3	309.2	311.7	107.4	639.5
45°	232.3	229.8	227.3	224.9	227.7	230.5	233.4	88.7	728.2
50°	153.1	157.3	162.2	165.7	168.7	170.3	172.6	69.1	797.3
55°	101.0	108.0	116.4	121.9	126.1	127.4	130.1	53.5	850.8
60°	69.7	77.3	85.0	92.6	95.1	97.5	100.0	42.1	892.9
65°	52.7	59.7	66.8	73.8	75.1	76.4	77.6	34.5	927.4
70°	47.7	51.1	54.5	57.9	57.1	56.3	55.4	28.2	955.6
75°	39.0	40.4	41.7	43.0	41.3	39.7	38.0	21.6	977.2
80°	27.0	27.5	28.1	28.7	28.0	27.3	26.5	15.0	992.1
85°	13.5	13.6	13.7	13.7	13.9	14.1	14.3	7.5	999.7
90°	0.5	0.6	0.6	0.6	0.6	0.6	0.5	0.3	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family	Order number: 51MQ12HC2L55	LP number
Apollon® 21	EAN: 4069025336347	59880_3

siteco

UGR-Table

Standard room

Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions x	y	View crosswise (C0)					View endwise (C90)				
2H	2H	15.5	17.1	15.9	17.4	17.7	16.3	17.8	16.6	18.1	18.4
	3H	16.4	17.8	16.8	18.1	18.5	17.3	18.7	17.6	19.0	19.3
	4H	16.9	18.2	17.3	18.6	19.0	17.7	19.0	18.1	19.3	19.7
	6H	17.5	18.7	17.9	19.0	19.4	18.1	19.3	18.5	19.6	20.0
	8H	17.7	18.8	18.2	19.2	19.6	18.3	19.4	18.7	19.8	20.2
	12H	17.9	18.9	18.3	19.3	19.7	18.5	19.5	18.9	19.9	20.3
4H	2H	16.1	17.4	16.5	17.7	18.1	16.7	18.0	17.1	18.3	18.7
	3H	17.2	18.3	17.6	18.7	19.1	17.9	19.0	18.3	19.4	19.8
	4H	17.9	18.9	18.4	19.3	19.7	18.5	19.5	18.9	19.9	20.3
	6H	18.6	19.4	19.0	19.9	20.3	19.0	19.9	19.5	20.3	20.8
	8H	18.9	19.6	19.3	20.1	20.6	19.3	20.0	19.7	20.5	21.0
	12H	19.1	19.8	19.6	20.2	20.7	19.5	20.2	20.0	20.6	21.1
8H	4H	18.3	19.0	18.7	19.5	20.0	18.8	19.5	19.2	20.0	20.5
	6H	19.1	19.7	19.6	20.2	20.7	19.5	20.1	20.0	20.6	21.1
	8H	19.5	20.0	20.0	20.5	21.0	19.8	20.4	20.3	20.9	21.4
	12H	19.8	20.3	20.3	20.8	21.3	20.1	20.6	20.6	21.1	21.6
12H	4H	18.3	19.0	18.8	19.5	20.0	18.8	19.5	19.3	20.0	20.4
	6H	19.2	19.8	19.7	20.2	20.8	19.6	20.1	20.1	20.6	21.1
	8H	19.6	20.1	20.2	20.6	21.1	19.9	20.4	20.5	20.9	21.5

Luminance table

Max. for $\gamma >= 65°$

Photometric dimensions in mm: L = 552, B = 552

C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	5023.6	4970.3	4916.9	4863.5	4924.9	4986.3	5047.8
50°	3641.6	3742.1	3858.0	3943.2	4013.2	4052.6	4107.3
55°	2693.1	2879.0	3102.5	3250.7	3361.4	3396.8	3469.8
60°	2131.0	2364.9	2598.6	2832.5	2908.0	2983.5	3059.0
65°	1907.5	2161.8	2416.0	2670.2	2716.6	2763.0	2809.4
70°	2130.7	2283.6	2436.4	2589.2	2552.5	2515.8	2479.1
75°	2306.8	2384.3	2461.9	2539.4	2441.7	2344.0	2246.3
80°	2375.2	2425.2	2475.3	2525.3	2462.8	2400.2	2337.7
85°	2376.1	2386.1	2396.3	2406.3	2440.7	2475.2	2509.6

Photometric test report

Family	Order number: 51MQ12HC2L55	LP number
Apollon® 21	**EAN: 4069025336347**	**59880_3**

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°

siteco



Photometric test report

Family	Order number: 51MQ12HC2L55	LP number
Apollon® 21	**EAN: 4069025336347**	**59880_3**

siteco

Multilumen Table

environmental temperature: 25°C

DIP-Step	Switch Setting 1	2	3	4	Luminous flux [lm]	Power consumption [W]
0	OFF	OFF	OFF	OFF	5780	39.8
1	ON	OFF	OFF	OFF	5500	37.8
2	OFF	ON	OFF	OFF	5220	35.8
4	OFF	OFF	ON	OFF	4940	33.8
7	ON	ON	ON	OFF	4660	31.8
8	OFF	OFF	OFF	ON	4380	29.8
10	OFF	ON	OFF	ON	4190	28.4
12	OFF	OFF	ON	ON	3900	26.4
13	ON	OFF	ON	ON	3620	24.4
14	OFF	ON	ON	ON	3330	22.4