Photometric test report

Family
Apollon® 21

Order number: 51MQ13WD2M55
EAN: 4069025468604

LP number
59881_2

serial documentation
30.10.2025

Version	recessed luminaire, square, wide distribution, UGR≤22, adjustable color temperature: 3000 K | 4000 K
Lamps	LED 3000 K | CRI ≥ 80
Controlgear	ECG-DALI
Setting	individual position: DIP-Step=8, colour temperature 3000K
Rated values	Net luminous flux = 1930 lm Power consumption = 16.2 W Luminous efficacy = 119.1 lm/W

siteco

Luminous intensity in cd/klm

C180-0 C270-90

Imax: 445 cd/klm



Classifications

DIN 5040	A 5 0
CIE	N1=60 N2=88 N3=97 N4=100 N5=100

Luminaire light output ratios

ηLB	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family	Order number: 51MQ13WD2M55	LP number
Apollon® 21	EAN: 4069025468604	59881_2

siteco

Table of values for luminous intensities

Maximum luminous intensity

C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	445.3	445.3	445.3	445.3	445.3	445.3	445.3	2.7	2.7
5°	443.4	443.2	443.0	442.7	442.4	442.3	442.3	21.2	23.8
10°	438.1	437.6	437.1	436.6	436.3	436.0	435.7	41.6	65.4
15°	429.0	428.5	427.9	427.1	426.3	426.0	425.8	60.6	126.0
20°	417.0	416.0	415.1	414.2	413.4	412.9	412.6	77.7	203.7
25°	401.5	400.5	399.4	398.1	396.9	396.2	395.8	92.3	295.9
30°	381.3	380.1	378.8	377.1	375.5	374.7	374.2	103.4	399.4
35°	355.6	353.5	351.6	350.0	348.6	347.1	345.6	110.1	509.5
40°	321.4	318.2	315.4	314.0	312.5	309.7	306.4	110.6	620.1
45°	267.1	261.2	255.3	255.4	255.4	249.9	244.3	99.0	719.1
50°	188.8	184.0	179.2	182.7	186.3	178.9	171.6	76.4	795.5
55°	154.0	131.3	108.5	131.4	154.3	129.3	104.2	58.7	854.1
60°	121.2	102.0	82.9	97.9	112.9	97.1	81.4	47.0	901.1
65°	80.8	75.8	70.8	70.3	69.8	68.2	66.6	35.5	936.6
70°	50.4	53.0	55.6	48.5	41.4	46.7	52.0	25.5	962.1
75°	35.5	36.8	38.2	35.4	33.0	31.9	31.3	18.4	980.5
80°	30.5	27.0	23.6	24.9	26.3	24.0	21.8	13.7	994.1
85°	14.0	12.1	10.2	10.0	9.8	9.0	8.2	5.6	999.8
90°	0.7	0.6	0.4	0.3	0.3	0.2	0.2	0.2	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family	Order number: 51MQ13WD2M55	LP number
Apollon® 21	EAN: 4069025468604	59881_2

siteco

UGR-Table

Standard room

Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	19.5	21.1	19.9	21.4	21.7	19.4	20.9	19.7	21.2	21.5
	3H	20.4	21.8	20.8	22.1	22.5	20.1	21.5	20.5	21.8	22.2
	4H	20.7	22.0	21.1	22.4	22.7	20.4	21.7	20.8	22.0	22.4
	6H	21.1	22.3	21.6	22.7	23.1	20.7	21.9	21.1	22.2	22.6
	8H	21.4	22.5	21.8	22.9	23.3	20.8	21.9	21.2	22.3	22.7
	12H	21.6	22.6	22.0	23.0	23.4	20.9	21.9	21.3	22.3	22.7
4H	2H	19.9	21.2	20.3	21.5	21.9	19.7	21.0	20.1	21.4	21.7
	3H	21.0	22.1	21.4	22.4	22.9	20.6	21.7	21.0	22.1	22.5
	4H	21.4	22.4	21.9	22.8	23.3	21.0	22.0	21.4	22.4	22.8
	6H	22.0	22.8	22.5	23.3	23.7	21.4	22.3	21.9	22.7	23.2
	8H	22.3	23.1	22.8	23.5	24.0	21.6	22.4	22.1	22.8	23.3
	12H	22.5	23.2	23.0	23.6	24.1	21.7	22.4	22.2	22.9	23.4
8H	4H	21.6	22.4	22.1	22.8	23.3	21.2	22.0	21.7	22.4	22.9
	6H	22.3	22.9	22.8	23.4	23.9	21.8	22.5	22.3	23.0	23.5
	8H	22.6	23.2	23.1	23.7	24.2	22.1	22.7	22.6	23.1	23.7
	12H	22.9	23.4	23.4	23.9	24.4	22.3	22.7	22.8	23.2	23.8
12H	4H	21.7	22.3	22.1	22.8	23.3	21.3	21.9	21.8	22.4	22.9
	6H	22.4	22.9	22.9	23.4	23.9	21.9	22.5	22.4	23.0	23.5
	8H	22.7	23.2	23.3	23.7	24.2	22.2	22.7	22.7	23.2	23.7

Luminance table

Max. for $\gamma >= 65°$

Photometric dimensions in mm: L = 231, B = 234

C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	13486.2	13188.8	12891.3	12893.8	12896.3	12616.4	12336.5
50°	10486.1	10219.4	9952.7	10150.7	10348.7	9939.0	9529.3
55°	9588.5	8171.2	6753.8	8180.4	9607.0	8047.9	6488.9
60°	8652.5	7285.3	5918.3	6988.5	8058.7	6934.1	5809.4
65°	6827.9	6405.2	5982.4	5937.6	5892.9	5758.2	5623.5
70°	5261.2	5533.4	5805.8	5064.3	4322.9	4876.8	5430.6
75°	4895.8	5080.1	5264.6	4881.8	4557.2	4407.2	4315.5
80°	6271.3	5556.8	4842.5	5121.3	5400.1	4939.1	4477.9
85°	5725.9	4945.5	4164.7	4081.5	3998.4	3672.3	3345.8

Photometric test report

Family	Order number: 51MQ13WD2M55	LP number
Apollon® 21	**EAN: 4069025468604**	**59881_2**

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°

siteco



Photometric test report

Family	Order number: 51MQ13WD2M55	LP number
Apollon® 21	**EAN: 4069025468604**	**59881_2**

siteco

Multilumen Table

environmental temperature: 25°C

DIP-Step	Switch Setting 1	2	3	4	Luminous flux [lm]	Power consumption [W]
0	OFF	OFF	OFF	OFF	3220	27.9
1	ON	OFF	OFF	OFF	2990	25.4
2	OFF	ON	OFF	OFF	2730	23.1
4	OFF	OFF	ON	OFF	2470	20.8
7	ON	ON	ON	OFF	2230	18.6
8	OFF	OFF	OFF	ON	1930	16.2
10	OFF	ON	OFF	ON	1660	13.9
12	OFF	OFF	ON	ON	1520	12.7
13	ON	OFF	ON	ON	1370	11.5
14	OFF	ON	ON	ON	1310	10.9