

Lichttechnischer Prüfbefund

Familie Highbay 11	Bestell-Nr.: 51HN11DB3PLA EAN: 4069025424297	LP-Nummer 59711_394
Wertetabelle Lichtstärkemessung	Maximale Lichtstärke	siteco

C- Ebenen	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-Zone	Summe Phi-Zone
γ	Lichtstärke in cd/klm							Lichtstrom in lm/klm	
0,0°	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	4.0	4.0
2,5°	2608.0	2619.4	2619.4	2616.5	2617.6	2616.2	2606.1	31.3	35.3
5,0°	2420.1	2415.7	2414.1	2408.4	2406.6	2402.3	2391.7	57.6	92.8
7,5°	2113.4	2116.1	2112.3	2103.0	2097.6	2090.5	2079.6	75.2	168.1
10,0°	1780.1	1768.7	1762.7	1751.6	1743.6	1735.2	1724.7	83.4	251.5
12,5°	1410.1	1409.3	1404.7	1395.9	1388.1	1380.5	1373.1	82.8	334.3
15,0°	1106.5	1097.8	1095.0	1089.4	1083.1	1078.4	1073.9	77.3	411.5
17,5°	830.1	840.2	835.5	831.1	826.6	824.9	824.1	68.5	480.0
20,0°	671.1	661.9	651.8	643.2	639.9	639.4	641.0	60.8	540.8
22,5°	531.9	530.5	514.2	498.9	497.0	496.6	496.8	53.4	594.2
25,0°	450.6	441.3	420.6	401.3	399.0	395.8	392.4	47.9	642.1
27,5°	370.8	368.7	351.4	331.7	326.8	321.1	316.0	43.1	685.2
30,0°	320.4	312.1	300.8	284.1	278.0	270.2	264.7	39.7	724.9
32,5°	271.0	266.8	259.0	245.6	238.0	229.0	224.7	36.5	761.4
35,0°	235.8	228.9	222.7	210.5	201.6	193.0	191.7	33.3	794.7
37,5°	204.4	197.8	191.5	181.1	172.0	164.3	162.4	30.3	825.0
40,0°	176.7	170.7	163.1	154.3	146.1	138.3	135.6	27.3	852.2
42,5°	147.6	145.5	138.6	130.6	123.2	115.8	113.3	24.2	876.4
45,0°	126.0	121.8	116.3	109.0	102.0	95.3	93.2	21.1	897.6
47,5°	103.2	101.5	97.1	90.9	84.6	78.4	76.7	18.3	915.9
50,0°	85.9	82.9	79.4	74.6	69.1	63.7	61.9	15.5	931.4
52,5°	69.0	67.2	64.5	61.0	56.2	51.6	49.7	13.0	944.4
55,0°	55.6	54.1	52.2	49.5	45.7	41.7	40.0	10.9	955.3
57,5°	43.6	43.1	41.8	39.8	37.0	33.6	32.2	9.0	964.3
60,0°	33.2	33.3	33.9	32.4	30.5	27.5	26.1	7.4	971.7
62,5°	25.9	26.0	27.0	26.2	25.1	22.4	21.3	6.1	977.8
65,0°	21.6	21.2	21.7	21.3	20.9	18.8	17.7	5.1	982.9
67,5°	17.0	17.1	17.8	17.0	17.3	15.6	14.8	4.3	987.2
70,0°	13.5	13.4	14.4	13.6	14.1	13.0	12.4	3.5	990.7
72,5°	11.0	10.8	10.9	10.9	11.0	10.7	10.6	2.8	993.5
75,0°	9.0	8.4	8.4	8.3	8.6	9.0	8.9	2.3	995.8
77,5°	6.6	6.4	6.2	6.2	6.6	7.3	7.4	1.8	997.5
80,0°	4.4	4.2	4.1	4.2	4.7	5.7	5.8	1.3	998.8
82,5°	2.0	2.1	2.2	2.4	3.0	3.9	4.1	0.8	999.6
85,0°	0.8	0.8	0.8	1.0	1.5	2.2	2.4	0.4	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Lichttechnischer Prüfbefund


Familie Highbay 11			Bestell-Nr.: 51HN11DB3PLA EAN: 4069025424297						LP-Nummer 59711_394		
UGR-Tabelle			Standardraum						siteco		
Reflexionsgrad Decke		0,7	0,7	0,5	0,5	0,3	0,7	0,7	0,5	0,5	0,3
Reflexionsgrad Wände		0,5	0,3	0,5	0,3	0,3	0,5	0,3	0,5	0,3	0,3
Reflexionsgrad Boden		0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2
Raumabmessungen		Blickrichtung quer zur Leuchte (C0)					Blickrichtung längs zur Leuchte (C90)				
x	y										
2H	2H	19,4	20,5	19,7	20,8	21,2	18,2	19,3	18,5	19,6	20,0
	3H	19,6	20,6	20,0	21,0	21,3	18,5	19,5	18,8	19,8	20,2
	4H	19,7	20,6	20,1	21,0	21,3	18,6	19,5	19,0	19,9	20,3
	6H	19,7	20,5	20,1	20,9	21,3	18,7	19,6	19,1	19,9	20,3
	8H	19,8	20,5	20,2	20,9	21,3	18,8	19,6	19,3	20,0	20,4
	12H	19,7	20,4	20,2	20,8	21,2	18,8	19,5	19,3	19,9	20,3
4H	2H	19,4	20,4	19,8	20,7	21,1	18,4	19,3	18,8	19,6	20,0
	3H	19,7	20,5	20,2	20,9	21,3	18,8	19,5	19,2	19,9	20,3
	4H	19,8	20,5	20,3	21,0	21,4	18,9	19,6	19,4	20,1	20,5
	6H	19,9	20,5	20,4	20,9	21,4	19,1	19,7	19,6	20,2	20,6
	8H	19,9	20,4	20,4	20,9	21,4	19,2	19,7	19,7	20,2	20,7
	12H	19,9	20,3	20,4	20,8	21,3	19,3	19,7	19,8	20,2	20,7
8H	4H	19,8	20,3	20,3	20,8	21,3	19,0	19,5	19,5	19,9	20,4
	6H	19,9	20,3	20,4	20,8	21,3	19,2	19,6	19,7	20,1	20,6
	8H	19,9	20,3	20,4	20,8	21,3	19,3	19,7	19,8	20,2	20,7
	12H	19,9	20,2	20,4	20,7	21,2	19,4	19,7	19,9	20,2	20,7
12H	4H	19,8	20,2	20,3	20,7	21,2	19,0	19,4	19,5	19,9	20,4
	6H	19,9	20,2	20,4	20,7	21,3	19,2	19,5	19,7	20,0	20,6
	8H	19,9	20,2	20,4	20,7	21,2	19,3	19,6	19,8	20,1	20,6

Leuchtdichten-Tabelle		Max. für $\gamma \geq 65^\circ$		Lichttechnische Abmessungen in mm:		L = 852 B = 264	
C- Ebenen	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Leuchtdichte in cd/m²						
45,0°	27091.1	26186.7	25007.0	23442.9	21933.4	20498.5	20039.7
50,0°	20309.3	19602.3	18772.0	17657.4	16333.5	15058.0	14631.8
55,0°	14736.5	14337.6	13840.8	13121.9	12111.1	11054.7	10610.4
60,0°	10110.9	10121.9	10310.1	9850.3	9264.6	8358.7	7941.5
65,0°	7762.9	7632.0	7805.0	7678.7	7516.5	6754.8	6385.0
70,0°	6014.5	5942.0	6383.4	6028.2	6255.9	5759.3	5504.1
75,0°	5272.6	4948.3	4959.4	4892.5	5047.5	5263.2	5253.8
80,0°	3846.6	3703.8	3583.0	3647.8	4076.0	4949.8	5050.5
85,0°	1423.6	1406.1	1470.7	1662.6	2552.3	3757.8	4258.5

Lichttechnischer Prüfbefund

Familie Highbay 11	Bestell-Nr.: 51HN11DB3PLA EAN: 4069025424297	LP-Nummer 59711_394
Leuchtdichten in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°		

siteco



Lichttechnischer Prüfbefund

Familie Highbay 11	Bestell-Nr.: 51HN11DB3PLA EAN: 4069025424297	LP-Nummer 59711_394
Dimmstufen-Tabelle		Umgebungstemperatur: 25°C

siteco

Lichtstrom [%]	Dimmstufe linear	Dimmstufe logarithmisch	Lichtstrom [lm]	Systemleistung [W]
100	254	254	34200	177.6
95	241	252	32547	168.2
90	227	250	30753	158.1
85	214	248	29081	148.9
80	201	245	27390	139.5
75	188	243	25694	130.3
70	175	240	23987	121.1
65	162	238	22275	112.1
60	149	234	20548	103.0
55	136	231	18818	94.0
50	123	227	17069	85.0
45	111	224	15441	76.8
40	98	219	13668	67.9
35	86	214	12024	59.8
30	73	208	10230	50.9
25	61	202	8557	42.9
20	49	194	6878	35.0
15	37	183	5188	27.2
10	25	169	3486	19.3
5	13	145	1769	11.1
1	4	102	477	4.8