




# Photometric test report

<b>Family</b> <b>Licross® 11 Recessed</b>	<b>Order number: 51TL11CN4CXR</b> <b>EAN: 4058352418079</b>	<b>LP number</b> <b>58784_12</b>
	<b>Version</b> cover frosted, narrow distribution <b>Lamps</b> LED 4000 K   CRI ≥ 80 <b>Controlgear</b> ECG-Multilumen CLOi <b>Setting</b> AC-mode <b>Rated values</b> Net luminous flux = 12100 lm Power consumption = 68.8 W Luminous efficacy = 175.9 lm/W	<b>serial documentation</b> <b>26.08.2020</b>
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 3431 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=87 N2=95 N3=99 N4=100 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	100.0%
$\phi_o$	0.0%

**Measurement conditions**  
 DIN EN 13032 and DIN 5032

## Photometric test report

<b>Family</b> <b>Licross® 11 Recessed</b>	<b>Order number: 51TL11CN4CXRD</b> <b>EAN: 4058352418079</b>	<b>LP number</b> <b>58784_12</b>
--	---	-------------------------------------

**sitEco**

<b>Table of values for luminous intensities</b>	<b>Maximum luminous intensity</b>
---	-----------------------------------

C-planes	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	3431.3	3431.3	3431.3	3431.3	3431.3	3431.3	3431.3	20.5	20.5
5°	3030.0	3009.9	2995.2	3008.4	3015.8	3015.7	3017.5	143.9	164.4
10°	2113.5	2098.5	2092.1	2104.8	2111.9	2109.7	2109.2	200.3	364.7
15°	1287.2	1281.7	1283.9	1294.7	1294.7	1286.2	1283.2	182.7	547.4
20°	703.4	705.4	717.6	726.5	719.3	702.5	697.3	133.5	680.9
25°	354.0	358.8	370.9	376.0	367.5	355.6	354.0	84.3	765.2
30°	176.2	179.2	185.6	185.7	179.6	178.8	183.6	49.7	814.9
35°	102.4	102.6	103.9	102.5	99.6	107.7	116.7	32.8	847.7
40°	73.1	72.4	71.7	70.6	70.7	80.9	90.2	26.3	874.0
45°	60.7	58.7	57.0	56.9	57.9	66.7	75.5	23.6	897.6
50°	52.7	51.5	51.2	50.6	50.0	56.0	63.2	22.2	919.8
55°	44.8	43.4	45.4	45.0	43.0	46.3	51.7	20.3	940.1
60°	37.3	36.1	38.2	39.8	37.2	38.0	41.8	18.1	958.2
65°	29.8	28.9	31.0	34.0	31.7	30.7	33.0	15.5	973.8
70°	21.9	21.7	22.9	26.9	25.3	23.3	24.3	12.3	986.1
75°	12.2	12.7	14.5	18.5	17.7	15.7	16.0	8.2	994.3
80°	5.5	5.6	6.4	9.0	10.0	8.8	8.6	4.2	998.5
85°	2.2	2.1	2.4	3.2	3.5	3.4	3.0	1.6	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

<b>Family</b> Licross® 11 Recessed	<b>Order number: 51TL11CN4CXRD</b> <b>EAN: 4058352418079</b>	<b>LP number</b> 58784_12
---------------------------------------	---	------------------------------

<b>UGR-Table</b>	<b>Standard room</b>	<b>siteco</b>
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	16.7	17.8	17.0	18.1	18.4	17.0	18.2	17.4	18.5	18.8
	3H	18.0	19.0	18.4	19.3	19.7	18.5	19.4	18.8	19.8	20.1
	4H	18.4	19.3	18.8	19.7	20.0	19.0	19.9	19.4	20.2	20.6
	6H	18.5	19.4	19.0	19.7	20.1	19.3	20.1	19.7	20.5	20.9
	8H	18.7	19.3	19.1	19.7	20.1	19.5	20.2	19.9	20.5	21.0
	12H	18.6	19.3	19.1	19.7	20.1	19.5	20.1	19.9	20.5	20.9
4H	2H	17.4	18.3	17.8	18.7	19.1	17.7	18.6	18.1	19.0	19.3
	3H	18.9	19.6	19.3	20.0	20.5	19.3	20.1	19.7	20.5	20.9
	4H	19.3	20.0	19.8	20.4	20.9	19.9	20.6	20.4	21.0	21.5
	6H	19.5	20.1	20.0	20.5	21.0	20.3	20.9	20.8	21.3	21.8
	8H	19.6	20.1	20.1	20.5	21.0	20.5	21.0	20.9	21.4	21.9
	12H	19.6	20.0	20.1	20.5	21.0	20.5	20.9	21.0	21.4	21.9
8H	4H	19.7	20.2	20.1	20.6	21.1	20.2	20.7	20.7	21.2	21.6
	6H	19.9	20.3	20.4	20.8	21.3	20.7	21.1	21.2	21.6	22.1
	8H	19.9	20.3	20.5	20.8	21.3	20.9	21.2	21.4	21.7	22.3
	12H	20.0	20.3	20.5	20.8	21.3	20.9	21.3	21.5	21.8	22.3
12H	4H	19.7	20.1	20.2	20.6	21.1	20.2	20.6	20.7	21.1	21.6
	6H	19.9	20.3	20.5	20.8	21.3	20.7	21.1	21.2	21.6	22.1
	8H	20.0	20.3	20.5	20.8	21.4	20.9	21.2	21.4	21.7	22.3

<b>Luminance table</b>	<b>Max. for <math>\gamma \geq 65^\circ</math></b>	<b>Photometric dimensions in mm:</b>	<b>L = 1500</b> <b>B = 58</b>
------------------------	---	--------------------------------------	----------------------------------


C-planes	$\gamma$	Luminance in cd/m <sup>2</sup>						
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
45°		11942.0	11550.2	11218.0	11188.1	11387.3	13114.3	14857.7
50°		11412.7	11148.9	11088.1	10954.2	10811.6	12119.6	13677.7
55°		10873.7	10533.5	11015.4	10916.4	10431.9	11236.5	12531.1
60°		10374.6	10035.8	10616.3	11065.8	10357.0	10570.4	11638.0
65°		9801.4	9522.0	10199.2	11174.3	10446.7	10113.7	10857.1
70°		8892.5	8816.4	9307.3	10920.8	10288.9	9474.0	9896.5
75°		6576.3	6813.8	7771.9	9921.9	9497.4	8412.5	8579.6
80°		4438.0	4478.8	5150.8	7229.2	7975.7	7018.6	6888.8
85°		3491.5	3424.5	3780.4	5060.2	5545.3	5382.5	4747.4

**Photometric test report**

<b>Family</b> Licross® 11 Recessed	<b>Order number: 51TL11CN4CXRD</b> <b>EAN: 4058352418079</b>	<b>LP number</b> 58784_12
---------------------------------------	---	------------------------------



**Luminance values in cd/m<sup>2</sup>**     $\gamma$  65°     $\gamma$  70°     $\gamma$  75°     $\gamma$  80°     $\gamma$  85°



### Photometric test report

<b>Family</b> Licross® 11 Recessed	<b>Order number: 51TL11CN4CXRD</b> <b>EAN: 4058352418079</b>	<b>LP number</b> <b>58784_12</b>
---------------------------------------	---	-------------------------------------

<b>Multilumen Table</b>	environmental temperature: 25°C	<b>sITeco</b>
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
	1	2	3			end of lifetime	average
1	A	C	E	12100	68.8	76.9	72.8
2	A	C	F	11050	62.1	69.3	65.7
3	A	D	E	10060	56.0	62.2	59.1
4	A	D	F	9050	49.9	55.2	52.6
5	B	C	E	8020	43.9	48.6	46.2
6	B	C	F	7050	38.4	42.2	40.3
7	B	D	E	6070	32.9	36.3	34.6
8	B	D	F	5070	27.5	30.0	28.8