


Photometric test report

Family LANTERN CLASSIC LED	Order number: 5XA5245AF14H + 5XA54000XS EAN: 4058352834411 + 4050737730073	LP number 59105_24
	Version post-top- or mounting to wall arm, spreader element, structured Optic asymmetric, wide distribution (ST1.2a) Cover cover transparent, PMMA Lamps LED 2200 K CRI ≥ 70 Controlgear ECG SITECO iQ Rated values Net luminous flux = 1310 lm Power consumption = 12.9 W Luminous efficacy = 101.6 lm/W	serial documentation 08.07.2022

Luminous intensity in cd/klm C180-0 C205-25 C210-30 C270-90 **Imax: 662 cd/klm**



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	97.2%
Eta 90° - 180°	2.8%

Luminous intensity class acc. to EN13201-2

Class:	---
Imax 70°	532.1
Imax 80°	201.9
Imax 90°	20.2
Imax >90°	12.6
Imax >95°	11.3


Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family LANTERN CLASSIC LED	Order number: 5XA5245AF14H + 5XA54000XS EAN: 4058352834411 + 4050737730073	LP number 59105_24
---	---	-------------------------------------

Envelope curve in cd/klm **KMK 60°** **KMK 57.5°** **KMK 55°** **KMK 52.5°** **siteco**



Photometric test report

Family LANTERN CLASSIC LED	Order number: 5XA5245AF14H + 5XA54000XS EAN: 4058352834411 + 4050737730073	LP number 59105_24
Table of values for luminous intensities		Maximum luminous intensity
siteco		

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
0,0°	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8
2,5°	29.3	29.3	29.9	30.2	30.2	30.9	31.2	31.8	32.8	33.7	34.7	35.0	35.6
5,0°	34.3	35.9	37.2	38.1	40.0	41.9	43.8	45.4	46.0	46.6	46.6	46.6	47.9
7,5°	59.2	62.4	63.6	63.0	63.3	64.6	66.8	69.6	72.5	73.1	72.8	70.3	67.4
10,0°	57.6	62.4	69.9	80.0	92.9	95.8	102.4	109.3	118.4	126.6	128.2	122.5	112.5
12,5°	107.4	107.7	114.7	127.6	141.8	148.7	152.8	159.1	160.3	155.6	155.6	145.9	143.0
15,0°	108.4	133.3	157.5	178.0	175.8	168.5	174.8	189.3	202.6	209.2	206.7	197.8	185.2
17,5°	180.2	187.4	186.2	203.2	218.3	211.4	211.7	222.7	227.4	230.6	232.5	223.0	211.1
20,0°	199.1	214.5	225.9	240.7	253.6	258.6	236.9	232.2	235.6	226.2	237.8	223.4	209.2
22,5°	240.0	252.0	254.2	256.1	255.5	241.6	234.1	224.3	236.3	224.0	244.1	233.7	217.1
25,0°	246.0	250.1	244.8	247.6	251.7	248.6	245.7	232.5	255.8	244.5	270.0	264.9	240.0
27,5°	200.7	212.0	228.1	244.5	253.9	262.4	269.3	249.8	276.9	256.1	284.5	272.8	243.5
30,0°	217.4	244.5	257.1	267.1	269.3	270.3	273.4	251.1	279.4	253.9	279.4	259.9	228.4
32,5°	236.9	253.6	256.4	252.0	245.4	235.6	225.2	185.5	222.1	199.1	234.4	234.7	222.1
35,0°	144.0	124.4	109.0	102.4	111.5	127.0	144.3	130.1	188.1	172.0	214.8	222.7	230.9
37,5°	98.0	108.7	125.1	147.1	173.9	199.7	217.7	208.5	242.6	224.9	274.1	260.2	250.1
40,0°	174.2	196.3	222.4	254.5	278.2	286.4	281.6	274.1	293.6	296.1	327.0	301.5	281.9
42,5°	272.5	289.5	311.2	332.4	331.4	323.5	321.3	321.0	348.1	364.5	385.3	363.2	339.0
45,0°	304.3	330.5	353.8	372.0	380.2	383.4	390.9	376.8	411.4	416.1	445.1	422.4	388.1
47,5°	316.9	350.0	387.2	412.7	436.0	445.4	457.7	427.2	444.8	435.7	463.1	441.0	396.0
50,0°	322.9	363.2	417.4	453.6	484.2	497.1	509.7	472.9	453.3	448.9	469.4	442.6	380.9
52,5°	324.5	369.8	432.2	486.1	536.5	551.3	550.0	513.8	454.9	453.9	460.2	427.8	351.9
55,0°	318.2	376.8	450.2	520.1	584.4	601.1	584.1	543.7	461.5	450.2	440.7	407.3	316.3
57,5°	304.0	373.3	457.1	540.0	616.5	640.1	611.8	562.3	469.1	440.1	416.1	380.9	276.3
60,0°	280.7	358.8	453.0	539.3	624.1	661.5	629.1	572.4	477.6	426.2	388.1	351.6	238.8
62,5°	249.5	335.8	430.6	518.5	605.8	657.8	626.6	566.1	476.6	408.6	361.3	321.3	200.7
65,0°	225.6	308.1	402.6	481.7	569.9	633.8	610.5	547.5	464.3	384.0	333.9	289.8	171.7
67,5°	207.3	291.7	376.8	445.8	526.1	595.7	578.7	513.5	436.9	356.0	304.9	259.9	143.0
70,0°	191.8	270.3	345.0	398.5	464.7	532.1	524.2	461.5	392.2	317.2	272.2	227.1	129.8
72,5°	171.4	243.8	307.1	352.8	407.6	458.0	453.3	398.2	335.8	268.1	229.3	198.8	103.3
75,0°	147.1	205.7	255.2	293.0	331.7	368.9	367.9	325.7	273.1	217.7	188.4	165.7	88.5
77,5°	111.8	158.8	196.3	226.5	256.4	283.8	285.7	252.6	212.0	170.4	150.9	140.8	79.4
80,0°	88.8	119.1	144.0	163.5	180.5	195.6	201.9	184.0	157.8	130.4	113.1	108.7	60.8
82,5°	63.3	84.4	102.4	115.6	127.0	135.5	144.6	136.1	119.7	98.0	81.0	76.9	43.2
85,0°	44.4	57.0	69.0	78.4	86.0	93.9	98.0	95.8	85.4	69.3	57.3	52.9	33.7
87,5°	30.9	40.3	47.6	54.8	59.2	62.4	66.5	66.2	58.9	49.5	41.9	39.4	27.1
90,0°	11.7	12.6	14.2	15.1	16.1	17.0	18.9	19.8	20.2	19.2	18.9	19.8	16.1
92,5°	9.8	10.1	10.7	11.3	12.0	12.0	12.0	12.0	11.7	11.7	11.7	11.7	10.7
95,0°	9.1	10.1	10.1	10.7	11.3	11.3	11.3	11.0	11.3	11.0	11.0	10.7	10.4
97,5°	8.8	9.5	10.1	10.1	10.7	10.7	10.7	10.7	10.7	10.7	10.4	10.4	10.1
100,0°	8.2	8.8	9.5	9.5	9.8	10.1	10.1	10.1	10.1	10.1	9.8	9.8	9.5
102,5°	7.9	8.2	8.8	8.8	8.8	9.5	9.5	9.5	9.1	9.1	9.1	9.1	8.8
105,0°	7.2	7.6	8.2	8.2	8.2	8.2	8.8	8.5	8.5	8.5	8.5	8.8	8.8
107,5°	6.6	6.9	7.2	7.6	7.6	7.9	8.2	8.2	7.9	7.9	8.2	8.2	8.2
110,0°	6.3	6.3	6.9	6.9	7.6	7.6	7.6	7.6	7.2	7.6	7.6	7.6	7.6
112,5°	5.7	6.3	6.3	6.9	6.9	6.9	7.2	6.9	6.9	6.9	6.9	6.9	6.9

Photometric test report

Family LANTERN CLASSIC LED	Order number: 5XA5245AF14H + 5XA54000XS EAN: 4058352834411 + 4050737730073	LP number 59105_24
Table of values for luminous intensities		Maximum luminous intensity
siteco		


C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
0,0°	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8
2,5°	35.9	36.2	36.5	36.5	36.9	36.5	28.7	28.4	28.0	27.7	27.7	27.4	27.1
5,0°	50.1	51.0	50.1	50.4	49.8	49.1	33.4	32.4	31.8	30.9	30.2	29.6	29.3
7,5°	68.7	74.3	81.0	85.7	92.3	94.5	54.5	49.1	42.2	38.1	34.0	31.5	30.2
10,0°	100.5	101.8	118.4	128.2	131.7	134.8	57.6	59.5	63.3	64.3	61.7	51.0	39.1
12,5°	140.8	150.0	172.6	192.2	204.1	206.0	86.0	93.2	69.3	59.2	45.7	39.4	43.5
15,0°	190.6	189.0	204.1	232.8	241.6	238.2	92.6	81.0	76.2	74.3	74.7	59.2	68.7
17,5°	222.4	222.7	237.2	272.5	284.5	285.4	151.8	99.5	121.0	105.8	100.2	75.3	75.6
20,0°	232.2	227.4	229.3	267.5	285.1	287.3	168.9	117.8	143.7	122.2	106.2	84.4	80.0
22,5°	242.3	228.4	206.3	230.3	239.1	241.3	204.5	130.1	153.1	137.4	119.4	95.1	81.9
25,0°	258.9	244.1	223.7	247.3	250.8	248.9	207.6	129.8	174.2	161.3	149.3	118.8	96.7
27,5°	264.9	255.2	241.0	269.0	278.8	280.4	152.5	94.8	161.3	144.6	134.2	109.0	90.4
30,0°	245.7	235.3	222.1	245.7	258.6	262.7	155.9	92.3	157.5	141.8	131.7	104.6	85.1
32,5°	218.0	209.8	207.6	226.8	218.0	212.3	176.1	96.7	155.9	135.1	125.4	97.7	76.9
35,0°	253.9	228.1	218.9	247.0	246.0	243.8	122.2	101.1	131.1	114.0	101.4	79.1	66.8
37,5°	287.9	248.2	258.0	320.7	343.1	349.7	87.6	77.5	80.0	69.6	61.1	51.7	46.6
40,0°	336.4	308.1	333.6	388.7	401.7	408.3	134.8	95.1	112.8	95.1	83.5	62.1	48.5
42,5°	397.2	355.7	378.0	414.3	424.0	428.4	182.4	127.9	161.3	127.3	99.9	69.0	61.7
45,0°	431.3	376.1	397.9	416.8	424.3	427.2	185.5	149.3	184.0	138.3	98.9	68.0	71.2
47,5°	429.4	370.2	392.8	404.2	411.7	413.9	178.6	161.3	179.9	128.5	84.4	68.0	73.1
50,0°	408.0	354.1	373.6	381.2	389.4	391.9	164.8	173.3	170.4	111.5	66.2	61.4	65.2
52,5°	374.9	328.6	346.5	350.9	359.8	363.5	155.3	182.7	161.3	100.5	62.4	61.4	59.5
55,0°	335.5	298.3	311.2	314.7	323.8	327.6	141.1	182.1	142.4	88.5	62.1	62.7	58.0
57,5°	292.7	262.1	268.4	272.2	281.3	285.4	125.7	171.1	121.9	76.2	58.0	56.7	52.6
60,0°	251.1	224.3	224.9	229.7	238.2	241.9	115.0	151.5	104.0	67.4	56.1	52.3	47.9
62,5°	211.7	186.2	182.7	187.1	193.1	195.3	104.3	128.8	88.8	62.4	55.1	50.4	45.0
65,0°	179.2	154.0	146.8	149.6	155.0	155.6	95.5	110.3	78.4	58.9	52.6	47.3	41.9
67,5°	150.3	125.1	115.9	117.2	119.7	121.6	85.7	97.3	71.5	55.8	50.4	44.1	38.4
70,0°	126.3	101.8	91.7	91.7	92.9	95.1	85.1	88.2	65.8	53.9	47.6	41.6	35.9
72,5°	104.3	81.3	70.9	69.3	71.2	72.5	74.0	80.0	58.6	50.4	44.1	37.8	32.8
75,0°	86.6	65.5	55.8	53.6	54.8	56.1	66.5	69.0	50.7	46.6	40.6	34.7	29.6
77,5°	73.7	52.0	43.2	40.6	41.9	43.5	55.8	55.8	42.8	40.3	35.3	30.9	26.5
80,0°	57.3	41.3	34.3	32.1	32.8	34.0	45.7	45.7	36.9	35.0	31.5	27.4	23.6
82,5°	41.3	31.8	27.1	25.2	25.2	25.8	35.9	35.0	29.3	28.4	25.2	22.7	19.8
85,0°	32.4	25.8	22.1	20.8	20.8	20.8	27.1	26.1	23.6	22.7	20.5	18.3	16.4
87,5°	26.8	22.1	19.5	18.0	17.6	17.6	20.8	19.5	19.2	17.6	16.1	14.8	13.2
90,0°	17.6	15.4	14.5	13.9	13.9	13.9	10.4	10.4	9.8	9.5	8.8	8.5	8.2
92,5°	11.3	11.7	12.0	12.0	12.6	12.6	8.8	8.8	8.5	8.2	7.9	7.9	7.6
95,0°	10.7	11.0	11.3	11.7	12.0	12.0	8.8	8.8	8.5	8.2	7.9	7.6	7.6
97,5°	10.7	10.7	10.7	11.3	11.3	11.3	8.2	8.2	8.2	7.9	7.6	7.6	7.6
100,0°	10.1	10.1	10.4	10.7	10.7	10.7	8.2	7.6	7.6	7.6	7.6	7.6	6.9
102,5°	9.5	9.5	9.5	9.8	10.1	10.1	7.6	6.9	6.9	6.9	6.9	6.9	6.3
105,0°	8.8	8.8	8.8	9.1	9.5	8.8	6.9	6.9	6.3	6.3	6.3	6.0	5.7
107,5°	8.2	8.2	8.5	8.8	8.8	8.2	6.3	6.0	5.7	5.7	5.7	5.4	5.0
110,0°	7.6	7.9	8.2	8.2	8.2	7.6	5.7	5.7	5.4	5.0	5.0	5.0	5.0
112,5°	7.6	7.6	7.6	7.6	6.9	4.4	5.7	5.4	5.0	5.0	5.0	5.0	5.0

Photometric test report

Family LANTERN CLASSIC LED	Order number: 5XA5245AF14H + 5XA54000XS EAN: 4058352834411 + 4050737730073	LP number 59105_24
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	0.0	0.0
2,5°	27.1	26.8	26.8	26.1	25.8	25.5	25.2	25.2	24.9	24.6	24.6	0.4	0.4
5,0°	28.7	28.0	27.1	26.5	26.1	25.8	25.5	25.5	25.2	24.9	25.2	0.9	1.3
7,5°	29.3	28.4	27.4	26.1	25.5	25.2	25.2	24.6	24.6	24.6	24.6	1.9	3.1
10,0°	32.1	29.3	27.7	26.5	25.8	25.2	24.6	24.3	23.9	23.9	23.9	3.4	6.6
12,5°	50.1	51.3	42.5	30.6	27.4	25.8	24.9	24.3	23.6	23.0	22.7	5.9	12.4
15,0°	66.5	57.0	64.0	69.0	58.6	41.6	29.9	26.1	24.9	23.6	23.9	8.8	21.2
17,5°	74.0	67.1	59.2	52.3	46.3	48.2	53.2	50.1	33.1	30.6	30.2	12.3	33.6
20,0°	73.7	64.9	59.5	57.6	57.6	52.6	48.2	44.7	37.2	44.7	52.3	15.0	48.6
22,5°	71.8	63.0	57.3	55.8	57.6	57.0	56.1	55.4	47.3	52.9	59.2	17.2	65.8
25,0°	78.8	63.6	56.7	56.4	60.2	60.8	64.6	65.8	59.9	64.3	67.4	20.3	86.1
27,5°	75.0	65.2	59.5	60.5	63.0	63.6	65.2	63.3	56.4	59.9	62.4	22.0	108.0
30,0°	73.1	65.8	61.4	60.2	61.4	62.4	62.7	58.6	52.6	56.1	58.6	23.6	131.7
32,5°	74.7	71.5	68.0	65.8	65.5	62.1	58.3	54.5	49.5	52.6	54.2	23.3	155.0
35,0°	65.5	67.7	67.1	69.3	70.3	65.8	60.2	54.5	48.5	50.1	51.7	20.5	175.5
37,5°	52.0	56.7	60.5	64.6	66.8	64.3	59.5	56.1	49.5	49.1	52.3	24.3	199.8
40,0°	43.2	40.3	46.9	52.3	59.2	60.2	59.2	55.8	51.7	54.2	59.9	32.4	232.2
42,5°	54.8	42.5	37.2	38.4	46.0	48.8	52.0	52.0	51.7	56.7	62.4	40.3	272.5
45,0°	64.3	51.7	43.2	39.7	38.7	37.2	39.4	42.2	43.5	46.9	50.4	46.3	318.8
47,5°	65.2	54.2	46.9	41.9	38.4	35.0	32.8	33.4	34.3	35.9	37.2	50.2	369.0
50,0°	59.2	52.0	46.6	42.8	40.6	36.5	33.1	31.2	30.9	32.1	32.8	52.8	421.8
52,5°	53.2	48.2	44.4	41.6	39.4	36.9	34.0	33.4	32.4	35.0	35.9	54.7	476.5
55,0°	50.7	44.7	41.0	38.7	38.7	36.9	35.0	34.3	34.3	37.5	37.8	55.8	532.3
57,5°	46.9	41.3	37.8	35.9	36.9	35.6	34.3	34.3	35.0	38.1	39.1	55.6	588.0
60,0°	41.9	37.2	34.3	32.8	33.7	33.4	32.8	32.8	35.0	37.8	38.4	54.4	642.4
62,5°	39.1	34.3	31.5	29.9	31.2	30.6	30.6	31.2	33.7	35.9	36.5	52.0	694.4
65,0°	36.5	31.8	29.6	27.7	28.7	28.0	28.0	28.7	32.1	33.4	34.0	48.9	743.4
67,5°	33.7	29.9	27.7	25.8	26.5	26.1	25.8	26.1	29.6	30.9	30.9	45.5	788.9
70,0°	31.5	27.4	25.5	23.6	24.3	23.6	23.3	23.9	26.8	27.7	27.7	41.3	830.1
72,5°	28.4	24.9	23.0	21.7	22.1	21.1	20.8	21.1	23.6	24.3	24.6	36.2	866.3
75,0°	25.5	22.7	20.8	19.2	19.5	18.6	18.3	18.9	20.8	20.8	21.4	30.4	896.7
77,5°	23.0	20.2	18.3	17.3	17.0	16.1	15.8	16.4	17.6	17.6	17.6	24.3	921.0
80,0°	20.2	17.6	16.1	15.1	14.8	13.9	12.9	13.5	14.5	14.5	14.5	18.5	939.5
82,5°	17.3	15.1	13.9	12.9	12.3	11.7	10.4	11.0	11.3	11.3	11.3	13.7	953.3
85,0°	14.5	12.6	11.7	10.7	10.1	9.1	8.5	8.8	8.8	8.5	8.2	10.0	963.3
87,5°	12.0	10.7	9.5	8.8	8.2	7.6	6.9	6.9	6.9	6.9	6.3	7.4	970.6
90,0°	7.9	7.6	6.9	6.3	6.3	5.7	5.7	5.7	5.4	5.4	5.0	3.3	973.9
92,5°	7.6	6.9	6.6	6.3	6.3	5.7	5.7	5.7	5.7	5.4	5.7	2.5	976.5
95,0°	7.2	6.9	6.6	6.6	6.3	6.0	5.7	5.7	5.7	5.7	5.7	2.5	978.9
97,5°	6.9	6.6	6.9	6.6	6.3	5.7	5.7	5.7	5.4	5.7	5.7	2.4	981.3
100,0°	6.6	6.3	6.3	6.3	6.3	5.7	5.7	5.0	5.0	5.4	5.7	2.2	983.5
102,5°	6.0	6.3	5.7	5.7	5.7	5.0	5.0	4.7	4.4	4.4	4.4	2.0	985.5
105,0°	5.7	5.7	5.4	5.0	5.0	4.4	4.4	4.4	4.4	3.8	3.8	1.9	987.4
107,5°	5.0	5.0	4.7	4.4	4.4	4.1	3.8	3.8	3.5	3.2	3.2	1.7	989.1
110,0°	4.4	4.4	4.4	4.4	3.8	3.8	3.8	3.2	3.2	3.2	3.2	1.5	990.6
112,5°	4.4	4.4	4.4	3.8	3.8	3.8	3.2	3.2	3.2	2.5	2.5	1.4	992.0

Photometric test report

Family LANTERN CLASSIC LED	Order number: 5XA5245AF14H + 5XA54000XS EAN: 4058352834411 + 4050737730073	LP number 59105_24
Table of values for luminous intensities		Maximum luminous intensity
		

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
115,0°	5.7	5.7	6.3	6.3	6.6	6.6	6.9	6.6	6.6	6.6	6.6	6.9	6.9
117,5°	5.0	5.7	5.7	5.7	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3
120,0°	5.0	5.0	5.7	5.7	5.7	6.0	6.0	5.7	5.7	5.7	6.0	6.3	6.3
122,5°	5.0	5.0	5.4	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	6.0
125,0°	3.8	4.1	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.7	4.7
127,5°	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2
130,0°	2.2	2.2	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9
132,5°	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9
135,0°	1.9	1.9	1.9	1.6	1.9	1.6	1.3	1.3	1.3	1.3	1.3	1.3	1.3
137,5°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
140,0°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.9	0.9	0.6	0.6	0.6	0.6
142,5°	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
145,0°	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
147,5°	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family LANTERN CLASSIC LED	Order number: 5XA5245AF14H + 5XA54000XS EAN: 4058352834411 + 4050737730073	LP number 59105_24
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
115,0°	6.9	6.9	7.6	7.6	6.0	2.5	5.0	5.0	5.0	4.7	4.7	4.7	4.4
117,5°	6.9	6.9	6.9	6.9	5.0	2.5	5.0	5.0	4.4	4.4	4.4	4.4	4.4
120,0°	6.3	6.3	6.3	6.3	4.4	1.9	5.0	4.4	4.4	4.4	4.4	4.4	4.4
122,5°	6.3	6.3	6.3	6.3	3.8	1.9	4.7	4.4	4.4	4.4	4.1	4.4	3.8
125,0°	5.0	5.0	5.0	5.0	3.2	1.9	3.8	3.8	3.8	3.2	3.2	3.2	3.2
127,5°	3.2	3.2	3.2	3.2	1.9	1.3	2.8	2.5	2.5	2.5	2.5	2.5	2.5
130,0°	1.9	1.9	2.2	1.9	1.3	0.6	1.9	1.9	1.9	1.9	1.9	1.9	2.2
132,5°	1.9	1.9	1.9	1.6	1.3	0.6	1.9	1.9	1.9	1.9	1.9	1.9	1.9
135,0°	1.3	1.3	1.3	1.3	0.6	0.6	1.9	1.9	1.9	1.9	1.9	1.9	1.9
137,5°	1.3	1.3	1.3	1.3	0.6	0.6	1.3	1.3	1.3	1.3	1.3	1.3	1.6
140,0°	0.6	0.6	0.6	0.6	0.6	0.6	1.3	1.3	1.3	1.3	1.3	1.3	1.3
142,5°	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.9	0.9	1.3	0.9
145,0°	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
147,5°	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family LANTERN CLASSIC LED	Order number: 5XA5245AF14H + 5XA54000XS EAN: 4058352834411 + 4050737730073	LP number 59105_24
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
115,0°	4.4	4.4	3.8	3.8	3.8	3.8	3.2	3.2	3.2	2.5	1.9	1.3	993.3
117,5°	4.4	4.1	3.8	3.8	3.8	3.2	3.2	3.2	3.2	2.5	1.9	1.2	994.6
120,0°	4.4	3.8	3.8	3.8	3.8	3.2	3.2	3.2	2.8	2.2	1.9	1.1	995.7
122,5°	3.8	3.8	3.8	3.8	3.2	3.2	3.2	3.2	2.5	1.9	1.9	1.1	996.8
125,0°	3.2	3.2	3.2	3.2	2.8	2.5	2.5	2.5	2.5	1.9	1.9	0.8	997.6
127,5°	2.5	2.5	2.5	2.5	2.5	2.5	2.5	1.9	1.9	1.6	1.3	0.6	998.2
130,0°	2.2	1.9	2.5	2.2	1.9	1.9	1.9	1.9	1.9	1.3	1.3	0.4	998.6
132,5°	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.6	1.3	1.3	0.4	998.9
135,0°	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.3	1.3	1.3	0.3	999.2
137,5°	1.3	1.3	1.3	1.3	1.6	1.3	1.3	1.3	1.3	1.3	1.3	0.2	999.5
140,0°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.6	1.3	0.2	999.7
142,5°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.9	0.6	0.6	0.1	999.8
145,0°	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.1	999.9
147,5°	0.6	0.6	0.6	0.6	0.9	0.9	0.6	0.9	0.6	0.6	0.6	0.1	1000.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family LANTERN CLASSIC LED	Order number: 5XA5245AF14H + 5XA54000XS EAN: 4058352834411 + 4050737730073	LP number 59105_24
---	---	-------------------------------------

Dimming levels table	environmental temperature: 25°C	siteco
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
				start of lifetime	end of lifetime	average
100	254	254	1310	12.9	13.3	13.1
95	241	252	1243	12.2	12.6	12.4
90	229	250	1181	11.5	11.9	11.7
85	216	248	1114	10.7	11.1	10.9
80	203	246	1047	10.1	10.5	10.3
75	190	243	980	9.4	9.8	9.6
70	178	241	918	8.9	9.1	9.0
65	165	238	851	8.2	8.4	8.3
60	152	235	784	7.6	7.8	7.7
55	140	232	722	7.0	7.2	7.1
50	127	229	655	6.4	6.6	6.5
45	114	225	588	5.8	6.0	5.9
40	102	221	526	5.3	5.4	5.4
35	89	216	459	4.8	4.9	4.8
30	76	210	392	4.3	4.3	4.3
25	63	203	325	3.7	3.8	3.8
24	60	201	309	3.5	3.7	3.6