


# Photometric test report

<b>Family</b> <b>Apollon® 31</b>	<b>Order number: 51MP11W72342</b> <b>EAN: 4058352926031</b>	<b>LP number</b> <b>59516_2</b>
	<b>Version</b> recessed luminaire for lay-in mounting, square M625, wide distribution, UGR≤19 (L65≤3000cd/m²) <b>Lamps</b> LED 3000 K   CRI ≥ 80 <b>Controlgear</b> ECG <b>Rated values</b> Net luminous flux = 3800 lm Power consumption = 27.5 W Luminous efficacy = 138.2 lm/W	<b>serial documentation</b> <b>11.12.2023</b>

**Luminous intensity in cd/klm**    C180-0    C270-90    **Imax: 456 cd/klm**



Classifications	
DIN 5040	A 5 0
CIE	N1=61 N2=87 N3=97 N4=100 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	100.0%
$\phi_o$	0.0%

**Measurement conditions**  
 DIN EN 13032 and DIN 5032

## Photometric test report

Family <b>Apollon® 31</b>	Order number: <b>51MP11W72342</b> EAN: <b>4058352926031</b>	LP number <b>59516_2</b>
Table of values for luminous intensities		Maximum luminous intensity
<b>siteco</b>		

C-planes	0°	15° 345°	30° 330°	45° 315°	60° 300°	75° 285°	90° 270°
$\gamma$	Luminous intensity in cd/klm						
0°	455.9	455.9	455.9	455.9	455.9	455.9	455.9
5°	454.0	453.9	453.9	453.9	453.9	453.9	453.9
10°	448.0	448.0	448.0	448.1	448.1	448.1	448.1
15°	438.4	438.3	438.4	438.5	438.5	438.6	438.5
20°	425.5	425.3	425.3	425.5	425.7	425.7	425.5
25°	408.8	408.7	408.7	408.8	409.0	409.1	408.9
30°	386.3	386.6	386.8	387.0	387.1	387.3	387.6
35°	356.0	357.3	358.0	358.0	357.9	358.4	359.6
40°	308.0	312.5	314.7	314.8	313.9	315.4	319.3
45°	237.4	240.4	242.0	242.0	242.8	245.2	249.3
50°	157.6	168.1	171.3	167.4	163.5	168.2	181.5
55°	95.3	119.8	128.0	119.9	107.7	114.5	140.2
60°	69.0	89.0	96.4	91.3	79.3	83.2	102.9
65°	59.5	68.4	72.7	72.3	65.8	66.0	72.9
70°	49.1	51.9	54.5	56.9	54.9	52.5	49.7
75°	38.5	40.5	42.0	43.2	41.8	40.0	37.8
80°	30.1	29.9	29.5	28.8	29.4	30.3	31.5
85°	16.8	15.8	15.0	14.4	15.2	15.6	15.7
90°	0.6	0.6	0.5	0.3	0.3	0.3	0.3
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0

## Photometric test report

Family <b>Apollon® 31</b>	Order number: <b>51MP11W72342</b> EAN: <b>4058352926031</b>	LP number <b>59516_2</b>
Table of values for luminous intensities		Maximum luminous intensity
		<b>sITeco</b>

C-planes	105° 255°	120° 240°	135° 225°	150° 210°	165° 195°	180°	Phi-zone	Total Phi-zone
$\gamma$	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0°	455.9	455.9	455.9	455.9	455.9	455.9	2.7	2.7
5°	453.9	453.9	453.9	453.9	453.9	454.0	21.7	24.4
10°	448.1	448.1	448.1	448.0	448.0	448.0	42.6	67.1
15°	438.6	438.5	438.5	438.4	438.3	438.4	62.2	129.3
20°	425.7	425.7	425.5	425.3	425.3	425.5	79.8	209.0
25°	409.1	409.0	408.8	408.7	408.7	408.8	94.7	303.7
30°	387.3	387.1	387.0	386.8	386.6	386.3	106.1	409.8
35°	358.4	357.9	358.0	358.0	357.3	356.0	112.5	522.3
40°	315.4	313.9	314.8	314.7	312.5	308.0	110.7	633.0
45°	245.2	242.8	242.0	242.0	240.4	237.4	94.0	727.0
50°	168.2	163.5	167.4	171.3	168.1	157.6	70.5	797.6
55°	114.5	107.7	119.9	128.0	119.8	95.3	53.0	850.5
60°	83.2	79.3	91.3	96.4	89.0	69.0	41.5	892.1
65°	66.0	65.8	72.3	72.7	68.4	59.5	34.1	926.1
70°	52.5	54.9	56.9	54.5	51.9	49.1	27.5	953.6
75°	40.0	41.8	43.2	42.0	40.5	38.5	21.7	975.3
80°	30.3	29.4	28.8	29.5	29.9	30.1	16.1	991.4
85°	15.6	15.2	14.4	15.0	15.8	16.8	8.4	999.8
90°	0.3	0.3	0.3	0.5	0.6	0.6	0.2	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

<b>Family</b> Apollon® 31	<b>Order number: 51MP11W72342</b> <b>EAN: 4058352926031</b>	<b>LP number</b> 59516_2
------------------------------	--	-----------------------------

<b>UGR-Table</b>	<b>Standard room</b>	<b>siteco</b>
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	15.2	16.8	15.6	17.1	17.4	15.3	16.8	15.6	17.1	17.5
	3H	16.1	17.5	16.5	17.8	18.2	16.2	17.6	16.6	17.9	18.3
	4H	16.6	17.9	16.9	18.2	18.6	16.6	17.9	17.0	18.3	18.6
	6H	17.1	18.3	17.5	18.6	19.0	17.2	18.4	17.6	18.7	19.1
	8H	17.4	18.5	17.8	18.9	19.3	17.4	18.6	17.9	19.0	19.4
	12H	17.6	18.6	18.0	19.0	19.5	17.7	18.7	18.1	19.1	19.5
4H	2H	15.6	16.9	16.0	17.3	17.7	15.7	17.0	16.1	17.3	17.7
	3H	16.8	17.9	17.2	18.2	18.7	16.8	17.9	17.3	18.3	18.7
	4H	17.4	18.4	17.8	18.8	19.2	17.5	18.4	17.9	18.9	19.3
	6H	18.1	19.0	18.6	19.4	19.9	18.2	19.0	18.6	19.5	19.9
	8H	18.5	19.2	18.9	19.7	20.2	18.5	19.3	19.0	19.7	20.2
	12H	18.8	19.5	19.3	19.9	20.4	18.8	19.5	19.3	20.0	20.4
8H	4H	17.7	18.5	18.2	19.0	19.4	17.8	18.6	18.3	19.0	19.5
	6H	18.6	19.3	19.1	19.7	20.2	18.7	19.3	19.2	19.8	20.3
	8H	19.1	19.6	19.6	20.1	20.6	19.1	19.7	19.6	20.2	20.7
	12H	19.5	19.9	20.0	20.4	21.0	19.5	20.0	20.0	20.5	21.0
12H	4H	17.8	18.5	18.3	18.9	19.4	17.9	18.5	18.3	19.0	19.5
	6H	18.7	19.3	19.2	19.8	20.3	18.8	19.3	19.3	19.8	20.3
	8H	19.2	19.7	19.7	20.2	20.7	19.3	19.7	19.8	20.2	20.8

<b>Luminance table</b>	<b>Max. for <math>\gamma \geq 65^\circ</math></b>	<b>Photometric dimensions in mm:</b>	<b>L = 555</b>
			<b>B = 555</b>

C-planes	0°	15° 345°	30° 330°	45° 315°	60° 300°	75° 285°	90° 270°	105° 255°	120° 240°	135° 225°	150° 210°	165° 195°	180°
$\gamma$	Luminance in cd/m <sup>2</sup>												
45°	4141.1	4194.5	4221.7	4222.6	4236.3	4278.5	4349.1	4278.5	4236.3	4222.6	4221.7	4194.5	4141.1
50°	3025.0	3225.3	3287.7	3212.2	3137.1	3227.7	3484.2	3227.7	3137.1	3212.2	3287.7	3225.3	3025.0
55°	2050.4	2577.4	2753.9	2579.9	2316.6	2461.7	3015.1	2461.7	2316.6	2579.9	2753.9	2577.4	2050.4
60°	1701.3	2194.9	2378.4	2251.7	1957.6	2053.6	2539.6	2053.6	1957.6	2251.7	2378.4	2194.9	1701.3
65°	1736.7	1997.4	2121.6	2109.2	1919.7	1926.4	2129.3	1926.4	1919.7	2109.2	2121.6	1997.4	1736.7
70°	1769.4	1872.1	1966.4	2052.6	1981.5	1894.4	1791.1	1894.4	1981.5	2052.6	1966.4	1872.1	1769.4
75°	1836.9	1928.2	2002.7	2060.4	1993.3	1906.6	1800.3	1906.6	1993.3	2060.4	2002.7	1928.2	1836.9
80°	2137.1	2127.4	2096.9	2045.5	2087.1	2150.4	2235.5	2150.4	2087.1	2045.5	2096.9	2127.4	2137.1
85°	2380.8	2242.7	2129.2	2040.3	2144.4	2206.6	2226.7	2206.6	2144.4	2040.3	2129.2	2242.7	2380.8

**Photometric test report**

<b>Family</b> <b>Apollon® 31</b>	<b>Order number: 51MP11W72342</b> <b>EAN: 4058352926031</b>	<b>LP number</b> <b>59516_2</b>
-------------------------------------	--	------------------------------------



**Luminance values in cd/m<sup>2</sup>**

$\gamma$ 65°	$\gamma$ 70°	$\gamma$ 75°	$\gamma$ 80°	$\gamma$ 85°
--------------	--------------	--------------	--------------	--------------

