

Photometric test report

Family
Lunis 41

Order number: 51DS107F34B
EAN: 4069025152138

LP number
59235_8

serial
documentation
16.01.2025



Version recessed luminaire, diffuse cover, extremely wide distribution
Lamps LED 3000 K | CRI ≥ 80
Controlgear ECG
Rated values Net luminous flux = 2150 lm
Power consumption = 17.5 W
Luminous efficacy = 122.9 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 345 cd/klm



Classifications

DIN 5040 A 4 0
CIE N1=47 N2=80 N3=97
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Lunis 41	Order number: 51DS107F34B EAN: 4069025152138	LP number 59235_8
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	344.9	344.9	344.9	344.9	344.9	344.9	344.9	2.1	2.1
5°	342.8	344.0	345.3	344.5	343.8	344.0	344.2	16.4	18.5
10°	337.2	338.5	339.8	339.8	339.8	340.3	340.9	32.3	50.8
15°	330.8	332.2	333.6	333.6	333.6	334.4	335.1	47.3	98.1
20°	321.0	321.7	322.4	323.2	323.9	325.8	327.7	60.7	158.8
25°	307.3	309.8	312.3	312.4	312.4	313.9	315.4	72.3	231.1
30°	294.6	295.5	296.4	297.3	298.2	299.8	301.4	81.5	312.6
35°	277.4	279.1	280.8	280.3	279.9	282.5	285.1	88.2	400.8
40°	257.2	258.8	260.3	260.8	261.2	264.3	267.4	92.1	492.9
45°	234.5	236.6	238.7	238.9	239.1	242.3	245.4	92.7	585.6
50°	211.9	213.7	215.6	215.6	215.7	219.1	222.5	90.8	676.4
55°	185.4	186.8	188.2	189.0	189.8	193.5	197.1	85.2	761.6
60°	157.0	158.4	159.8	160.4	161.1	164.2	167.4	76.4	838.0
65°	126.9	126.3	125.7	127.9	130.2	133.7	137.2	64.2	902.3
70°	95.3	92.3	89.4	92.2	95.1	99.0	102.9	48.7	950.9
75°	62.0	58.6	55.2	53.5	51.8	61.7	71.6	30.7	981.6
80°	32.0	28.3	24.7	22.4	20.0	28.2	36.4	14.2	995.8
85°	8.7	7.4	6.2	5.4	4.6	9.1	13.5	4.0	999.8
90°	0.3	0.4	0.4	0.3	0.1	0.4	0.7	0.2	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Lunis 41	Order number: 51DS107F34B EAN: 4069025152138	LP number 59235_8
--------------------	---	----------------------

UGR-Table		Standard room							siTeco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	23.7	25.4	24.1	25.7	26.1	24.0	25.6	24.3	26.0	26.3
	3H	25.3	26.8	25.7	27.1	27.5	25.6	27.1	26.0	27.4	27.8
	4H	25.8	27.2	26.2	27.6	28.0	26.2	27.6	26.6	28.0	28.3
	6H	26.1	27.5	26.6	27.8	28.2	26.6	27.9	27.0	28.3	28.6
	8H	26.3	27.5	26.7	27.9	28.3	26.7	27.9	27.1	28.3	28.7
	12H	26.3	27.5	26.7	27.8	28.3	26.8	27.9	27.2	28.3	28.7
4H	2H	24.5	25.9	24.9	26.3	26.7	24.7	26.1	25.1	26.5	26.8
	3H	26.2	27.4	26.6	27.8	28.2	26.4	27.6	26.9	28.0	28.4
	4H	26.8	27.9	27.2	28.3	28.7	27.1	28.2	27.5	28.6	29.0
	6H	27.2	28.1	27.6	28.5	29.0	27.5	28.4	28.0	28.9	29.3
	8H	27.3	28.1	27.7	28.6	29.1	27.6	28.5	28.1	28.9	29.4
	12H	27.3	28.1	27.8	28.6	29.0	27.7	28.5	28.2	28.9	29.4
8H	4H	27.0	27.9	27.5	28.3	28.8	27.3	28.1	27.7	28.6	29.0
	6H	27.4	28.2	27.9	28.6	29.1	27.7	28.4	28.2	28.9	29.4
	8H	27.6	28.2	28.1	28.7	29.2	27.8	28.5	28.3	28.9	29.5
	12H	27.6	28.2	28.1	28.7	29.2	27.9	28.5	28.5	29.0	29.5
12H	4H	27.0	27.8	27.5	28.2	28.7	27.3	28.1	27.8	28.5	29.0
	6H	27.5	28.1	28.0	28.6	29.1	27.7	28.3	28.2	28.8	29.3
	8H	27.6	28.1	28.1	28.6	29.2	27.9	28.4	28.4	28.9	29.4

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		D = 186	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	26246.3	26477.0	26707.6	26732.4	26757.1	27111.3	27465.6
50°	26081.5	26307.9	26534.5	26543.6	26552.6	26969.4	27386.4
55°	25572.4	25765.4	25958.4	26070.1	26181.8	26689.6	27197.3
60°	24838.5	25059.7	25281.3	25386.0	25491.0	25991.8	26492.7
65°	23762.8	23652.5	23542.2	23955.6	24369.2	25030.9	25692.4
70°	22038.9	21357.6	20676.3	21340.5	22004.7	22907.7	23810.4
75°	18950.8	17915.3	16879.8	16362.2	15844.6	18860.6	21876.5
80°	14558.7	12915.1	11271.5	10197.9	9124.4	12848.1	16571.9
85°	7886.7	6750.1	5614.3	4878.9	4143.5	8220.8	12297.2

Photometric test report

Family
Lunis 41

Order number: 51DS107F34B
EAN: 4069025152138

LP number
59235_8

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

