




Photometric test report

Family Monsun® 21	Order number: 51FB20DL447K3H EAN: 4069025131744	LP number 59394_67
	Version prismatic diffuser, opal, polycarbonate, wide distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Setting emergency light operation: 3 h Rated values Net luminous flux = 830 lm Power consumption = 4.5 W Luminous efficacy = 184.4 lm/W	serial documentation 05.02.2026
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 318 cd/klm**



Classifications	
DIN 5040	A 4 1
CIE	N1=45 N2=75 N3=93 N4=94 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	93.7%
ϕ_o	6.3%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 21	Order number: 51FB20DL447K3H EAN: 4069025131744	LP number 59394_67
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	318.2	318.2	318.2	318.2	318.2	318.2	318.2	1.9	1.9
5°	317.5	317.5	315.1	315.9	316.6	317.2	317.8	15.1	17.0
10°	312.4	312.6	310.3	310.8	311.5	312.2	312.9	29.7	46.7
15°	304.0	304.5	302.1	302.5	303.1	303.6	304.5	43.0	89.7
20°	293.0	293.3	291.0	291.0	291.4	291.9	292.8	54.7	144.5
25°	278.2	280.0	277.5	276.9	276.9	277.3	278.2	64.3	208.8
30°	264.9	265.0	262.4	260.7	260.0	260.0	261.0	71.8	280.6
35°	248.3	248.5	245.7	243.1	241.2	240.6	241.7	76.7	357.3
40°	231.4	230.9	227.8	224.4	221.2	219.7	220.8	79.3	436.6
45°	213.0	212.5	208.9	204.3	200.0	197.3	198.2	79.4	515.9
50°	194.4	193.4	189.5	184.3	178.4	174.4	174.7	77.3	593.2
55°	174.9	174.0	169.9	163.6	156.5	151.3	150.6	73.2	666.4
60°	155.2	153.6	149.3	142.2	134.7	128.1	126.2	67.1	733.5
65°	134.5	133.3	127.9	120.6	112.6	105.3	102.1	59.5	793.0
70°	113.8	111.2	106.2	98.6	90.1	81.8	77.7	50.1	843.1
75°	91.9	90.6	84.2	76.2	67.3	58.7	53.5	39.7	882.8
80°	70.8	68.8	62.9	54.4	45.2	36.1	30.1	28.6	911.4
85°	52.2	50.3	44.7	36.3	26.8	17.6	11.2	18.9	930.2
90°	41.3	39.2	33.7	25.7	16.7	7.7	2.0	13.2	943.5
95°	37.2	35.5	30.5	23.1	14.2	5.7	1.8	11.7	955.1
100°	33.6	31.9	27.2	20.0	11.9	4.1	1.6	10.1	965.3
105°	29.8	28.2	23.6	17.2	9.5	2.6	1.4	8.5	973.8
110°	26.0	24.2	20.2	14.2	7.2	1.5	1.2	7.0	980.8
115°	21.9	20.5	16.9	11.4	5.1	1.4	1.2	5.5	986.3
120°	18.6	17.0	13.7	8.7	3.2	1.3	1.1	4.3	990.6
125°	14.8	13.4	10.4	6.0	1.7	1.3	1.1	3.1	993.6
130°	11.3	10.0	7.4	3.7	1.5	1.3	1.1	2.1	995.7
135°	7.8	6.8	4.7	1.9	1.5	1.3	1.0	1.3	997.1
140°	4.8	4.0	2.4	1.7	1.5	1.2	1.0	0.8	997.9
145°	2.3	2.1	1.9	1.7	1.5	1.3	1.2	0.5	998.4
150°	2.0	2.0	1.9	1.7	1.5	1.4	1.3	0.5	998.9
155°	1.9	1.9	1.8	1.7	1.5	1.4	1.3	0.4	999.3
160°	1.8	1.8	1.8	1.6	1.5	1.5	1.4	0.3	999.6
165°	1.7	1.7	1.6	1.5	1.5	1.5	1.4	0.2	999.8
170°	1.5	1.6	1.5	1.5	1.5	1.5	1.4	0.1	999.9
175°	1.5	1.5	1.5	1.5	1.5	1.5	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

Photometric test report

Family Monsun® 21	Order number: 51FB20DL447K3H EAN: 4069025131744	LP number 59394_67
------------------------------------	--	-------------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	14.2	15.9	14.6	16.2	16.6	13.9	15.6	14.3	16.0	16.3
	3H	16.0	17.6	16.4	17.9	18.3	15.5	17.0	15.8	17.4	17.7
	4H	16.9	18.3	17.3	18.7	19.1	16.1	17.6	16.5	17.9	18.3
	6H	17.6	19.0	18.0	19.3	19.7	16.5	17.9	16.9	18.2	18.6
	8H	17.9	19.2	18.4	19.6	20.0	16.6	17.9	17.1	18.3	18.7
	12H	18.2	19.4	18.7	19.8	20.2	16.7	17.9	17.1	18.3	18.7
4H	2H	14.9	16.4	15.3	16.8	17.1	14.7	16.2	15.1	16.5	16.9
	3H	17.0	18.2	17.4	18.6	19.0	16.5	17.7	16.9	18.1	18.5
	4H	17.9	19.1	18.4	19.5	19.9	17.2	18.3	17.6	18.8	19.2
	6H	18.8	19.8	19.3	20.3	20.7	17.7	18.7	18.2	19.2	19.6
	8H	19.2	20.1	19.7	20.6	21.0	17.9	18.8	18.3	19.3	19.7
	12H	19.6	20.4	20.1	20.9	21.4	18.0	18.8	18.5	19.3	19.8
8H	4H	18.3	19.2	18.7	19.6	20.1	17.6	18.6	18.1	19.0	19.5
	6H	19.3	20.1	19.8	20.6	21.1	18.3	19.1	18.8	19.6	20.1
	8H	19.8	20.5	20.3	21.0	21.5	18.5	19.2	19.0	19.7	20.2
	12H	20.3	20.9	20.8	21.4	21.9	18.7	19.3	19.2	19.8	20.3
12H	4H	18.3	19.2	18.8	19.6	20.1	17.7	18.6	18.2	19.0	19.5
	6H	19.4	20.1	19.9	20.6	21.1	18.5	19.1	19.0	19.6	20.1
	8H	20.0	20.6	20.5	21.1	21.6	18.7	19.3	19.3	19.8	20.4

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1299	H(C0) = 21	H(C180) = 21
			B = 87	H(C90) = 21	H(C270) = 21

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		1782.5	1783.7	1782.3	1795.1	1830.6	1900.4	2026.0	
50°		1724.9	1722.1	1719.9	1729.8	1756.3	1822.8	1958.9	
55°		1665.7	1663.7	1660.4	1662.5	1680.2	1742.7	1884.2	
60°		1607.5	1599.3	1593.2	1587.3	1604.0	1657.1	1803.7	
65°		1540.2	1535.3	1517.1	1507.3	1518.5	1567.0	1715.6	
70°		1468.9	1445.9	1428.5	1411.6	1411.8	1446.7	1597.4	
75°		1372.0	1363.6	1320.0	1287.4	1270.1	1289.9	1431.2	
80°		1263.4	1239.5	1191.9	1131.4	1084.2	1059.1	1166.5	
85°		1169.3	1141.8	1080.7	992.9	888.3	781.7	795.8	

Photometric test report

Family Monsun® 21	Order number: 51FB20DL447K3H EAN: 4069025131744	LP number 59394_67
------------------------------------	--	-------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

siteco

