

Order No.: 5XA7694F000AD | **GTIN (EAN):** 4058352399088

Product description: FL20mxG4,hous,DA,948W,IC1



Floodlight FL 20 maxi Gen.4, housing, primary light characteristic: asymmetric, control gear: DALI, control: overheat protection, electronic power reduction, with terminal, 5-pole, max. 2.5mm², mains connection: 220..240V, AC, rated input power: 948W, housing frame, housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 975mm, width: 730mm, height: 115mm, DALI, protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, ball protection: ball impact resistant, packaging unit: 1 piece



Wt. (kg):	13.9
GTIN (EAN):	4058352399088

Order No.: 5XA7694F000AD | **GTIN (EAN):** 4058352399088

Detailed technical description: FL20mxG4,hous,DA,948W,IC1



Key data

- Product type: housing
- Product name: Floodlight FL 20 maxi Gen.4
- Order No.: 5XA7694F000AD

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Symmetry: asymmetric distribution

Lamps:

- Rated input power: 948W

Operating device:

- Control gear: ECG Plus
- Control: DALI
- Equipment: overheat protection
- Switching method: electronic power reduction

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, ENEC, VDE

Material, Colour

- housing frame: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S)
- housing: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S)
- Colour specification: Siteco® metallic grey (DB 702S)

Electrical connection

- Connection: terminal, 5-pole, max. 2.5mm²
- Nominal voltage: 220..240V, AC
- Surge voltage resistance: 10kV 1.2/50µs

Dimensions, Weight

- Length: 975mm
- Width: 730mm
- Height: 115mm
- Weight: 13.9kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -