

Order No.: 5DTAXTSCF62003 | GTIN (EAN): 4050737913544 Product description: AXT,3ph-tr,rec,wh,L2000,DA



AX T, 3-phase track, installation type: recessed, mains connection: 220..240V/380..400V, AC, of extruded aluminium section, coated, white, length: 2.000 mm, width: 32 mm, height: 33mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, packaging unit: 1 piece

∰ IP 20 🛓 (€

Wt. (kg): 2.0 GTIN (EAN): 4050737913544

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 24.02.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 5DTAXTSCF62003 | GTIN (EAN): 4050737913544 Detailed technical description: AXT,3ph-tr,rec,wh,L2000,DA



Key data

- Product type: 3-phase track
- Product name: AX T
- Order No.: 5DTAXTSCF62003

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: max. 16A

Operating device:

- Control: DALI

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I
 - (protective earthing)
- Certification, designation: CE, ENEC

Material, Colour

- Colour specification: white
- Mounting
- Mounting method, mounting location: recessed, in the ceiling

Electrical connection

 Nominal voltage: 220..240V/380..400V, AC

Dimensions, Weight

- Length: 2000mm
- Width: 32mm
- Height: 33mm
- Weight: 2.0kg