

Order No.: 5EA3AM000001 | GTIN (EAN): 4058352404607

**Product description:** SConWi,SmartPlug



SITECO Connect WirelessSmart Plug, luminaire controller, communication: 2.4GHz, local mesh radio network, D4i type A, control: local setting and operation with USB stick, by daylight, manual, by time, by timer, by weekday, optionally via radio push button, sensor technology: daylight sensor, inclination sensor, Smart Interface below and above, automatic adjustment of the DALI dimming curve, optionally adjustable manually, optional remote setup and operation via gateway, installation type: screw fastening, installation location: to the luminaire, of PBT, voltage: 24V, voltage type: DC, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 CE

Wt. (kg): 0.1  
GTIN (EAN): 4058352404607

Order No.: 5EA3AM000001 | GTIN (EAN): 4058352404607

Detailed technical description: SConWi,SmartPlug



#### Key data

- System family: SITECO Connect
- Product type: luminaire controller
- Product name: SITECO Connect Wireless
- Order No.: 5EA3AM000001

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Operating device:

- Control: DALI DT8, D4i, Smart Interface below and above, automatic adjustment of the DALI dimming curve, optionally adjustable manually, optional remote setup and operation via gateway

#### Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

#### Material, Colour

- housing: PBT, transparent, colour-backed, transparent

#### Mounting

- Mounting method, mounting location: screw fastening, to the luminaire

#### Electrical connection

- Nominal voltage: 24V, DC

#### Dimensions, Weight

- Diameter: 81.5mm
- Height: 33mm
- Weight: 0.1kg