


Order No.: 5TR10350H | GTIN (EAN): 4039806496355

Product description: Mod,trunk.rail,3lg,L3588,5x2.52,wh




Modario®, trunking rail, of sheet steel, coated, pure white, 3-length, length: 3.588 mm, width: 58 mm, height: 43mm, through-wiring: 5x 2.5mm², with terminal, 5-pole, max. 2.5mm², protection rating (complete): for IP20/IP40 protection rating, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, standard: EN 60598, packaging unit: 1



Wt. (kg): 4.7

GTIN (EAN): 4039806496355





Order No.: 5TR10350H | GTIN (EAN): 4039806496355

Detailed technical description: Mod,trunk.rail,3lg,L3588,5x2.5²,wh



Key data

- Product type: trunking components group (TS)
- Product name: Modario®
 Order No.: 5TR10350H

Lighting technology | Lamps | Control gear

Component 1

Lamps:

 Supplement: for electrical and mechanical plug and socket connection of rail elements

Certificates, Standards

- Protection rating: for IP20/IP40 protection rating
- Insulation class: insulation class I (protective earthing)
- Standard: EN 60598
- Certification, designation: CE, ENEC, VDE

Material, Colour

- trunking rail: sheet steel, coated, pure white, 3-length
- Colour specification: pure white

Mounting

- Mounting method, mounting location: suspended mounting, surfacemounted, to the ceiling
- Arrangement: single/continuous arrangement
- Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: terminal, 5-pole, max.
 2.5mm²
- Through-wiring: 5x 2.5mm²

Dimensions, Weight

System units: 12x SELength: 3588mmWidth: 58mmHeight: 43mm

- Mounting distance: max. 3.5m

- Weight: 4.7kg



Order No.: 5TR10350H | GTIN (EAN): 4039806496355

Dimensions: Mod,trunk.rail,3lg,L3588,5x2.52,wh

