

**Order No.:** 5LS591030 | **GTIN (EAN):** 4050737712284

**Product description:** Mon11Xbatt.box,batt.box,emerg.lght.elem



Monsun 11 Extreme, battery box, battery box, installation type: surface-mounted, with system connector: plug/socket, 2-pole, control gear: emergency light element, battery: NiMH, 4Ah, mains connection: 6V, DC, fixing bracket, of stainless steel (V2A), grey, battery box, rectangular, of PC, grey, protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, permissible operating ambient temperature: +5..+40°C, standard: EN 60598-2-22, packaging unit: 1 piece

IP 66  

Wt. (kg): 0.9  
GTIN (EAN): 4050737712284

**Order No.:** 5LS591030 | **GTIN (EAN):** 4050737712284

**Detailed technical description:** Mon11Xbatt.box,batt.box,emerg.lght.elem



## Key data

- Product type: battery box
- Product name: Monsun 11 Extreme
- Order No.: 5LS591030

## Lighting technology | Lamps | Control gear

### Component 2

#### Lamps:

- Supplement: for emergency light function, suitable for emergency light operating devices according to EN 60598-2-22, battery NiMH 4Ah 6V(DC)

#### Operating device:

- Control gear: emergency light element
- Battery: NiMH
- Nominal operating time: 3h

#### Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): +5..+40°C
- Standard: EN 60598-2-22
- Certification, designation: CE, UKCA

#### Material, Colour

- fixing bracket: stainless steel (V2A), grey
- Colour specification: grey
- battery box: PC, grey, rectangular
- Colour specification: grey

#### Mounting

- Mounting method, mounting location: surface-mounted, to the luminaire
- Arrangement: single arrangement

#### Electrical connection

- Connection: system connector: plug/socket, 2-pole

#### Dimensions, Weight

- Weight: 0.9kg