

Order No.: 5TR31SDS | GTIN (EAN): 4058352139059 Product description: Mod,track-ad-ins,DA,wh,2su



Modario[®], track adapter insert, with plug, 5-pole, with phase selection, for trunking rail, 10-core, mains connection: 230/400V, track adapter insert, of sheet steel, coil coated, pure white, 2x system unit, max. weight load 5kg, length: 598mm, width: 48mm, protection rating (complete): for IP20 protection rating, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece

⊕ (€

Wt. (kg): 0.8 GTIN (EAN): 4058352139059

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 07.07.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 5TR31SDS | GTIN (EAN): 4058352139059 Detailed technical description: Mod,track-ad-ins,DA,wh,2su



Key data

- Product type: track adapter insert
- Product name: Modario®
- Order No.: 5TR31SDS

Lighting technology | Lamps | Control gear

Component 1

- Lamps:
- Supplement: max. current consumption 6A

Operating device:

- Control: DALI

Certificates, Standards

- Protection rating: for IP20 protection rating
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Material, Colour

- track adapter insert: sheet steel, coil coated, pure white, 2x system unit, max. weight load 5kg
- Colour specification: pure white

Electrical connection

- Connection: plug, 5-pole, with phase selection, for trunking rail, 10-core
- Nominal voltage: 230/400V

Dimensions, Weight

- System units: 2x SE
- Length: 598mm
- Width: 48mm
- Weight: 0.8kg