

Order No.: 5XA7680D2D00C | GTIN (EAN): 4058352233771

Product description: FL20md, LED-unit, PL52, 740, 142W



Floodlight FL 20 midi, LED unit, primary light control with lens, of plastic, primary optical cover: cover panel, of toughened safety glass, transparent, light distribution: PL52, light emission: direct distribution, primary light characteristic: asymmetric, installation type: screw fastening, LED, High Power LED, light colour: 740, colour temperature: 4000K, with cable with plug, mains connection: 220..240V, AC, 50/60Hz, rated input power: 142W, LED unit, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 402mm, width: 421mm, height: 57mm, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 (€

Lamps: LED Wt. (kg): 5.5

GTIN (EAN): 4058352233771



Order No.: 5XA7680D2D00C | GTIN (EAN): 4058352233771

Detailed technical description: FL20md, LED-unit, PL52, 740, 142W



Key data

- Product type: LED unit

- Product name: Floodlight FL 20 midi

Order No.: 5XA7680D2D00C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of plastic

- Cover: cover panel, transparent

- Light distribution: PL52

- Symmetry: asymmetric distribution

- Light emission: direct distribution

Lamps:

- Lamps: High Power LED, LED

- Colour temperature: 4000K

- Colour rendering index: CRI > 70

- Light colour: 740

- Rated input power: 142W

Certificates, Standards

- Protection rating: IP66

- Certification, designation: CE

Material, Colour

 LED unit: diecast aluminium, powdercoated, Siteco® metallic grey (DB 702S)

 Colour specification: Siteco® metallic grey (DB 702S)

Cover: cover panel of toughened safety glass

Mounting

 Mounting method, mounting location: screw fastening, in housing

Electrical connection

- Connection: cable with plug

 Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

Length: 402mmWidth: 421mmHeight: 57mmWeight: 5.5kg