


Order No.: 59MX2AW000BA | **GTIN (EAN):** 4058352608807


Product description: Sil21,controller,wirel



Silica® 21controller, master, local control, dimmable, installation arrangement: single/continuous arrangement, installation type: slip-in mounting, installation location: to the luminaire, of extruded aluminium section, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece


IP 20  

Wt. (kg): 0.3
GTIN (EAN): 4058352608807



Order No.: 59MX2AW000BA | GTIN (EAN): 4058352608807

Detailed technical description: Sil21,controller,wirel



Key data

- System family: SITECO Connect 31 Wireless
- Product type: control unit
- Product name: Silica® 21
- Order No.: 59MX2AW000BA

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: Bluetooth® mesh 4.2, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): 0..+40°C
- Certification, designation: CE

Material, Colour

- housing: extruded aluminium section, anodised, jet black (RAL 9005), for luminaires with darklight reflector
- Colour specification: jet black (RAL 9005)

Mounting

- Mounting method, mounting location: slip-in mounting, to the luminaire
- Arrangement: single/continuous arrangement
- Supplement: for surface-mounted luminaires, for pendant luminaires

Dimensions, Weight

- Length: 127mm
- Width: 53mm
- Height: 54mm
- Weight: 0.3kg

Order No.: 59MX2AW000BA | GTIN (EAN): 4058352608807

Dimensions: Sil21,controller,wirel

