



Order No.: 51WD107AG1AS | **GTIN (EAN):** 4058352520956


Product description: Rond41,1350lm830/840,0/1,PMMA,sens,wh



Rondel 41, wall and ceiling luminaire, primary optical cover: enclosure, of PMMA, opal, light emission: direct distribution, primary light characteristic: symmetric, installation type: surface-mounted, LED, rated luminous flux: 1.350lm, luminous efficacy: 96lm/W, light colour: 830/840, colour temperature: 3000/4000K, control gear: ON/OFF, with terminal, 3-pole, max. 2.5mm², mains connection: 230V, AC, 50/60Hz, rated input power: 14W, luminaire housing, round, of steel, powder-coated, white, diameter: 280mm, height: 100mm, brightness and presence sensor, HF sensor, protection rating (complete): IP44, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, permissible operating ambient temperature: -20..+40°C, permissible storage temperature: -30..+80°C, packaging unit: 1 piece


IP 44  

Lamps:	LED
Wt. (kg):	0.6
GTIN (EAN):	4058352520956



Order No.: 51WD107AG1AS | GTIN (EAN): 4058352520956

Detailed technical description: Rond41,1350lm830/840,0/1,PMMA,sens,wh



Key data

- Product type: wall and ceiling luminaire
- Product name: Rondel 41
- Order No.: 51WD107AG1AS

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Cover: enclosure, opal
- Beam angle: diffuse distribution
- Symmetry: symmetric
- Light emission: direct distribution

Lamps:

- Lamps: with LED
- Rated luminous flux: 1350lm
- Luminous efficacy: 96lm/W
- Colour temperature: 3000/4000K
- Colour rendering index: CRI > 80
- Light colour: 830/840
- SDCM (Standard Deviation of Colour Matching): MacAdam \leq 5 SDCM (initial)
- Rated input power: 14W
- Supplement: colour temperature can be selected via DIP switch

Operating device:

- Control gear: ECG
- Control: ON/OFF

Certificates, Standards

- Protection rating: IP44
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Temperature range (operation): -20..+40°C
- Certification, designation: CE

Material, Colour

- luminaire housing: steel, powder-coated, white, round
- Cover: enclosure of PMMA

Mounting

- Mounting method, mounting location: surface-mounted, to the ceiling, to the wall
- Arrangement: single arrangement

Electrical connection

- Connection: terminal, 3-pole, max. 2.5mm²
- Nominal voltage: 230V, 220..240V, 50/60Hz, AC

Dimensions, Weight

- Diameter: 280mm
- Height: 100mm
- Weight: 0.6kg

Service life

- Rated service life: 50000h (L80/B10) at AT = 25°C

Order No.: 51WD107AG1AS | GTIN (EAN): 4058352520956

Dimensions: Rond41,1350lm830/840,0/1,PMMA,sens,wh

