

Order No.: 5EA3CM000001 | **GTIN (EAN):** 4058352571590

Product description: SConWi,SmartPlugCellular



SITECO Connect WirelessSmart Plug Cellular, luminaire controller, communication: local mesh radio network, EGPRS, NB-IoT NB2, LTE Cat M1, 5G, 4G, 2G, 2.4GHz, D4i type A, control: remote setup and operation, local setting and operation with USB stick, manual, by time, by timer, by weekday, by AstroDim calendar, by daylight, via API, with radio clock, optionally via radio push button, sensor technology: GALILEO, GLONASS, GNSS, GPS, inclination sensor, temperature sensor, daylight sensor, Usage fees for remote access via web application and mobile network (LTE CAT M1 / NB IoT NB2 / EGPRS) are included in the scope of delivery, amounting to 60 credit points (= 60 months). This individually extendable term begins when the device's QR code is scanned into a system. The credit can then be used by other devices within the system, Smart Interface below and above, Logarithmic DALI dimming curve preset. Can be switched to linear via software, installation type: screw fastening, installation location: to the luminaire, Smart Interface above: Zhaga, Smart Interface below: Zhaga, of PBT, voltage: 24V, voltage type: DC, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 

Wt. (kg): 0.1
GTIN (EAN): 4058352571590

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 23.01.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5EA3CM000001 | **GTIN (EAN):** 4058352571590

Detailed technical description: SConWi,SmartPlugCellular



Key data

- System family: SITECO Connect
- Product type: luminaire controller
- Product name: SITECO Connect Wireless
- Order No.: 5EA3CM000001

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI DT8, D4i, Smart Interface below and above, Usage fees for remote access via web application and mobile network (LTE CAT M1 / NB IoT NB2 / EGPRS) are included in the scope of delivery, amounting to 60 credit points (= 60 months). This individually extendable term begins when the device's QR code is scanned into a system. The credit can then be used by other devices within the system, Logarithmic DALI dimming curve preset. Can be switched to linear via software

Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): - 40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

Material, Colour

- housing: PBT, transparent, colour-backed, transparent
- Colour specification: transparent

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire

Electrical connection

- Nominal voltage: 24V, DC

Dimensions, Weight

- Diameter: 80mm
- Height: 46mm
- Weight: 0.1kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 23.01.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -