

Order No.: 5XA7681D0000C | **GTIN (EAN):** 4058352236482

Product description: FL20md,hous,Basic,142W,IC1



Floodlight FL 20 midi, housing, primary light characteristic: asymmetric, control gear: ECG Basic, control: overheat protection, electronic power reduction, with terminal, 5-pole, max. 2.5mm², mains connection: 220..240V, AC, rated input power: 142W, housing frame, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm, length: 654mm, width: 450mm, height: 76mm, ON/OFF, protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, packaging unit: 1 piece



Wt. (kg): 6.5
GTIN (EAN): 4058352236482

Order No.: 5XA7681D0000C | GTIN (EAN): 4058352236482

Detailed technical description: FL20md,hous,Basic,142W,IC1



Key data

- Product type: housing
- Product name: Floodlight FL 20 midi
- Order No.: 5XA7681D0000C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Symmetry: asymmetric distribution

Lamps:

- Rated input power: 142W

Operating device:

- Control gear: ECG Basic
- Control: Basic
- Equipment: overheat protection
- Switching method: electronic power reduction

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, ENEC, VDE

Material, Colour

- housing frame: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- Colour specification: Siteco® metallic grey (DB 702S)

Electrical connection

- Connection: terminal, 5-pole, max. 2.5mm²
- Nominal voltage: 220..240V, AC

Dimensions, Weight

- Length: 654mm
- Width: 450mm
- Height: 76mm
- Weight: 6.5kg