


## Order No.: 59MX2AW000SA | GTIN (EAN): 4058352608814

## Product description: Sil21,controller,wirel




Silica® 21controller, master, local control - self-sufficient standalone sensors, dimmable, installation arrangement: single/continuous arrangement, installation type: slip-in mounting, installation location: to the luminaire, of extruded aluminium section, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece

IP 20 ⊕ (∈

Wt. (kg): 0.3


GTIN (EAN): 4058352608814





## Order No.: 59MX2AW000SA | GTIN (EAN): 4058352608814

### Detailed technical description: Sil21,controller,wirel



#### Key data

System family: SITECO Connect 31 Wireless

Product type: control unit
Product name: Silica® 21
Order No.: 59MX2AW000SA

# Lighting technology | Lamps | Control gear

#### Component 1

#### Operating device:

 Control: Bluetooth® Mesh 4.2, dimmable

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): 0..+40°C
- Certification, designation: CE

#### Material, Colour

- housing: extruded aluminium section, anodised, metallic grey (RAL 9006), for luminaires with darklight reflector
- Colour specification: metallic grey (RAL 9006)

#### Mounting

- Mounting method, mounting location: slip-in mounting, to the luminaire
- Arrangement: single/continuous arrangement
- Supplement: for surface-mounted luminaires, for pendant luminaires

#### **Dimensions, Weight**

Length: 127mmWidth: 53mmHeight: 54mmWeight: 0.3kg



## Order No.: 59MX2AW000SA | GTIN (EAN): 4058352608814

**Dimensions:** Sil21,controller,wirel

