

Order No.: 59TP1CN7 | GTIN (EAN): 4058352340240

Product description: Lic-cent.feed-I/I,L450,7x2.52,IP64,wh



Licross® central feed for 2x feed-in, white; wiring trunking rail element of sheet steel, galvanised, coated, with cable entry for four cables, Ø 8.5..13mm; 2x end cap of PC, white, with cable entry for one cable, Ø 8.5..16mm; blank cover of PC/ABS, white; 2x connector of steel, galvanised, connector preassembled on trunking rail; connection via terminal, 7-pole, 1.5..2.5mm², wired ready for connection, internal wiring halogen-free; dimension: (LxWxH) = 450 x 64 x 67mm; for protection rating IP50/IP54/IP64; insulation class: insulation class I (protective earthing); certification: CE, UKCA; packaging unit: 1 piece

(<u>I</u>

 \in

Wt. (kg): 1.6

GTIN (EAN): 4058352340240



Order No.: 59TP1CN7 | GTIN (EAN): 4058352340240

Detailed technical description: Lic-cent.feed-I/I,L450,7x2.52,IP64,wh



Key data

Product type: additional feed
Product name: Licross®

- Order No.: 59TP1CN7

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: for connection on rail side

Component 2

Certificates, Standards

- Protection rating: for protection rating IP50/IP54/IP64
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

Material, Colour

- trunking rail element: sheet steel, galvanised, coated, white
- Colour specification: white
- end cap: PC, white
- Quantity: 2 pieceColour specification: white
- blank cover: PC/ABS, white
- Colour specification: white
- connector: steel, galvanised, connector pre-assembled on trunking rail
- Quantity: 2 piece

Electrical connection

- Connection: terminal, 7-pole, 1.5..2.5mm²
- Through-wiring: 7x 2.5mm²

Dimensions, Weight

Length: 450mmWidth: 64mmHeight: 67mmWeight: 1.6kg