

Order No.: 59TP1CNE | GTIN (EAN): 4058352340264 Product description: Lic-cent.feed-I/I,L650,14x2.5²,IP64,wh



Licross[®] central feed for 2x feed-in, white; wiring trunking rail element of sheet steel, galvanised, coated, with cable entry for six cables, Ø 8.5..13mm; 2x end cap of PC, white, with cable entry for one cable, Ø 8.5..16mm; blank cover of PC/ABS, white; 2x connector of steel, galvanised, connector pre-assembled on trunking rail; connection via terminal, 14-pole, 1.5..2.5mm², wired ready for connection, internal wiring halogen-free; dimension: (LxWxH) = 650 x 64 x 67mm; for protection rating IP50/IP54/IP64; insulation class: insulation class I (protective earthing); certification: CE, UKCA; packaging unit: 1 piece

⊕ (€

Wt. (kg): 2.1 GTIN (EAN): 4058352340264

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 11.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 59TP1CNE | GTIN (EAN): 4058352340264 Detailed technical description: Lic-cent.feed-I/I,L650,14x2.5²,IP64,wh



Key data

- Product type: additional feed
- Product name: Licross®
- Order No.: 59TP1CNE

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: for connection on rail side

Component 2

Certificates, Standards

- Protection rating: for protection rating IP50/IP54/IP64
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

Material, Colour

- trunking rail element: sheet steel, galvanised, coated, white
- Colour specification: white
- end cap: PC, white
- Quantity: 2 piece
- Colour specification: white
- blank cover: PC/ABS, white
- Colour specification: white
- connector: steel, galvanised, connector pre-assembled on trunking rail
- Quantity: 2 piece

Electrical connection

- Connection: terminal, 14-pole,
- 1.5..2.5mm² — Through-wiring: 14x 2.5mm²

Dimensions, Weight

- Length: 650mm
- Width: 64mm
- Height: 67mm
- Weight: 2.1kg