

Order No.: 5XA861D2N0A | **GTIN (EAN):** 4050737978314

Product description: TV20VPL,LED,2130lm840,DALI,PC,dir,surf



TV 20, vandal-proof luminaire, primary light control with specular reflector, of aluminium, matt, primary optical cover: enclosure, of PC, frosted, light emission: direct distribution, primary light characteristic: symmetric, installation type: surface-mounted, LED, rated luminous flux: 2.130lm, luminous efficacy: 101lm/W, light colour: 840, colour temperature: 4000K, control gear: DALI, mains connection: 230V, AC, 50Hz, rated input power: 21W, luminaire housing, of aluminium, coated, Siteco® metallic grey (DB 702S), with wall and ceiling fixing element, length: 705mm, width: 260mm, height: 70mm, mounting height: 2.5..4.0m, protection rating (complete): IP65, insulation class (complete): insulation class I (protective earthing), certification: CE, protection symbol: F, impact resistance: 2x IK10, standard: EN 60598, packaging unit: 1 piece


4050737978314

5XA861D2N0A


LED 4000K / CRI ≥ 80

Φ_h 2130 lm

IP 65 2xIK 10



Lamps: LED
Wt. (kg): 4.1
GTIN (EAN): 4050737978314



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5XA861D2N0A | **GTIN (EAN):** 4050737978314

Detailed technical description: TV20VPL,LED,2130lm840,DALI,PC,dir,surf



Key data

- Product type: vandal-proof luminaire
- Product name: TV 20
- Order No.: 5XA861D2N0A

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: specular reflector of aluminium, matt
- Cover: enclosure, frosted
- Symmetry: symmetric
- Light emission: direct distribution

Lamps:

- Lamps: with LED
- Rated luminous flux: 2130lm
- Luminous efficacy: 101lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 21W

Operating device:

- Control gear: ECG DALI
- Control: DALI

Certificates, Standards

- Protection rating: IP65
- Insulation class: insulation class I (protective earthing)
- Impact resistance: 2x IK10
- Protection symbol: F
- Standard: EN 60598
- Certification, designation: CE

Material, Colour

- luminaire housing: aluminium, coated, Siteco® metallic grey (DB 702S), with wall and ceiling fixing element
- Colour specification: Siteco® metallic grey (DB 702S)
- Cover: enclosure of PC

Mounting

- Mounting method, mounting location: surface-mounted, to the ceiling, to the wall
- Arrangement: single/continuous arrangement

Electrical connection

- Nominal voltage: 230V, 50Hz, AC

Dimensions, Weight


- Length: 705mm
- Width: 260mm
- Height: 70mm
- Weight: 4.1kg

Service life

- Rated service life: 50000h (L80/B10) at AT = 25°C

Order No.: 5XA861D2N0A | **GTIN (EAN):** 4050737978314

Dimensions: TV20VPL,LED,2130lm840,DALI,PC,dir,surf



Order No.: 5XA861D2N0A | GTIN (EAN): 4050737978314

Planning data: TV20VPL,LED,2130lm840,DALI,PC,dir,surf


5XA861D2N0A: 1x LED 4000K
/ CRI ≥ 80

4050737978314

5XA861D2N0A

LED 4000K / CRI ≥ 80

Φ_h 2130 lm



C 0/180

C 90/270

No. of luminaires in room

Reflection factors 70/50/20

Em(lx)	100		200		500	
Lh(m)	2.5	3.0	2.5	3.0	2.5	3.0
20 m²	1.4	1.7	2.9	3.3	7.2	8.3
30 m²	2.1	2.4	4.3	4.9	11	12
40 m²	2.7	3.1	5.5	6.1	14	15
50 m²	3.3	3.6	6.6	7.3	16	18
75 m²	4.8	5.2	9.6	10	24	26
100 m²	6.2	6.6	12	13	31	33
500 m²	28	29	56	58	140	144

Maintenance factor 0.8

Rh = Lh