


## Order No.: 5TS101A0Q | GTIN (EAN): 4039806907042

## Product description: Mod64,trunk.rail,1lg,L1495,10x2.52,wh




Modario® IP64, trunking rail, of sheet steel, galvanised, coated, pure white, 1-length, length: 1.495 mm, width: 58 mm, height: 43mm, through-wiring: 10x 2.5mm², with terminal, 10-pole, max. 2.5mm², protection rating (complete): for IP64 protection rating, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, standard: EN 60598, packaging unit: 1 piece



Wt. (kg): 2.4

GTIN (EAN): 4039806907042





## Order No.: 5TS101A0Q | GTIN (EAN): 4039806907042

## Detailed technical description: Mod64,trunk.rail,1lg,L1495,10x2.52,wh



#### Key data

- Product type: trunking components group (TS)
- Product name: Modario® IP64Order No.: 5TS101A0Q

# Lighting technology | Lamps | Control gear

#### **Component 1**

#### Lamps:

 Supplement: for electrical and mechanical plug and socket connection of rail elements

#### Certificates, Standards

- Protection rating: for IP64 protection rating
- Insulation class: insulation class I (protective earthing)
- Standard: EN 60598
- Certification, designation: CE, ENEC, VDE

#### Material, Colour

- trunking rail: sheet steel, galvanised, coated, pure white, 1-length
- Colour specification: pure white

### Mounting

- Mounting method, mounting location: suspended mounting, surfacemounted, to the ceiling
- Arrangement: single/continuous arrangement

#### **Electrical connection**

- Connection: terminal, 10-pole, max.
  2.5mm²
- Through-wiring: 10x 2.5mm²

## **Dimensions, Weight**

System units: 5x SELength: 1495mmWidth: 58mm

- Height: 43mm

- Mounting distance: max. 3.5m

- Weight: 2.4kg



## **Order No.:** 5TS101A0Q | **GTIN (EAN):** 4039806907042

Dimensions: Mod64,trunk.rail,1lg,L1495,10x2.52,wh

