Order No.: 5EA40EH01 | **GTIN (EAN):** 4058352450178

Product description: SConWi,SmartPlugMotionHigh

SITECO Connect WirelessSmart Plug Motion High, Smart Interface below, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, 2.4GHz, local mesh radio network, D4i, local setting and operation with USB stick, by daylight, by movement, manual, by time, by timer, by weekday, via API, optionally via radio push button, 1 PIR movement sensor, daylight sensor, temperature sensor, inclination sensor, PIR movement sensor, brightness sensor, radio, 2.4GHz, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 CE

Wt. (kg):	0.1
GTIN (EAN):	4058352450178

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 06.06.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

siteco

Order No.: 5EA40EH01 | **GTIN (EAN):** 4058352450178

Detailed technical description: SConWi,SmartPlugMotionHigh

Key data
- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40EH01

Lighting technology | Lamps | Control gear

Component 1

Operating device:
- Control: D4i, Smart Interface below

Certificates, Standards
- Protection rating: IP66
- Temperature range (operation): -40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

Material, Colour
- housing: plastic, transparent, colour-backed, dark grey
- Colour specification: dark grey

Mounting
- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 6..12m

Electrical connection
- Nominal voltage: 24V, DC

Dimensions, Weight
- Weight: 0.1kg

Inputs

PIR movement sensor
- Detection range: D max. 18m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 06.06.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

Order No.: 5EA40EH01 | **GTIN (EAN):** 4058352450178

Dimensions: SConWi,SmartPlugMotionHigh

Detection zone "Smart Plug Motion High"
5EA40EH01

Side view



Top view



Mounting height	X axis	Y axis
7.0 m	11.9 m	12.4 m
8.0 m	13.6 m	14.2 m
9.0 m	15.3 m	15.9 m
10.0 m	17.0 m	17.7 m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 06.06.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com