

Order No.: 5XA7680D1A00C | **GTIN (EAN):** 4058352233634

Product description: FL20md,LED-unit,PL43,830,142W



Floodlight FL 20 midi, LED unit, primary light control with lens, of plastic, primary optical cover: cover panel, of toughened safety glass, transparent, light distribution: PL43, light emission: direct distribution, primary light characteristic: asymmetric, installation type: screw fastening, LED, High Power LED, light colour: 830, colour temperature: 3000K, with cable with plug, mains connection: 220..240V, AC, 50/60Hz, rated input power: 142W, LED unit, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 402mm, width: 421mm, height: 57mm, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 CE

Lamps:	LED
Wt. (kg):	5.5
GTIN (EAN):	4058352233634

Order No.: 5XA7680D1A00C | **GTIN (EAN):** 4058352233634

Detailed technical description: FL20md,LED-unit,PL43,830,142W



Key data

- Product type: LED unit
- Product name: Floodlight FL 20 midi
- Order No.: 5XA7680D1A00C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of plastic
- Cover: cover panel, transparent
- Light distribution: PL43
- Symmetry: asymmetric distribution
- Light emission: direct distribution

Lamps:

- Lamps: High Power LED, LED
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830
- Rated input power: 142W

Certificates, Standards

- Protection rating: IP66
- Certification, designation: CE

Material, Colour

- LED unit: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S)
- Colour specification: Siteco® metallic grey (DB 702S)
- Cover: cover panel of toughened safety glass

Mounting

- Mounting method, mounting location: screw fastening, in housing

Electrical connection

- Connection: cable with plug
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 402mm
- Width: 421mm
- Height: 57mm
- Weight: 5.5kg