

Order No.: 5LZ902050TW | GTIN (EAN): 4058352145807


Product description: SCon41Rotrot.dimmm,rot/push-bttn,rec



SITECO Connect 41 Rotaryrotary dimmer, Touchdim, local control, dimmable, installation type: recessed, installation location: in the switch box, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, voltage: 230V, voltage type: AC, 1 x rotary button/push button, 1 x DALI, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.1
GTIN (EAN): 4058352145807



Order No.: 5LZ902050TW | GTIN (EAN): 4058352145807

Detailed technical description: SCon41Rotrot.dimm,rot/push-bttm,rec



Key data

- System family: DALI
- Product type: rotary dimmer
- Product name: SITECO Connect 41 Rotary
- Order No.: 5LZ902050TW

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -5..+45°C
- Certification, designation: CE

Material, Colour

- installation housing: plastic, grey
- Colour specification: grey

Mounting

- Mounting method, mounting location: recessed, in the switch box
- Supplement: only for mounting indoors

Electrical connection

- Nominal voltage: 230V, 50/60Hz, AC

Dimensions, Weight

- Length: 80mm
- Width: 80mm
- Height: 32mm
- Weight: 0.1kg

Inputs

1x rotary button/push button

- Connection: screw terminal, 2-pole, max. 4.0mm²



Outputs

1x DALI

- Connection: screw terminal, 2-pole, max. 4mm²
- Limiting: max. 25x ECG DALI
- Feature: ON/OFF, bright/dark, storing of brightness power on illumination levels, expansion of control units or number of ECG DALI via parallel switching of several rotary potentiometers; incl. rotary button and frame of white plastic
- Cable length: max. 300m

Order No.: 5LZ902050TW | GTIN (EAN): 4058352145807

Dimensions: SCon41Rotrot.dimmm,rot/push-bttn,rec



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 05.01.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -