

Order No.: 5EA40M000201 | GTIN (EAN): 4058352408490

Product description: SConWi, Motion2PIR





SITECO Connect WirelessMotion 2PIR, sensor, communication: D4i type B, control: by daylight, by movement, sensor technology: 2 PIR movement sensors, daylight sensor, mandatory accessory: Smart Plug Standard 5EA3AM000001, Smart Plug Cellular 5EA3CM000001 or Smart Plug Casambi 5EA3TDC01, installation type: screw fastening, installation location: to the luminaire, of PBT, voltage: 24V, voltage type: DC, 2 x PIR movement sensor, 1 x protection rating (complete): IP66, certification: CE, UKCA, packaging unit: 1 piece

IP 66 IK 08 (€

Wt. (kg): 0.1

GTIN (EAN): 4058352408490



Order No.: 5EA40M000201 | GTIN (EAN): 4058352408490

Detailed technical description: SConWi, Motion 2PIR



Key data

- System family: SITECO Connect 31 Wireless
- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40M000201

Lighting technology | Lamps | Control gear

Component 1

Operating device:

Control: D4i, mandatory accessory:
Smart Plug Standard 5EA3AM000001,
Smart Plug Cellular 5EA3CM000001 or
Smart Plug Casambi 5EA3TDC01

Certificates, Standards

- Protection rating: IP66
- Impact resistance: IK08
- Temperature range (operation): -25..+50°C
- Standard: according to Zhaga book 18
- Certification, designation: CE, UKCA

Material, Colour

- housing: PBT, grey
- Colour specification: grey

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 4..8m

Electrical connection

- Nominal voltage: 24V, DC

Dimensions, Weight

Diameter: 46mmHeight: 57mmWeight: 0.1kg

Inputs

2x PIR movement sensor

- Detection range: max. 35x16m




Order No.: 5EA40M000201 | GTIN (EAN): 4058352408490

Dimensions: SConWi, Motion 2PIR

Detection zone "Motion 2 PIR" 5EA40M000201

Xaxis →



| Mounting height | X axis | Y axis |
|-----------------|--------|--------|
| 4.0 m | 17.0 m | 8.0 m |
| 5.0 m | 21.5 m | 10.0 m |
| 6.0 m | 26.0 m | 12.0 m |
| 7.0 m | 30.5 m | 14.0 m |
| 8.0 m | 35.0 m | 16.0 m |

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -