

Order No.: 59LJ203 | GTIN (EAN): 4058352612422 Product description: Ecop31emerg.lght.elem,rec

Ecopack[®] 31, emergency light element, installation type: recessed, EM-KIT 3h,battery: LiFeP04, 3Ah, housing, of steel, silver, incl. screws, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, impact resistance: IK02, permissible operating ambient temperature: 0..+50°C, packaging unit: 1 piece

IP 20 🗌 🤆

Wt. (kg): 0.3 GTIN (EAN): 4058352612422

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 07.07.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -



Order No.: 59LJ203 | GTIN (EAN): 4058352612422 Detailed technical description: Ecop31emerg.lght.elem,rec

Key data

- Product type: emergency light element
- Product name: Ecopack[®] 31
- Order No.: 59LJ203

Lighting technology | Lamps | Control gear

Component 2

Operating device:

- Battery: LiFeP04

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK02
- Temperature range (operation): 0..+50°C
- Certification, designation: CE

Material, Colour

- housing: steel, silver, incl. screws
- Colour specification: silver

Mounting

 Mounting method, mounting location: recessed, in the luminaire

Dimensions, Weight

- Weight: 0.3kg

Service life

Rated service life: 30000h at AT = 25°C

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 07.07.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -