

Order No.: 5LS44301EK | **GTIN (EAN):** 4039806171436 **Product description:** Mon21G1,TW,3x1.5²,L1.4m,term,3x2.5²



Monsun[®] 21 Gen.1, through-wiring, installation type: recessed, through-wiring set,3-core, 1.5mm², cable length: 1,4m, terminal,3-pole, max. 2.5mm², with protective earth, insulation class (complete): insulation class I (protective earthing), packaging unit: 1 piece

Wt. (kg): 0.1 GTIN (EAN): 4039806171436

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 24.02.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 5LS44301EK | GTIN (EAN): 4039806171436 Detailed technical description: Mon21G1,TW,3x1.5²,L1.4m,term,3x2.5²



Key data

- Product type: through-wiring
- Product name: Monsun® 21 Gen.1
- Order No.: 5LS44301EK

Lighting technology | Lamps | Control gear

Component 1

Lamps:

 Supplement: for through-wiring within a luminaire, through-wiring set includes heat-resistant single-core cable, terminals and mounting hardware

Certificates, Standards

 Insulation class: insulation class I (protective earthing)

Mounting

- Mounting method, mounting location: recessed, in the luminaire
- Arrangement: interrupted trunking
- Supplement: wiring from one luminaire to the next is with standard cable (e.g. NYM)

Dimensions, Weight

- Weight: 0.1kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 24.02.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -