

Order No.: 5EA40EL01 | **GTIN (EAN):** 4058352450208

Product description: SConWi,SmartPlugMotionLow



SITECO Connect WirelessSmart Plug Motion Low, sensor, communication: 2.4GHz, local mesh radio network, D4i type A, control: local setting and operation with USB stick, by daylight, by movement, manual, by time, by timer, by weekday, via API, optionally via radio push button, sensor technology: 1 PIR movement sensor, daylight sensor, temperature sensor, inclination sensor, Logarithmic DALI dimming curve preset. Can be switched to linear via software, Smart Interface below, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, PIR movement sensor, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 CE

Wt. (kg): 0.1
GTIN (EAN): 4058352450208

Order No.: 5EA40EL01 | **GTIN (EAN):** 4058352450208

Detailed technical description: SConWi,SmartPlugMotionLow



Key data

- System family: SITECO Connect 31 Wireless
- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40EL01

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: D4i, Smart Interface below, Logarithmic DALI dimming curve preset. Can be switched to linear via software

Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

Material, Colour

- housing: plastic, transparent, colour-backed, transparent
- Colour specification: transparent

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 0..6m

Electrical connection

- Nominal voltage: 24V, DC

Dimensions, Weight

- Weight: 0.1kg

Inputs

PIR movement sensor


- Detection range: max. ø11m

Order No.: 5EA40EL01 | GTIN (EAN): 4058352450208


Dimensions: SConWi,SmartPlugMotionLow

Detection zone "Smart Plug Motion Low"
5EA40EL01

Side view



Top view



Mounting height	X axis	Y axis
5.0 m	8.5 m	8.8 m
6.0 m	10.2 m	10.6 m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -