

Order No.: 51TR6J7 | GTIN (EAN): 4058352242599 Product description: Lic,trunk.rail,L4500,7x2.52,sr



Licross®, trunking rail, of sheet steel, galvanised, coil coated, metallic grey (RAL 9006), length: 4.500 mm, width: 64 mm, height: 67mm, through-wiring: 7x 2.5mm², protection rating (complete): maximum IP64, depends on used inserts and accessories, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, LABS conformity tested according to VDMA 24364:2018-05, packaging unit: 1 piece



Wt. (kg): 6.9

GTIN (EAN): 4058352242599





Order No.: 51TR6J7 | GTIN (EAN): 4058352242599

Detailed technical description: Lic,trunk.rail,L4500,7x2.5²,sr



Key data

- Product type: trunking components group (TS)
- Product name: Licross®Order No.: 51TR6J7

Lighting technology | Lamps | Control gear

Component 1

Lamps:

 Supplement: internal wiring halogenfree

Certificates, Standards

- Protection rating: maximum IP64, depends on used inserts and accessories
- Insulation class: insulation class I (protective earthing)
- Supplement: LABS conformity tested according to VDMA 24364:2018-05
- Certification, designation: CE, UKCA

Material, Colour

- trunking rail: sheet steel, galvanised, coil coated, metallic grey (RAL 9006)
- Colour specification: metallic grey (RAL 9006)

Mounting

- Mounting method, mounting location: suspended mounting, surfacemounted, to the ceiling
- Arrangement: single/continuous arrangement
- Supplement: only suitable for use in indoor areas

Electrical connection

Through-wiring: 7x 2.5mm²

Dimensions, Weight

Length: 4500mmWidth: 64mmHeight: 67mmWeight: 6.9kg



Order No.: 51TR6J7 | GTIN (EAN): 4058352242599

Dimensions: Lic,trunk.rail,L4500,7x2.5²,sr

