

**Order No.:** 5LZ980100 | **GTIN (EAN):** 4058352398517

**Product description:** SConWi,psh.btn.interf,locCtrl,pushb.inp



SITECO Connect Wireless push button interface, lighting management components, slave, local control - self-sufficient standalone sensors, dimmable, installation type: recessed, installation location: in the switch box, voltage: 230V, 4 x push button input, 1 x Bluetooth® interface, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.1  
GTIN (EAN): 4058352398517

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

**Order No.:** 5LZ980100 | **GTIN (EAN):** 4058352398517

**Detailed technical description:** SConWi,psh.bttb.interf,locCtrl,pushb.inp



## Key data

- System family: SITECO Connect 31 Wireless
- Product type: lighting management components
- Product name: SITECO Connect Wireless
- Order No.: 5LZ980100

## Lighting technology | Lamps | Control gear

### Component 1

#### Operating device:

- Control: Bluetooth® Mesh 4.2, dimmable

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): 0..+55°C
- Certification, designation: CE

#### Mounting

- Mounting method, mounting location: recessed, in the switch box
- Supplement: only suitable for use in indoor areas

#### Electrical connection

- Nominal voltage: 230V

#### Dimensions, Weight

- Weight: 0.1kg

#### Outputs

##### 1x Bluetooth® interface

- Feature: operating frequency 2.4..2.483GHz, +4dBm