

Order No.: 5LS90800ED | **GTIN (EAN):** 4039806166531

Product description: DUSIP60,bl-ins,sh.steel,wh



DUS® IP60, blank insert, of sheet steel, coated, pure white, length: 1.535mm, width: 60mm, height: 45mm, system units: 307mm, for manufacturing hall, retail areas, ancillary rooms, corridors and circulation routes, office, protection rating (complete): IP20 / IP60, insulation class (complete): insulation class I (protective earthing), IP60 for complete trunking system achieved in combination with suitable IP60 components, packaging unit: 1 piece

IP 20 IP 60 

Wt. (kg): 0.8
GTIN (EAN): 4039806166531

Order No.: 5LS90800ED | GTIN (EAN): 4039806166531

Detailed technical description: DUSIP60,bl-ins,sh.steel,wh



Key data

- Product type: blank insert
- Product name: DUS® IP60
- Order No.: 5LS90800ED

Certificates, Standards

- Protection rating: IP20 / IP60
- Insulation class: insulation class I (protective earthing)
- Supplement: IP60 for complete trunking system achieved in combination with suitable IP60 components

Material, Colour

- blank insert: sheet steel, coated, pure white
- Colour specification: pure white

Dimensions, Weight

- System units: 5x SE
- Length: 1535mm
- Width: 60mm
- Height: 45mm
- Weight: 0.8kg