

Order No.: 5LZ980301 | GTIN (EAN): 4058352398593


Product description: SConWi,controller,lokCtrl,1,switch



SITECO Connect Wirelesscontroller, master, local control, dimmable, installation type: lay-in mounting, installation location: in the ceiling, voltage: 230V, 1 x DALI, 1 x Bluetooth® interface, 1 x switching contact, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.2
GTIN (EAN): 4058352398593



Order No.: 5LZ980301 | GTIN (EAN): 4058352398593

Detailed technical description: SConWi,controller,lokCtrl,1,switch



Key data

- System family: SITECO Connect 31 Wireless
- Product type: lighting management components
- Product name: SITECO Connect Wireless
- Order No.: 5LZ980301

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: Bluetooth® mesh 4.2, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+40°C
- Certification, designation: CE

Mounting

- Mounting method, mounting location: lay-in mounting, in the ceiling
- Supplement: only suitable for indoor use

Electrical connection

- Nominal voltage: 230V

Dimensions, Weight

- Weight: 0.2kg

Outputs

1x DALI

- Limiting: maximum 2x ECG DALI or 2x ECG DALI DT8 and 1 sensor PS3 DALI2 controllable

1x Bluetooth® interface

- Feature: operating frequency 2.4..2.483GHz, +4dBm

1x switching contact

- Feature: number of ECG's depends of the ECG type

Order No.: 5LZ980301 | GTIN (EAN): 4058352398593

Dimensions: SConWi,controller,lokCtrl,1,switch

