

Order No.: 56TL3MDSPC3A | GTIN (EAN): 4058352407639

Product description: Licsens, PIR-sens







Licross®sensor module PC3-S, slave, central control - connection to lighting or building management, dimmable, installation location: to the Licross® trunking rail, of sheet steel, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, 1 x PIR movement sensor, 1 x light sensor, 1 x DALI-2, packaging unit: 1 piece

IP 20 ⊕ (∈

Wt. (kg): 0.3

GTIN (EAN): 4058352407639



# Order No.: 56TL3MDSPC3A | GTIN (EAN): 4058352407639

## **Detailed technical description:** Licsens, PIR-sens



#### Key data

 System family: Siteco Connect 11, SITECO Connect 22

Product type: sensorProduct name: Licross®Order No.: 56TL3MDSPC3A

# Lighting technology | Lamps | Control gear

#### **Component 1**

#### Lamps:

 Supplement: internal wiring halogenfree

#### Operating device:

Control: DALI 2, dimmable

## Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): 0..+40°C
- Certification, designation: CE, UKCA

#### Material, Colour

- sensor module: sheet steel, coil coated, black
- Colour specification: black

#### Mounting

- Mounting height: 2.5..5m
- Supplement: only suitable for use in indoor areas

#### **Dimensions, Weight**

Length: 300mmWidth: 66mmHeight: 71mmWeight: 0.3kg

#### Inputs

### 1x PIR movement sensor

- Connection: PIR sensor (passiveinfrared)
- Detection range: tangential max. 4x5m
- Detection range: max. 2x 2m

#### 1x light sensor

- Illuminance: 2..1000lx

#### **Outputs**

#### 1x DALI-2


 Feature: DALI, slave function, DALI current max. 6mA


It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -



Order No.: 56TL3MDSPC3A | GTIN (EAN): 4058352407639

**Dimensions:** Licsens, PIR-sens





## Sensor PS3

Mh	R	Т	Р
2,8m	4x4m	ca. 4x5m	ca. 2x2m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -