

Order No.: 5EA40LL01 | GTIN (EAN): 4058352449974

Product description: SConWi,MotionLow



SITECO Connect WirelessMotion Low, Smart Interface below, setting of the ECG to logarithmic DALI dimming required, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, Bluetooth, D4i, local setting and operation with smartphone app, by daylight, by movement, 1 PIR movement sensor, daylight sensor, PIR movement sensor, protection rating (complete): IP66, certification: CE, UKCA, packaging unit: 1 piece

IP 66 IK 09 CE

Wt. (kg): 0.1
GTIN (EAN): 4058352449974

Order No.: 5EA40LL01 | GTIN (EAN): 4058352449974

Detailed technical description: SConWi,MotionLow



Key data

- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40LL01

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: D4i, Smart Interface below, setting of the ECG to logarithmic DALI dimming required

Certificates, Standards

- Protection rating: IP66
- Impact resistance: IK09
- Temperature range (operation): -40..+70°C
- Standard: according to Zhaga book 18
- Certification, designation: CE, UKCA

Material, Colour

- housing: plastic, grey
- Colour specification: grey

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: max. 4.5m

Electrical connection

- Nominal voltage: 24V, DC

Dimensions, Weight

- Weight: 0.1kg

Inputs

PIR movement sensor

- Detection range: D max. 15m
- Feature: incl. shield for reducing detection area

Order No.: 5EA40LL01

Dimensions: SConWi, Motion

Y axis



Mounting height

2.4 m

X axis

6.0 m

Y axis

6.0 m